GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2021/30

Dated: 20/01/2021

FIRE SAFETY CERTIFICATE

Delhi comprised of Ground + 03 Upper floor (29 guest rooms), Ground floor (reception + lounge and other shops), 1st floor (09 Guest Room), 2nd Floor (11 guest room) and 3rd floor (09 Guest Room) was granted FSC by this department vide letter No.F6/DFS/MS/GH/2017/NDZ/750 dated 25/05/2017. The premise was re-inspected by the officer concerned of this department on 14/01/21 in the presence of Mr. Sohib Alam and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 29 guest rooms only with effect from 20/01/2021—for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 20/01/2021 at New Delhi by.

(Dr.S.K. Tomar) Dy. Chief Fire Officer Delhi Fire Service

0×10mm/

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. Online ID no; 2021010509412 dated 08/01/2021.
- 2. The Manager, HERITAGE HOME located at 1603-04, Main Bazar, Pahar Ganj, New Delhi Condition for the validity of fire safety certificate
 - 1. This clearance/ FSC shall stand canceled if guest house owner/occupier fails to comply all other condition mentioned in the gazette notification dated 27.05.2019 & clarification issued dated on 25.09.2019 & 17.12.2020 latest by 31.03.2021

2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

4. The trained fire fighting staff should be available round the clock.

5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. Any flammable material for interior decoration is prohibited.

INSPECTION REPORT

1. Name & address of the building HERITAGE HOME located at 1603-04,

Main Bazar, Pahar Ganj, New Delhi. 2. Type of occupancy:-Residential, Group A-1 Ground +3

upper Floor (29 guest rooms)Ground floor (reception + lounge and other shops) 1st floor (09 Guest Room), 2nd Floor(11 guest room) and

3rd floor (09 Guest Room)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2017/NDZ/750 dated

25/05/2017.

5. Fire safety directives No.-

N/A 6. Date of inspection:-14/01/21

7. Name of the inspecting officer:-

Sh. Ravinder Singh (ADO/CC) Sh. Rajinder Atwal (DO/CC)

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Sh. Sohib Alam

2021010509412 dated 08/01/2021.

Old Case S.No. Minimum Standards on fire Requirement/ Provided at site Remarks Existing fire safety Prevention and fire safety MR/NMR arrangements U/R 33 1. Access to Building 1) Road width N/A 09 mtr. N/A 2) Gate width N/A N/A N/A 3) Width of internal road N/A N/A N/A 2. Number, Width Type & Arrangement of Exits A. Number of staircases 1. Upper floors 01 Nos. 01 Nos. MR 2. Basements N/A N/A N/A B. Width of staircase 1. Upper floors 1.5mtr 1.5 mtr MR 2. Basements N/A N/A N/A C. Protection of exits 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous 01 01 MR staircase to terrace E. Width of corridor N/A N/A N/A F. Door size 1.0 mtr. 1.0 mtr. MR 3. Compartmentation 1) Fire check door N/A N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers N/A N/A N/A 4. Smoke Management System 1) Basements N/A N/A N/A 2) Upper floors 12 a/c per Natural MR



	*			
		hour		
5.	Fire Extinguishers			
	1) Total numbers	10 Nos.	10 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel	- Troquitou	TTOVIGEG	IVIIC
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	Provided	MR
	3) Nozzle diameter	05 mm	Provided	MR
7.	Automatic Fire Detection &			IVIIC
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required N	10 SOURT 100	MR ND
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	Required	TTOVIGEG	IVIK
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	IN/A	IN/A	IN/A
11.	Internal Hydrants			
11.	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	14/71	I W/ PK	IN/A
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants	1 1/7 1	1 1/11	1 1 1 1
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement	14/71	14/11	1,477
13.	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump	IN/A	IN/A	IN/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
		N/A	N/A	N/A
	g) Stand by pump head h) Auto starting/Manual	N/A	N/A	N/A
	stopping	1 1/7	INIA	1 1/2 2
	2) Terrace level			
	,	450 LPM	450 LPM	MR
	a) Discharge of pump	30 mtr.	30 mtr.	MR
	b) Head of pump	Required	Provided	MR
	c) Power supply		Provided	MR
	d) Auto starting of pump	Required	TTOVIUCU	IVIIC



14.	Captive Water Storage for Fire Fighting					
	1) Under ground tank capacity	N/A	N/A	N/A		
	a) Draw-off connection	N/A	N/A	N/A		
	b) Fire service inlet	N/A	N/A	N/A		
	c) Access to tank	N/A	N/A	N/A		
	d) Over head tank capacity	5,000 ltr.	Provided	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.		,	-		
	a) Pressurization of lift shaft	N/A	N/A	N/A		
	b) Pressurization of lift lobby	N/A	N/A	N/A		
	c) Communication in lift car	N/A	N/A	N/A		
	d) Fireman's switch	N/A	N/A	N/A		
	e) Lift signage	N/A	N/A	N/A		
17.	Stand by Power Supply	Required	Provided	MR		
18.	Refuge Area	N/A	N/A	N/A		
	Total area location	N/A	N/A	N/A		
19.	Fire Control Room	N/A	N/A	N/A		
	a) Detector system panel	N/A	N/A	N/A		
	b) Flow switch panel	N/A	N/A	N/A		
	c) PA system panel	N/A	N/A	N/A		
	d) Battery backup	N/A	N/A	N/A		
v	e) Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Moreover, Fire check door & CO detector as required as per Gazette notification dated 27.05.2019 is not checked as same are exempted till 31.03.2021 by govt. clarification letter dated 17.12. 2020.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/ GH/ 2017/ NDZ /750 dated 25/05/2017, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Sh. Rajinder Atwal Designation :- DO (CD)

Name :- Sh. Rayinder Singh Designation: ADO (CC)

Pl. Apeak about Pt no. P. Pl. nee H/2

Correction made as directed