## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2021/ | 6

Dated (8./1../2021

## FIRE SAFETY CERTIFICATE

Certified that the M/s My Bar Headquaeters (A Unit of Sransh Traders Pvt. Ltd.) located at N-49, 2<sup>nd</sup> Floor, Connaught Place, New Delhi comprises of Ground + Mezzanine + 02 Upper floor, Restaurant running at 2<sup>nd</sup> floor only owned/occupied by M/s My Bar Headquaeters (A Unit of Sransh Traders Pvt. Ltd.) was granted FSC by this department vide letter No.F6/DFS/MS/EH/NDZ/2018/1050 dated 14/05/18. The premises was re-inspected by the officer concerned of this department on 12/01/21 in the presence of Mr. Gurvinder Singh (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building, Group-D of Sub-Division D-5 Restaurant at 2<sup>nd</sup> floor only with effect from floor period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued Rew Delhi by.

(Dr. S.K. Tomar)

Dy. Chief Fire officer Delhi Fire Service

Copy to:-

- m 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Delhi. Id No. 2020122109124 dated 21/12/2020
- 2. The Manager,

M/s My Bar Headquaeters (A Unit of Sransh Traders Pvt. Ltd.), N-49, 2<sup>nd</sup> Floor, Connaught Place, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Inflammable material, if any for interior decoration, shall strictly be prohibited.

**INSPECTION REPORT** 1. Name & address of the building M/s My Bar Headquaeters (A Unit of Sransh Traders Pvt. Ltd.) located at N-49, 2<sup>nd</sup> Floor, Connaught Place, New Delhi Assembly Building Group-D 2. Type of occupancy:-Ground + Mezzanine + 02 Upper floor Restaurant running at 2nd floor only 3. Type of case:-4. Details of previous FSC:-F6/DFS/MS/EH/NDZ/2018/1050 dated 14/05/18. N/A 5. Fire safety directives No.-6. Date of inspection:-12/01/21 Sh. Ravinder Singh(ADO/CC) 7. Name of the inspecting officer:-Sh. Rajinder Atwal (DO/CC) 8. Name & designation of officer Mr. Gurvinder Singh (Manager) from the building side:-Old Heritage Bldg. 9. Year of construction:-2020122109124 dated 21/12/2020 10. Applicant's letter No:-

|       |  |  |                                | Old case          |
|-------|--|--|--------------------------------|-------------------|
| S.No. | Minimum Standards on fire<br>Prevention and fire safety U/R 33 | Requirement/<br>Existing fire safety<br>arrangements | Provided at site               | Remarks<br>MR/NMR |
| 1.    | Access to Building   |  |                                |                   |
|       | 1) Road width  | 09 mtr   | 12 mtr.                        | MR                |
|       | 2) Gate width  | N/A  | N/A                            | N/A               |
|       | 3)Width of internal road                                       | N/A  | N/A                            | N/A               |
| 2.    | Number, Width Type & Arra                                      | angement of Ex                                       | its                            |                   |
|       | A. Number of staircases  |  |                                | 0                 |
|       | 1. Upper floors  | 02 No.   | 03 No.                         | MR                |
|       | 2. Basements   | N/A  | N/A                            | N/A               |
|       | B. Width of staircase  |  |                                |                   |
|       | 1. Upper floors  | 1.5 mtr.   | 1.50 mtr., & 02 Nos. 1.20 mtr. | Old case          |
|       | 2. Basements   | N/A  | N/A                            | N/A               |
|       | C. Protection of exits   | N/A  | N/A                            | N/A               |
|       | 1. Fire check door   | N/A  | N/A                            | N/A               |
|       | 2. Pressurization  | N/A  | N/A                            | N/A               |
|       | D. No. of continuous   | 01   | 01                             | MR                |
|       | staircase to terrace   |  | 8                              | 271               |
|       | E. Width of corridor   | N/A  | N/A                            | N/A               |
|       | F. Door size   | 02 mtr.  | 02 mtr.                        | MR                |
| 3.    | Compartmentation   |  |                                |                   |
|       | 1) Fire check door   | N/A  | N/A                            | N/A               |
|       | 2) Sealing of electrical shafts                                | N/A  | N/A                            | N/A               |
|       | 3) Fire rating of shaft door                                   | N/A  | N/A                            | N/A               |
|       | 4) Water curtain   | N/A  | N/A                            | N/A               |
|       | 5) Fire Dampers  | N/A  | N/A                            | N/A               |
| 4.    | Smoke Management System  | l .  |                                | 1                 |
|       | 1) Basements   | 30 ACPH  | N/A                            | N/A               |
|       | 2) Upper floors  | 12 ACPH  | Natural                        | MR                |
| 5.    | Fire Extinguishers   | MD   |                                |                   |
|       | 1) Total numbers   | 08 Nos.  | 08 Nos.                        | MR                |
|       | 2) Types   | ABC & CO2  | ABC & CO2                      | MR                |

|     | NIC                             |                   |                           | - Francis                 |     |                  |
|-----|---------------------------------|-------------------|---------------------------|---------------------------|-----|------------------|
|     | 3) ISI marking                  |                   | equired                   | Provided                  | N   | 1R               |
|     |                                 |                   | •                         |                           |     |                  |
| 6   | First-Aid Hose Reel             |                   |                           |                           |     |                  |
| 6.  | 1) Total number of eachfloor    | 01                |                           | 01                        | 1   | 1R               |
|     | 2) Length of hose reel hose     | -                 | mtr.                      | 30 mtr.                   |     | AR<br>AR         |
|     | 3) Nozzle diameter              | -                 | mm                        | 05 mm                     |     | AR AR            |
| 7.  | Automatic Fire Detection &      |                   |                           |                           | 1\  | /IK              |
| 7.  | 1) Type of detectors            |                   |                           | Provided                  | Λ   | 1/R              |
|     | 2) Location of main panel       | Required Required |                           | Provided                  |     | AR<br>AR         |
|     | 3) Location of repeater panel   | Required          |                           | Provided                  |     | AR AR            |
|     | 4) Alternate source of power    | 1                 |                           | Provided                  |     | AR<br>AR         |
|     | 5) Hooter's Location            | Required          |                           |                           |     | J/A              |
|     |                                 | N/A               |                           | N/A                       |     |                  |
| 3.  | MOEFA                           |                   | equired                   | Provided                  |     | <u>AR</u>        |
| 9.  | Public Address System           | N/                | A                         | N/A                       | I   | J/A              |
| 10. | Automatic Sprinkler System      |                   | / *                       | NT/A                      |     | T / A            |
|     | 1) Basement                     | N/                |                           | N/A                       |     | J/A              |
|     | 2) Ground floors                | N/                |                           | Provided                  |     | J/A              |
|     | 3) Sprinkler above false        | N/                | Α                         | N/A                       | Γ   | J/A              |
| 11  | ceiling                         | 1                 |                           |                           |     |                  |
| 11. | Internal Hydrants               | 10                | 00 mm                     | 100 mm                    | 1   | ⁄IR              |
|     | 1) Size of riser/down-comer     | 01                |                           | 01                        |     | AR<br>AR         |
|     | 2) Number of hydrants per floor | 01                |                           | 01                        | 11  | /IK              |
|     | 3) Hose box                     | 01                |                           | 01                        | N   | /IR              |
| 12  | Yard Hydrants                   | 01                |                           | 01                        | 1   | /IIX             |
| 12. | 1) Total number of hydrants     | N/                | / ^                       | N/A                       | N   | J/A              |
|     | 2) Hose box                     | N/                |                           | N/A                       |     | J/A              |
| 13. | Pumping Arrangement             | 1 47              |                           | 14/11                     | 1   | 1/21             |
| 13. | 1) Ground level                 |                   |                           |                           | -   |                  |
|     | a) Discharge of main            |                   | N/A                       | N/A                       |     | N/A              |
|     | - 1857.                         |                   | IV/A                      | 14/71                     | -   | 14/11            |
|     | b) Head of main pump            |                   | N/A                       | N/A                       |     | N/A              |
|     | c) Number of main pun           |                   | N/A                       | N/A                       |     | N/A              |
|     | d) Jockey pump out pu           |                   | N/A                       | N/A                       |     | N/A              |
|     | e) Jockey pump head             |                   | N/A                       | N/A                       |     | N/A              |
|     | f) Stand by pump outp           | nit               | N/A                       | N/A                       |     | N/A              |
|     | g) Stand by pump head           |                   | N/A                       | N/A                       |     | N/A              |
|     | h) Auto starting/Manu           |                   | N/A                       | N/A                       |     | N/A              |
|     | stopping                        | ш                 | 1 1/2 %                   | 11/12                     |     |                  |
|     | 2) Terrace level                |                   |                           |                           |     |                  |
|     | a) Discharge of pump            |                   | 450 LPM                   | 450 & 280                 | LPM | MR               |
|     | b) Head of pump                 |                   | 40 mtr.                   | 40 mtr.                   |     | MR               |
|     | c) Power supply                 |                   | Required                  | Provided                  |     | MR               |
|     | d) Auto starting of pur         | nn                | Required                  | Provided                  |     | MR               |
| 14. | Captive Water Storage fo        | r Fi              |                           |                           |     |                  |
| 14. | 1) Under ground tank            |                   | N/A                       | N/A                       |     | N/A              |
|     | capacity                        |                   | - N - A                   |                           | - 8 | 2 12 8           |
| 1   |                                 | n                 | N/A                       | N/A                       |     | N/A              |
|     | a) Draw-off connection          | 4.4               | A 1/ A A                  | - "                       |     |                  |
|     | a) Draw-off connection          |                   | N/A                       | N/A                       |     | N/A              |
|     | b) Fire service inlet           |                   | N/A<br>N/A                | N/A<br>N/A                |     |                  |
|     |                                 |                   | N/A<br>N/A<br>10,000 ltr. | N/A<br>N/A<br>10,000 ltr. |     | N/A<br>N/A<br>MR |

| 15. | Exit Signage.   | Required | Provided | MR  |
|-----|---|----------|----------|-----|
| 16. | Provision of Lifts.                                     |          |          |     |
|     | a) Pressurization of lift shaft                         | N/A      | N/A      | N/A |
|     | b) Pressurization of lift lobby                         | N/A      | N/A      | N/A |
|     | c) Communication in lift car                            | N/A      | N/A      | N/A |
|     | d) Fireman's switch                                     | N/A      | N/A      | N/A |
|     | e) Lift signage   | N/A      | N/A      | N/A |
| 17. | Stand by Power Supply                                   | N/A      | Provided | N/A |
| 18. | Refuge Area   | N/A      | N/A      | N/A |
| •   | Total area location                                     | N/A      | N/A      | N/A |
| 19. | Fire Control Room                                       | N/A      | N/A      | N/A |
|     | a) Detector system panel                                | N/A      | N/A      | N/A |
|     | b) Flow switch panel                                    | N/A      | N/A      | N/A |
|     | c) PA system panel                                      | N/A      | N/A      | N/A |
|     | d) Battery backup                                       | N/A      | N/A      | N/A |
|     | e) Building floor plan                                  | N/A      | N/A      | N/A |
| 20. | Special Fire Protection Syst<br>Risk, if any: ABC & Co2 | MR       |          |     |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter F6/DFS/MS/EH/NDZ/2018/1050 dated 14/05/18 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Rajinder Atwal Designation :- DO (CD) Name: - Ravinder Singh

Designation: - ADO (CC)

As approved, Fr i pertrip for Knd Peeus and