## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/CGHS/NDZ/2021/ 62

Dated: 35.01.2021

## FIRE SAFETY CERTIFICATE

(**Dr. S.K Tomar**)
Dy. Chief Fire Officer
Delhi Fire Service

02 Jamy 2571/21

## Copy to:-

- The Dy. Health Officer, EDMC(Health Deptt.), Shadhra Zone, Karkardooma, Shadhra, Delhi.
- 2. Sh. Satish Kapoor, M/s S.K Eastend Party Hall, Star city Mall, Mayur Vihar-1, Delhi-92.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INICI	ECTION DED	DET N					
1	Nome & address of the building Mark Fort Fort Park H. H. Phys. 14							
1.	Name & address of the building M/s S.K. East End Party Hall, Plt No. 1 A,							
	Grade Level, Star City Mall, Mayur Vihar- 1, Delhi – 110092.							
2.	Type of occupancy:-							
2.	Type of occupancy.	Assembly Building (Community Hall) (Ground floor Only)						
3.	Type of case:-	Renewal	oor Omy)					
1	Details of previous FSC:- F6/DFS/MS/GH/NDZ/2017/1565 dated							
	03/11/17							
5.	Fire safety directives No F6/DFS/MS/2011/2167 dated 06/09/11							
6.	Date of inspection:-	19/01/2020						
7.	7. Name of the inspecting officer:- Sh. Francis Brown (DO/ED) &							
	Sh. Manoj Kumar Sharma (ADO/LN)							
8.	8. Name & designation of officer							
	From the building side:-		em (Manager)					
	Year of construction:-	2006						
	Applicant's letter No:-		d 13/01/2021					
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement NBC Part-IV/	Provided at site	Remarks				
	Trevention and the safety 6/10 55	BBL		MR/NMR				
1.	Access to Building							
	1) Road width	06 mtr.	06 mtr.	MR				
	2) Gate width	N/A	06 mtr.	MR				
	3)Width of internal road	N/A	N/A	N/A				
2.	Number, Width Type & Arrangement of Exits							
	A. Number of staircases			* 3				
	1. Upper floors	N/A	N/A	N/A				
	2. Basements	N/A	N/A	N/A				
	B. Width of staircase							
	1. Upper floors	N/A	N/A	N/A				
	2. Basements	N/A	N/A	N/A				
	C. Protection of exits							
	1. Fire check door	Required	Provided	MR				
	2. Pressurization	N/A	N/A	N/A				
	D. No. of continuous staircase	N/A	N/A	N/A				
	to terrace	02	00					
	E. Width of corridor F. Door size	02 mtr.	02 mtr.	MR				
3.	Compartmentation	02 mtr.	02 mtr.	MR				
J.	1) Fire check door	D 1	D '1 1	1.00				
	2) Sealing of electrical shafts	Required	Provided	MR				
	3) Fire rating of shaft door	Required 2 hrs.	sealed	MR				
	4) Water curtain	N/A	2 hrs. N/A	MR				
	5) Fire Dampers	Required	Provided	N/A MR				
4.	Smoke Management System	Required	TTOVIded	IVIK				
	1) Basements	30 ACPH	Provided	MR				
	2) Upper floors	12 ACPH	Provided	MR				
5.	Fire Extinguishers	12111	110/1004	IVII				
2 4 2 3	1) Total numbers	06 Nos.	08 Nos.	MR				
	2) Types	ABC & CO2	ABC & CO2	MR				
	3) ISI marking	Required	Provided	MR				
	/		210 VIGOG	WIII				

6.	First-Aid Hose Reel			
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	20 mm	20 mm	MR
7.	Automatic Fire Detection &			
	1) Type of detectors	Heat/Smoke	Provided	MR
	2) Location of main panel	Control Room	Provided	MR
	3) Location of repeater panel	Security Room	Provided	MR
	4) Alternate source of power	Battery & DG room	Provided	MR
	5) Hooter's Location	Different location	Different location	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	_	1101100	
10.	1) Basement	Required	Provided in	MR
	1) Dascillett	required	entire basement	
	2) Upper floors	Required	Provided	MR
	3) Sprinkler above false ceiling	Required	Provided	MR
11.	Internal Hydrants	Toquired		
11.	1) Size of riser/down-comer	150 mm	150 mm	MR
	2) Number of hydrants per floor	01	01	MR
	3) Hose box	01	01	MR
12.	Yard Hydrants		01	
12.	1) Total number of hydrants	01	02	MR
	2) Hose box	01	02	MR
13.	Pumping Arrangement		entire star city ma	
13.	1) Ground level	Required	Provided Provided	MR
	a) Discharge of main pump	2850 LPM	2850 LPM	MR
	b) Head of main pump	70 mtrs.	70 mtrs.	MR
	c) Number of main pump	02	02	MR
	d) Jockey pump out put	180 LPM	180 LPM	MR
	e) Jockey pump head	70 mtrs.	70 mtrs.	MR
	JUCKEY DUILID HEAD	/ / / IIIII ).		
		The second secon		
	f) Stand by pump outpu	t 2850 LPM	2850 LPM	MR
	f) Stand by pump output g) Stand by pump head	t 2850 LPM 70 mtrs.	2850 LPM 70 mtrs.	MR MR
	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping	t 2850 LPM	2850 LPM	MR
	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	t 2850 LPM 70 mtrs. Required	2850 LPM 70 mtrs. Provided	MR MR MR
	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump	t 2850 LPM 70 mtrs. Required 450 LPM	2850 LPM 70 mtrs. Provided 450 LPM	MR MR MR MR
	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump	t 2850 LPM 70 mtrs. Required 450 LPM 39 mtr.	2850 LPM 70 mtrs. Provided 450 LPM 39 mtr.	MR MR MR MR MR
	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	70 mtrs. Required 450 LPM 39 mtr. Required	2850 LPM 70 mtrs. Provided 450 LPM 39 mtr. Provided	MR MR MR MR MR MR
	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	70 mtrs. Required 450 LPM 39 mtr. Required Required Required	2850 LPM 70 mtrs. Provided 450 LPM 39 mtr.	MR MR MR MR MR
14.	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for	t 2850 LPM 70 mtrs. Required 450 LPM 39 mtr. Required Required Required Fire Fighting	2850 LPM 70 mtrs. Provided 450 LPM 39 mtr. Provided Provided	MR MR MR MR MR MR MR
14.	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for 1) Under ground tank capacit	70 mtrs. Required 450 LPM 39 mtr. Required Required Required Fire Fighting (ty 2,00,000 ltr	2850 LPM 70 mtrs. Provided 450 LPM 39 mtr. Provided Provided 2,00,000 ltr.	MR
14.	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for 1) Under ground tank capacital Draw-off connection	70 mtrs. Required 450 LPM 39 mtr. Required Required Required Tire Fighting Ty 2,00,000 ltr Required	2850 LPM 70 mtrs. Provided 450 LPM 39 mtr. Provided Provided 2,00,000 ltr. Provided	MR
14.	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for 1) Under ground tank capacital Draw-off connection b) Fire service inlet	t 2850 LPM 70 mtrs. Required 450 LPM 39 mtr. Required Required Fire Fighting ty 2,00,000 ltr Required Required Required	2850 LPM 70 mtrs. Provided  450 LPM 39 mtr. Provided Provided  2,00,000 ltr. Provided Provided	MR
14.	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for 1) Under ground tank capaci a) Draw-off connection b) Fire service inlet c) Access to tank	70 mtrs. Required 450 LPM 39 mtr. Required Required Tire Fighting Ty 2,00,000 ltr Required Required Required Required	2850 LPM 70 mtrs. Provided  450 LPM 39 mtr. Provided Provided Provided Provided Provided Provided Provided Provided	MR M
14.	f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for 1) Under ground tank capacital Draw-off connection b) Fire service inlet	t 2850 LPM 70 mtrs. Required 450 LPM 39 mtr. Required Required Fire Fighting ty 2,00,000 ltr Required Required Required	2850 LPM 70 mtrs. Provided  450 LPM 39 mtr. Provided Provided Provided Provided Provided Provided Provided Provided	MR

w

16.	Provision of Lifts.	THE STATE OF			
	a) Pressurization of lift shaft	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	Required	1000 KVS	MR	
18.	Refuge Area	N/A	N/A	N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room				
	a) Detector system panel	Required	Provided	MR	
	b) Flow switch panel	Required	Provided	MR	
	c) PA system panel	Required	Provided	MR	
14 V 1	d) Battery backup	Required	Provided	MR	
	e) Building floor plan	Required	Provided	MR	
20.	Special Fire Protection System 1 any:	NA			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/NDZ/2021/BNQT/13 dated 04/01/2021 have been rectified.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, grant of fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended please.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name: Francis Brown Designation: DO (ED) 20

Name: - M.K. Sharma Designation: - ADO (LN)

DY. Cool No 21

Has thort comings point no. 6. complied ?

Alore
2011121

DOCKO) yes sir, owner has complete lie short-coming

In- n- of Point No- 6.

DY. CADINDZ