GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No.F.6/FDS/MS/2021/SZ 67

Dated: 27/01/202

FIRE SAFETY CERTIFICATE

Certified that Hahnemann Pharmaceuticals Pvt. Ltd., A-7, Naraina Industrial Area, Phase-1, New Delhi- 110028, running in 7 rooms and one hall in a building comprised of Basement, Ground, mezzanine & two upper floors was granted NOC vide this department letter No. F.5/(3)/DFS/93/346 dated 27.09.1993. The building was re-inspected by the officer concerned of this department on 08.01.2021 in presence of Smt. Neeru Narula (Owner/Occupier) and found that the management of M/s. Hahnemann Pharmaceuticals Pvt. Ltd. have deemed complied with the fire prevention and fire safety requirements in accordance with rule as per Previous NOC No. F.5/(3)/DFS/93/346 dated 27.09.1993 and that the said building is fit for occupancy class "Industrial" with effect from 21/01/2021 for a period of three years, in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 printed below.

Assued on $\frac{21/31/2021}{}$ at New Delhi by.

(Sunil Chaudhary)
Dy. Chief Fire Officer (SZ)
Delhi Fire Service

Copy to: -

- 1. The Manager, M/s. Hahnemann Pharmaceuticals Pvt. Ltd., A-7, Naraina Industrial Area, Phase-1, Delhi- 28.
- 2. The Executive Engineer(Building), North DMC, Karol Bagh Zone, Anand Parbat, New Delhi

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. Basement shall be used as per UBBL. Stilt floor shall only be used for parking.
- 7. All comments / directions of licensing department shall always be permitted and followed.
- 8. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 9. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building

Hahnemann Pharmaceuticals Pvt. Ltd., A-7, Naraina

Industrial Area Phase-1. New Delhi- 110028

2. Type of Occupancy

: Business

3. Type of Case

: Renewal

4. Details of previous NOC

: F.5/(3)/DFS/93/346 dated 27.09.1993

5. Fire Safety directives letter No

: Nil

6. Date of inspection

: 08.1.2021

7. Name of the Inspecting Officers

: D.B Mukharjee, DO (SW) & P.V Rathee, ADO (SRD)

8. Name and designation of officers

from the building side

: Smt. Neeru Narula

9. Year of Construction

: Before 1993

10. Applicant's letter No.

: Email ID hahnemann99@gmail.com dated 27.11.2020

The building is comprised of Basement, ground, Mezzanine & two upper floors

/	Minimum Standards on fire prevention and fire safety U/R 33	Requirement as per NOC dt. 27.09.1993	Provided at site	Remarks MR/NMR		
1	Access to building					
	Road width	06 mts	Provided	MR		
	• Gate width	N/A	Accessible from main road	MR		
	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	-	-	-		
	• Upper Floors	01	01	MR		
	Basements	N/A	N/A	N/A		
	b. Width of staircases		-	-		
	Upper Floors	N/A	0.88 to 1.18 mts	MR being old case		
	Basements	N/A	N/A	N/A		
	c. Protection of exits	-		T 40		
	• Fire check door	N/A	N/A	N/A		
	 Pressurization 	N/A	N/A	N/A		
	e. No. of continuous staircases to	N/A	N/A	N/A		
	terrace	N/A	N/A	N/A		
	g. Width of Corridor	N/A	0.85 mts	MR		
	h. Door Size	14/11	0.02 1113	1111		
	Compartmentation.	N/A	N/A	N/A		
	• Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	N/A N/A	N/A	N/A		
	• Fire Rating of shaft door	N/A N/A	N/A	N/A		
	Water Curtain	N/A N/A	N/A	N/A		
	Fire Dampers	IN/A	IV/A	IN/A		
-	Smoke Management System.		77/1	27/4		
	Basements	N/A	N/A	N/A		
	Upper floors	N/A	N/A	N/A		
5	Fire Extinguishers					
	Total numbers	8	Provided	MR		
	Types	ABC & CO ₂ type	Water CO2, CO2 &	MR		
	IS marking	ISI marked	Foam type	1.00		
			Provided	MR		

	Total numbers on each floor	N/A	N/A	N/A	
	Length of hose reel hose	N/A	N/A	N/A	
	Nozzle diameter	N/A	N/A	N/A	
7	Automatic fire detection and alarming s	ystem.			
	Type of detectors	N/A	N/A	N/A	
	Location of Main Panel	N/A	N/A	N/A	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	Hooters' Location	N/A	N/A	N/A	
8	MOEFA	N/A	N/A	N/A	
9	Public Address System.	N/A	N/A	N/A	
10	Automatic Sprinkler System.				
	Basement	N/A	N/A	N/A	
	Upper Floor	N/A	N/A	N/A	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants				
11	Size of riser/down-comer	N/A	N/A	N/A	
	Number of hydrants per floor	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
12	Yard Hydrants.				
12	Total number of hydrants	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
13	Pumping Arrangements.				
13	Ground Level	N/A	N/A	N/A	
	> Discharge of main Pump	N/A	N/A	N/A	
	Head of Main pump	N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	Jockey Pump out put	N/A	N/A	N/A	
	Jockey pump head	N/A	N/A	N/A	
	Standby Pump out put	N/A	N/A	N/A	
		N/A	N/A	N/A	
	Standby Pump Head	27/4	NT/A	DT/A	
	Auto Starting/ Manual stopping	N/A	N/A	N/A	
	Pump House Access	N/A	N/A	N/A	
	Terrace level	N/A	N/A	N/A	
	Discharge of pump	N/A	N/A	N/A	
	Head of the pump	N/A	N/A	N/A	
	> Power Supply	N/A	N/A	N/A	
-	> Auto Starting of pump	N/A	N/A	N/A	
14	Captive Water Storage for fire fighting.				
	Underground tank capacity	N/A	N/A	N/A	
	> Draw-off connection	N/A	N/A	N/A	
	> Fire service inlet	N/A	N/A	N/A	
"	> Access to tank	N/A	N/A	N/A	
	Overhead Tank capacity	N/A	N/A	N/A	
15	Exit Signage.	N/A	N/A	N/A	

16	Prov	ision of Lifts. Provided but not co	ommissioned					
0		Pressurization of Lift Shaft	N/A	N/A	N/A			
	•	Pressurization of Lift lobby	N/A	N/A	N/A			
		Communication In lift Car	N/A	N/A	N/A			
		Fireman's Grounding Switch	N/A	N/A	N/A			
	0	Lift Signage	N/A	N/A	N/A			
17	Stand	dby power supply	N/A	N/A	N/A			
18	Refu	Refuge Area.						
1	>	Total Area	N/A	N/A	N/A			
	>	Location	N/A	N/A	N/A			
19	Fire Control Room							
		Detector System Panel	N/A	N/A	N/A			
		Flow Switch Panel	N/A	N/A	N/A			
		PA System Panel	N/A	N/A	N/A			
		Batter backup	N/A	N/A	N/A			
		Building Floor Plans	N/A	N/A	N/A			
20		al Fire Protection Systems for ction of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.5/(3)/DFS/93 /346 dated 27.09.1993, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended. DFA is put up for approval & signature please.

D.B Mukharjee

Divisional Officer (SW)

P.V. Rathee

Asstt. Div. Officer (SRD)

reak an addition