GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/Indl./2021/SZ/

Dated: 01/02/202/

FIRE SAFETY CERTIFICATE

Certified that M/s Munna Lal Ram Dayal, Plot no. A-188 Okhla Industrial Area, Phase-I, New Delhi-110020 comprised of Basement, Ground plus two upper floors owned/occupied by M/s Munna Lal Ram Dayal, was granted FSC by this department vide letter No. F6/DFS/MS/Indl./2016/SZ/142 dated 20/01/2016. The premises was re-inspected by officer concerned of this department on 25/01/2021 in the presence of Mr. Virender Singh Negi (Authorize Signatory) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules Act-2007 & Rules- 2010 and that premises/building is fit for occupancy class "Industrial" effect from a 1 22-22 for a period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued 61 02 2021 at New Delhi by

(Sunil Chawdhary)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to: -

- 1. The Authorized Signatory, Sh. Virendra Singh Negi, A-188 Okhla Industrial Area Phase-I, New Delhi-110020.
- 2. The executive Engineer (Bldg.)-I, SDMC, 8th floor, Civic Centre, Minto Road, New Delhi-110002.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1	No		M/a Myses I al Par	- David Blad as A 16	00 0111		
1	INE	ame & Address of the Building		n Dayal, Plot no. A-18			
2	Ty	pe of Occupancy	Industrial Area, Phase-I, New Delhi-110020 Industrial "Group-G"				
3	Bu	ilding Comprised of	Basement + Ground	d + 2 Upper Floors	1		
4	Ty	pe of Case	Renewal	11			
5	De	tails of Previous NOC	F.6/DFS/MS/Indl/2	016/SZ/142 dated 20/	01/2016		
6	Fir	e Safety Directives Letter No	F.6/DFS/MS/BP/20	010/1038 dated 12/04/2	2010		
7	Da	te of Inspection	25/01/2021				
8	Na	me of the Inspecting Officers	ADO Avtar Singh				
9	Na	me & Designation of Officers	Mr. Virender Singh Negi (Authorize Signatory)				
		m the building side			, a		
10	1200	ar of construction	2010				
11		plicant letter No.	Email dated 19/01/2021				
S. No	-	nimum standards on Fire Prevention I Fire Safety U/R 33	As Per Old NOC	Provided at Site	Remarks MR/NMR		
1	Ac	cess to Building.					
		• Road width	09 m	Provided	MR		
		• Gate width	4.5 m	Provided	MR		
		• Width of internal road	-N/A-	-N/A-	-N/A-		
2	Nu	lumber, width, type & arrangement of exits.					
	a)	Number of Staircase					
		Upper floors	02 nos	Provided	MR		
		Basement floors	02 nos	Provided	MR		
	b)	Width of Staircase					
	-	> Upper floors	1.5 m	Provided	MR		
		> Basement floors	1.5 m	Provided	MR		
	c)	Protection of exits					
		Fire check door	Required	Provided	MR		
	-0	Pressurization	-N/A-	-N/A-	-N/A-		
		No. of continuous staircase to terrace	02 nos	Provided	MR		
		Width of corridor	-N/A-	-N/A-	-N/A-		
	/ =	Door size	1 m	1 mtr	MR		
3	Co	mpartmentation.					
	2.0	• Fire check door.	Required	Provided	MR		
	- 2	Sealing of electrical shafts.Fire rating of shaft door.	Required	Provided	MR		
		Water curtain	-N/A-	-N/A-	-N/A-		
	2	• Fire dampers.	-N/A-	-N/A-	-N/A-		
			Required	Provided	MR		
4.	Sm	oke Management system.		P 111			
		Basement	30 ACPH		MR		
		• Upper floors	12 ACPH	Provided	MR		
5.	Fir	e Extinguishers.	10.0100	1.7	1.00		
	-	• Total numbers	IS:2190	15 nos	MR		
	W 1	• Types	ABC / CO ₂ / W.CO ₂		MR		
	0	ISI Marking	ISI Marked	Provided	MR		
6.	Fir	st Aid Hose Reels.	1	D 11 1	MD		
		Total numbers on each floor	1 nos	Provided	MR		
		• Length of hose-reel hose.	30 m	Provided	MR		

7	Automatic fire detection & alarming s	utomatic fire detection & alarming system.		
	Type of detectors	Smoke & Heat	Provided	MR
	 Location of Main Panel 	Ground Floor	Ground Floor	MR
	Location of Repeater Panel	-N/A-	-N/A-	-N/A-
	Alternate source of powerHooter's location	Required	Provided	MR
	Trooter's location	All Area	Provided	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	-N/A-	-N/A-	-N/A-
10.	Automatic Sprinkler System			
	Basement.	Required	Provided	MR
	Upper floors	Required	Provided	MR
	Sprinkler above false ceiling	Required	Provided	MR
11.	Internal Hydrants.			
	Size of Riser / Down-comer	100mm	Provided	MR
	Number of Hydrant per floor	1 nos	Provided	MR
	Hose box.	1 nos	Provided	MR
12.	Yard Hydrants.			
	Total number of hydrants.	Required	2 nos	MR
13	Hose box.	Required	2 nos	MR
13.	Pumping arrangements.			
	Ground Level			
	Discharge of main pump.	2280 LPM	Provided	MR
	Head of main pumpNumber of main pumps	70 m	Provided	MR
	· ·	1 Nos	Provided	MR
	> Jockey Pump output.	180 LPM	Provided	MR
	Jockey Pump head.	70 m	Provided	MR
	> Standby Pump output.	2280 LPM	Provided	MR
	> Standby Pump head.	70 m	Provided	MR
	> Auto Starting/Manual stopping	Required	Provided	MR
	Pump house access. Auto	Required	Provided	MR
	Terrace Level			
	Discharge of pump.	900 LPM	Provided	MR
	Head of pump.	40 m	Provided	MR
	Power supply.Auto starting of pump.	Required	Provided Provided	MR MR
1.4	, the second sec	Required	Tiovided	· IVIIX
14.	Captive water storage for firefighting.	1.00.0001	D	MR
	 Underground tank capacity. Draw-off connection. 	1,00,000 ltrs	Provided Provided	MR
	Fire Service Inlet.	Required	Provided	MR
	> Access to tank.	Required	Provided	MR
		Required		MR
1=	Overhead tank capacity. Compared tank capacity. Overhead tank capacity. Overhead tank capacity.	20,000 ltrs	20,000 ltrs Provided	MR
15.	Exit Signage.	Required	rrovided	IVII
16.	Provision of Lifts.	NI/A	-N/A-	-N/A-
	 Pressurization of lift shaft. Pressurization of lift lobby. 	-N/A-	-N/A-	-N/A-
	• Pressurization of lift lobby. • Communication in lift car.	-N/A-	-N/A-	-N/A-
		-N/A-	-IN/A-	-1N/ <i>F</i> 1-
-	• Fireman's switch.	-N/A-	-N/A-	-N/A-

- MI19 -

17	Standby Power Supply	Required	Provided	MR		
18.	Refuge Area					
	Total area	-N/A-	-N/A-	-N/A-		
	• Location	-N/A-	-N/A-	-N/A-		
19.	Fire Control Room.					
	Detector System Panel.	-N/A-	-N/A-	-N/A-		
	 Flow Switch Panel. 	-N/A-	-N/A-	-N/A-		
	PA system Panel.Battery backupBuilding floor plan	-N/A-	-N/A-	-N/A-		
		-N/A-	-N/A-	-N/A-		
		-N/A-	-N/A-	-N/A-		
20.	0. Special Fire Protection System for the Protection of special Risk, if any.					

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

The shortcoming communicated vide letter no. F6/DFS/MS/SZ/2021/68 dated 11/01/2021 found complied.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety measures as required under the rules of NOC issued vide letter no. F.6/DFS/MS/Indl/2016/SZ/142 dated 20/01/2016, renewal under rule 37 of the Delhi Fire Service rule 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name : Avtar Singh Designation: ADO (MR)

DO (SD)

Liv 30/01/21

CF. Q(S2)

FT letter is put af far sign please

c Go (\$p)

30/81/2021