FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/Hospital/2021/SZ/ /0 §

Dated: 102/2021

FIRE SAFETY CERTIFICATE

Certified that the M/s Vardhaman Mahavir Medical College located at Safdarjung Hospital Complex, Ring Road, New Delhi-110029, comprised of Two Basements, Ground plus six upper floors, owned / occupied by Ministry of Health, Govt. of India was granted Fire Safety Certificate Vide letter No. F6/DFS/MS/2017/SZ/1182 dated 08/08/2017. The premises was re-inspected by the officer concerned of Fire Service on 01.02.2021 in the presence of Sh. R.N. Singh, XEN (E) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with rule 33 of the Delhi Fire Service Rule, 2010 and that the building / premises is fit for occupancy class "Educational" (Group - 'B') with effect from for / 102/2021 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010.

TUL GARG) DIRECTOR.

Copy to :-

- 1. Executive Engineer (E), PWD, Safdarjung Hospital Complex, New Delhi-110029.
- 2. Medical Superintendent, Safdarjung Hospital Complex, New Delhi-110029.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provision of building bye laws.
- 6. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 7. <u>"The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".</u>
- 8. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on WWW.dfs.Delhigovt.nic.in.

INSPECTION REPORT

- 1. Name & address of the building: M/s Vardhaman Mahavir Medical College, Safdarjung Hospital Complex, Ring Road, New Delhi-110029.
- Type of Occupancy : Education Building "B" (Medical College) 3. Building Comprised of : Two basements, ground plus six upper floors
- 4. Type of Case : Renewal
- 5. Details of previous NOC : F6/DFS/MS/2017/SZ/1182 dated 08/08/2017 🗸
- 6. Fire Safety directives Letter No.:F6/DFS/MS/BP/2005/1500 dated 15/07/05
- 7. Date of inspection : 01/02/2021 8. Name of the Inspecting Officer: A.D.O. (S.J.)
- 9. Name and designation of Officer

from the building side : Sh. R.N. Singh, XEN (E)

S		num standards on	-	1)/DV/2020-2		Provided at				
No		revention and fire		Requirement as per BBL /		site		Remarks		
140	_	U/R 33		S PCI BBI IBC	<i>.</i> /	Site	101	MR/NMR		
1.	-		1,	NDC .						
1.	Access of building • Road width			2m		12		D		
	•		12m 6 mtr			12m / MI		***************************************		
	•	Gate width	-			6 mtr		∕IR		
	•	Width of internal road	0	mtr		6 mtr	MF	₹		
2.	Numb	per, width, Type &	A rr	angement	s of	fevits				
	a.	Number of stairca			.5 01	LOVIES				
	•	Upper floors	06			05		MR		
		Basements	06nos. + 2ramps		nns			/IR /IR		
	b.	Width of staircase				001103. 1 21 y 111p				
	•	Upper floors		os=1.50m(eac	h),	1.5,1.5,1.85,1	l 8m	MR		
		opper moors	02nos=2m(each) &			& 2m		IVIIX		
		Danabasa	1no=1.7m 3nos=1.50m			1.5, 1.5, 1.85, 1.8m, &		NAD.		
	•	Basements		each),02nos=2m (eac		I		MR		
			&1no=1.7m			Ramps=4.5m(each)				
	C.	Protection of exits						-		
	•	Fire check door	R	Required	Pr	ovided		MR		
	•	Pressurization		NA	1	NA		NA		
	d.	No of continuous		5	5			MR		
		staircase to terrace				2		1 2 2 2		
	e.	Width Of Corrido	r	r 2m		m		MR		
	f.	Door Size		1m 1		1m		MR		
3.	Compartmentation									
	•	Fire check door	Required Pr		Pro	rovided		MR		
	•	Sealing of electric shafts	al	Required		Provided		MR		
	•	Fire Rating of shaft d	oor	r Required		Provided		MR		
	•	Water Curtain		NA *		NA N		1		
	•	Fire Dampers	NA	7	NA		NA			
4.	Smoke	e managements Sys	ten	em						
	•	Basements	30	a/c per ho	ur	Provided &		MR		
	 Upper floors 		12 a/c per hour		Natural ventilation MR		-			
5.	Fire Extinguishers									
	•	Total numbers	60)		60 N		1R		
	•	Types		BC/CO ₂ &		ABC,CO ₂ , MR				
	707			WCO ₂		WCO ₂				
	•	ISI marking	IS	1		Provided	MR			

Length of hose reel hose Nozzle diameter 5 mm. 5 mm. MR			• Total numbers on		3		3		MR
Noze Nozzle diameter 5 mm.			each floorLength of hose reel		301	Mtr	30	N/tr (NAD
Type of detection and alarming system Type of detector Location of Main Panel Location of Repeater Panel Location of Repeater Panel Alternate source of power Heat & Fire Semake in mechanical stress Infunctional Alternate Source of Panel Alternate source of power Hooters' Location All Areas Provided MR Required Provided MR MR MOEFA Required Provided Functional MR Public Address System Required Provided MR MR Automatic Sprinkler System Basements Required Provided MR Upper Floor Required Provided MR Sprinkler above false ceiling Required Provided MR Sprinkler above false ceiling Required Provided MR Internal Hydrants Size of riser/downcomer Number of hydrants per floor Hose Box Total number of hydrants Hose Box Hose Box Boy Head of main pump Head of main pump Head of main pump Jockey pump out put Jockey pump out put Jockey pump Head Jockey pump Head Jockey pump Head MR Standby Pump Head MR Head of the pump Head of the pump Head of the pump Power supply Required Provided MR MR MR MR NA NA NA NA NA NA NA NA NA N					301	VILI.	30	IVILI.	IVIK
Provided & MR Location of Main Panel Location of Repeater Panel Location of Repeater Panel Location of Repeater Panel Alternate source of power Hooters' Location All Areas Provided MR Required Provided & functional MR MR MR MR Alternate source of power Hooters' Location All Areas Provided MR MR MR MOEFA Required Provided & functional MR Public Address System Required Provided & functional MR MR MR MOEFA Required Provided & MR MR MR MR MR MI MI MI MI MI	-		 Nozzle diameter 		5 m	m.	5 m	ım.	MR
Location of Main Panel Location of Repeater Panel Location of Repeater Panel Location of Repeater Panel Location of Repeater Panel Alternate source of Panel Alternate source of Panel Alternate source of Power Hooters' Location All Areas Provided MR 8. MOEFA Required Provided Functional MR 9. Public Address System Required Provided Functional MR 10. Automatic Sprinkler System Basements Required Provided MR Upper Floor Required Provided MR Sprinkler above false ceiling Required Provided MR 11. Internal Hydrants Size of riser/down-comer 100 mm 100 mm		7.	Automatic fire detection an	d al				1	
Location of Main Panel Panel Location of Repeater Panel Location of Repeater Panel Alternate source of power Panel Alternate source of power Provided Provided Provided Provided Provided MR MOEFA Required Provided & functional MR Public Address System Required Provided MR P			 Type of detector 					MR	
Panel Location of Repeater Panel Alternate source of power Hooters' Location All Areas Provided MR Required Provided & functional MR Required Provided & functional MR Provided & functional MR Required Provided MR Required Provided MR Required Provided MR Provided MR Required Provided MR			 Location of Main 				11643		MR
Panel Alternate source of power Alternate source of power Hooters' Location All Areas Provided MR MOEFA Required Provided Functional MR Public Address System Required Provided MR Automatic Sprinkler System Basements Required Provided MR Upper Floor Required Provided MR Sprinkler above false ceiling Required Provided MR Sprinkler above false ceiling Required Provided MR Sprinkler above false ceiling Required Provided MR Number of hydrants Provided MR Size of riser/down-comer Number of hydrants Provided MR Total number of hydrants Provided MR Total number of hydrants Provided MR Total number of Hose Box Brundler Brundl			Panel						IVIIC
Alternate source of power Required Provided MR				r	NA			NA	NA
Number of hydrants Size of riser/down-comer Number of hydrants Hose Box Size of main pump Siz					Required			Provided	MR
8. MOEFA Required Provided & functional MR 9. Public Address System Required Provided MR 10. Automatic Sprinkler System • Basements Required Provided MR • Upper Floor Required Provided MR • Upper Floor Required Provided MR • Sprinkler above false ceiling Required Provided MR 11. Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Number of hydrants per floor • Hose Box 3 3 3 MR 12. Yard Hydrants • Total number of hydrants • Hose Box 6 6 6 MR 13. Pumping Arrangements • Ground Level • Discharge of main pump 2850 LPM 2850 LPM MR > Head of main pump 90 m 90 m MR > Number of main pump 180 LPM x 2 / MR > Jockey pump head 90 m 90 m MR > Standby Pump out put 180 LPM 2850 LPM MR > Standby Pump Head 90m 90 m MR > Standby Pump Head 90m 90 m MR > Catalogue Access Required Provided MR > Pump House Access Required Provided MR > Power supply Required Provided MR > Auto Starring/Manual stopping Required Provided MR > Power supply Required Provided MR > Captive water Storage for fire fighting • Underground tank capacity > Draw of connection Required Provided MR Fire service inlet Required Provided MR Provided MR									
9. Public Address System Required Provided MR 10. Automatic Sprinkler System ■ Basements Required Provided MR ■ Upper Floor Required Provided MR ■ Sprinkler above false ceiling Required Provided MR ■ Sprinkler above false ceiling Required Provided MR 11. Internal Hydrants ■ Size of riser/down-comer ■ Number of hydrants per floor ■ Hose Box 3 3 3 MR 12. Yard Hydrants ■ Total number of hydrants Hose Box 6 6 6 MR 13. Pumping Arrangements ■ Ground Level ■ Discharge of main pump 2850 LPM 2850 LPM MR ■ Head of main pump 90 m 90 m MR ■ Number of main pump 1 180 LPM × 2 / MR ■ Jockey pump head 90 m 90 m MR ■ Standby Pump out put 2850 LPM 2850 LPM MR ■ Standby Pump Head 90 m 90 m MR ■ Standby Pump Head 90 m 90 m MR ■ Auto Staring/Manual stopping ■ Pump House Access Required Provided MR ■ Terrace level ■ Discharge of pump 450 LPM 480 LPM (MR) ■ Head of the pump 40 MR ■ Auto starting of pump Required Provided MR ■ Auto starting of pump Required Provided MR ■ Auto starting of pump Required Provided MR ■ Captive water Storage for fire fighting ■ Underground tank capacity ■ Draw of connection Required Provided MR ■ Fire service inlet Required Provided MR					All A	reas		Provided	MR
10. Automatic Sprinkler System Sprinkler System Sprinkler System		127		quir	ed	Prov	ided	& functional	MR
Basements Required Provided MR					ed	Prov	/ided		MR
Upper Floor Required Provided MR Sprinkler above false ceiling Required Provided MR Sprinkler above false ceiling Required Provided MR Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box 3 3 MR 12. Yard Hydrants Total number of hydrants Hose Box 6 6 MR 13. Pumping Arrangements Ground Level Shade of main pump 2850 LPM 2850 LPM MR Head of main pump 90 m 90 m MR Number of main pump 1 2 MR Head of main pump 1 2 MR Jockey pump out put 1 880 LPM 180 LPM 2 MR Standby Pump out put 2850 LPM 2850 LPM MR Standby Pump Head 90 m 90 m MR Standby Pump Head 90 m 90 m MR Auto Staring/Manual Required Provided MR Terrace level Discharge of pump 450 LPM 450 LPM (MR) Head of the pump 40 m 40 m 40 m(each) MR Power supply Required Provided MR Auto starting of pump Required Provided MR Power supply Required Provided MR Captive water Storage for fire fighting Underground tank capacity Provided MR Fire service inlet Required Provided MR	1	0.		1					
Sprinkler above false ceiling Required Provided MR Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box Total number of hydrants Hose Box Size of riser/down-comer Number of hydrants per floor Hose Box Total number of hydrants Hose Box Size of riser/down-comer Number of hydrants Total number of hydrants Hose Box Size of riser/down-comer Number of hydrants Size of riser/down-comer MR MR MR Total number of hydrants Foround Level Size of main pump Siz					Requ	uired		Provided	MR
11. Internal Hydrants Size of riser/downcomer Number of hydrants per floor Hose Box Total number of hydrants Hose Level Hose L			The state of the s			ired		Provided	MR
Size of riser/down-comer Number of hydrants per floor Hose Box Total number of hydrants Hose Box Total number of hydrants Hose Box Total number of hydrants Hose Box Size of riser/down-comer Hose Box Total number of hydrants Hose Box Total number of hydrants Hose Box Size of riser/down-comer Hose Box Total number of hydrants Total number of hydrants Hose Box Size of riser/down-comer MR MR Pumping Arrangements Total number of hydrants Size of riser/down-comer Box Size of riser/down-comer MR MR Size of riser/down-comer Box Box Size of riser/down-comer Box Box Box Size of riser/down-comer Box Box Box Size of riser/down-comer Box Box Box Box Box Box Box Bo	1	1		cei	lling	R	equi	red Provided	MR
Comer Number of hydrants per floor Hose Box Total number of hydrants Total number of hydrants Hose Box Total number of hydrants Total number of hydrants Hose Box Total number of hydrants Hose Box Total number of hydrants Hose Box Total number of hydrants Total num	1	1.			100		Т	·	
Number of hydrants per floor Hose Box Total number of hydrants Total number of hydrants Hose Box Total number of hydrants Total number of hydrants Hose Box Total number of hydrants Total num			20		100 mm			100 mm	MR
Per floor Hose Box Total number of hydrants Total number of hydrants Hose Box Total number of hydrants Hose Box Hose Hose Hose Hose Hose Hose Hose Hose					3		-	3	MD
12. Yard Hydrants • Total number of hydrants • Hose Box 6 6 6 6 MR 13. Pumping Arrangements • Ground Level • Discharge of main pump 2850 LPM 2850 LPM MR > Head of main pump 90 m 90 m MR > Number of main pumps 1 2 MR > Jockey pump out put 180 LPM 180 LPM 2 Z850 LPM MR > Standby Pump out put 2850 LPM 2850 LPM MR > Standby Pump Head 90 m 90 m MR > Standby Pump Head 90 m 90 m MR > Auto Staring/Manual Required Provided MR • Terrace level > Discharge of pump 450 LPM 450 LPM MR > Head of the pump 40 MR > Power supply Required Provided MR > Power supply Required Provided MR 14. Captive water Storage for fire fighting • Underground tank capacity > Draw of connection Required Provided MR Fire service inlet Required Provided MR Provided MR Provided MR			per floor					3	IVIK
12. Yard Hydrants • Total number of hydrants • Hose Box 6 6 6 MR 13. Pumping Arrangements • Ground Level • Discharge of main pump 2850 LPM 2850 LPM MR > Head of main pump 90 m 90 m MR > Number of main pumps 1 2 MR > Jockey pump out put 180 LPM 180 LPM 2 MR > Jockey pump head 90 m 90 m MR > Standby Pump out put 2850 LPM 2850 LPM MR > Standby Pump out put 2850 LPM 180 LPM MR > Standby Pump Head 90 m 90 m MR > Auto Staring/Manual stopping Pump Head Provided MR • Terrace level > Discharge of pump 450 LPM 450 LPM MR > Head of the pump 40 MR > Power supply Required Provided MR > Power supply Required Provided MR - Auto starting of pump Required Provided MR - Auto starting of pump Required Provided MR - Auto starting of pump Required Provided MR - Draw of connection Required Provided MR - Fire service inlet Required Provided MR - Provided MR			Hose Box		3			3	MR
hydrants Hose Box Hos	12	2.	Yard Hydrants						1711
hydrants Hose Box Hos			 Total number of 	(6	ń		6	MR
13. Pumping Arrangements Ground Level Discharge of main pump Head of main pump Number of main pumps Jockey pump out put Standby Pump out put Standby Pump Head MR Standby Pump Head MR Standby Pump Head MR Standby Pump Head MR Required Provided MR Auto Staring/Manual stopping Pump House Access Required Terrace level Discharge of pump Head of the pump Head of the pump Auto starting of pump Required Provided MR		-							1,.
 Ground Level Discharge of main pump Head of main pump Head of main pump Number of main pumps Jockey pump out put Jockey pump head Jockey pump head Standby Pump out put Standby Pump Head Pom Auto Staring/Manual stopping Pump House Access Required Provided Terrace level Discharge of pump Head of the pump Auto starting of pump Required Provided MR Auto starting of pump Captive water Storage for fire fighting Underground tank capacity Fire service inlet Provided MR Provided MR MR Provided MR MR Provided MR Provided MR Provided MR 	1.0			6	5			6	MR
 Discharge of main pump Head of main pump Head of main pump Head of main pump Number of main pumps Jockey pump out put Jockey pump head Jockey pump head Standby Pump out put Standby Pump Head Auto Staring/Manual stopping Pump House Access Required Provided MR Terrace level Discharge of pump Head of the pump Auto starting of pump Required Provided MR Auto starting of pump Auto starting of pump Auto starting of pump Required Provided MR Auto starting of pump Auto starting of pump Required Provided MR Auto starting of pump Required Provided MR Auto starting of pump Required Provided MR Provided MR Provided MR Provided MR Provided MR Auto starting of pump Required Provided MR Provided MR Provided MR Provided MR Provided MR 	13								
 → Head of main pump → Number of main pumps → Jockey pump out put → Jockey pump head → Jockey pump head → Standby Pump out put → Standby Pump Head → Auto Staring/Manual stopping → Pump House Access → Terrace level → Discharge of pump → Head of the pump → Auto starting of pump → Required → Provided → Provided → MR → Auto starting of pump → Auto starting of pump → Captive water Storage for fire fighting → Underground tank capacity → Draw of connection → Fire service inlet → Provided → Provided → MR 		•							
 Number of main pumps Jockey pump out put Jockey pump out put Jockey pump head 90 m 90 m MR Standby Pump out put 2850 LPM Standby Pump Head 90m 90m MR Standby Pump Head 90m 90m MR Auto Staring/Manual stopping Pump House Access Required Provided MR Terrace level Discharge of pump 450 LPM 450 LPM+ (MR 180LPM) Head of the pump 40m 40m(each) MR Power supply Required Provided MR Auto starting of pump Required Provided MR Captive water Storage for fire fighting Underground tank capacity Draw of connection Required Provided MR Fire service inlet Required Provided MR 		_	Head of main nume			LPM			
 Jockey pump out put Jockey pump head Jockey pump head Standby Pump out put Standby Pump out put Standby Pump Head Standby Pump Head Pom Auto Staring/Manual stopping Pump House Access Required Provided MR Terrace level Discharge of pump Head of the pump Power supply Required Provided MR Power supply Required Provided MR Auto starting of pump Required Provided MR Captive water Storage for fire fighting Underground tank capacity Draw of connection Required Provided MR Fire service inlet Required Provided MR 								/	
 Jockey pump head Standby Pump out put ≥ Standby Pump Head ⇒ Standby Pump Head ⇒ Om ⇒ Standby Pump Head ⇒ Om ⇒ Auto Staring/Manual stopping ⇒ Pump House Access ⇒ Required ⇒ Provided ⇒ Discharge of pump ⇒ Head of the pump ⇒ Head of the pump ⇒ Auto starting of pump ⇒ Auto starting of pump ⇒ Captive water Storage for fire fighting ■ Underground tank capacity ⇒ Draw of connection ⇒ Required ⇒ Provided ⇒ MR → Provided ⇒ MR → Provided → Provided → MR → Provided → Provided → MR → Provided → Provided	-				-	N 4			
Standby Pump out put Standby Pump out put Standby Pump Head Standby Provided MR Provided MR Head of the pump Standby Pump Head Standby Provided MR Head of the pump Standby Pump Head Standby Provided MR Head of the pump Standby Provided MR Power supply Required Provided MR Lapacity Draw of connection Required Provided MR Provided MR Provided MR Provided MR Required Provided MR Provided MR Required Provided MR				-		101	_		
 ➢ Standby Pump Head ➢ Auto Staring/Manual stopping ➢ Pump House Access ➢ Pump House Access Æ Required Æ Provided MR Terrace level ➢ Discharge of pump ➢ Head of the pump ➢ Head of the pump ➢ Power supply ➢ Auto starting of pump Required Æ Provided MR ➢ Auto starting of pump Required Provided MR 14. Captive water Storage for fire fighting ④ Underground tank capacity ➢ Draw of connection ➢ Fire service inlet Required Provided MR MR 		->				PM		25 P. 1995)	
Auto Staring/Manual stopping Pump House Access Required Provided MR Terrace level Discharge of pump 450 LPM 180LPM Head of the pump Auto starting of pump Required Provided MR Power supply Required Provided MR Auto starting of pump Required Provided MR 14. Captive water Storage for fire fighting Underground tank capacity Draw of connection Required Provided MR Provided MR Provided MR Provided MR Required Provided MR		>		_				/	
stopping Pump House Access Required Provided MR Terrace level Discharge of pump 450 LPM 450 LPM+ 180LPM Head of the pump 40m Power supply Required Provided MR Auto starting of pump Required Provided MR 14. Captive water Storage for fire fighting Underground tank capacity Draw of connection Required Provided MR		>		_					
 Terrace level Discharge of pump Head of the pump Power supply Auto starting of pump Captive water Storage for fire fighting Underground tank capacity Draw of connection Required Provided MR Provided MR Provided MR MR Provided MR 			stopping					, , , , , , , , , , , , , , , , , , , ,	IVIN
 Discharge of pump 450 LPM 450 LPM+ (180LPM) → Head of the pump 40m 40m(each) MR → Power supply Required Provided MR → Auto starting of pump Required Provided MR 14. Captive water Storage for fire fighting Underground tank capacity → Draw of connection Required Provided MR → Fire service inlet Required Provided MR 		7	- 5311p 110 date 110 cc 55	R	equir	ed	F	Provided	MR
Head of the pump 40m 40m(each) MR Power supply Required Provided MR Auto starting of pump Required Provided MR 14. Captive water Storage for fire fighting Underground tank capacity Draw of connection Required Provided MR Fire service inlet Required Provided MR			TO THE RESERVE TO THE						
 ➢ Head of the pump ➢ Power supply ➢ Auto starting of pump Head of the pump Required Provided MR Provided MR Captive water Storage for fire fighting Underground tank capacity ➢ Draw of connection Required Provided MR Fire service inlet Required Provided MR 		1	Discharge of pump	45	50 LPI	M		(MR
Power supply Required Provided MR Auto starting of pump Required Provided MR 14. Captive water Storage for fire fighting Underground tank capacity Draw of connection Required Provided MR Provided MR Provided MR Provided MR Provided MR	-	<u> </u>	Head of the numn	1	2				
Auto starting of pump Required Provided MR 14. Captive water Storage for fire fighting Underground tank capacity Draw of connection Required Provided MR Provided MR Provided MR Required Provided MR				-		- al			4.000
14. Captive water Storage for fire fighting • Underground tank capacity Draw of connection Required Provided MR Fire service inlet Required Provided MR									
 Underground tank capacity Draw of connection Fire service inlet Underground tank capacity Provided Provided MR Provided MR 								rovided	MR
capacity Draw of connection Required Provided MR Fire service inlet Required Provided MR	14		Captive water Storage for fire fighting						
 Draw of connection Fire service inlet Required Provided MR MR 								,00,000 ltr (MR
Fire service inlet Required Provided MR		-							
Toviaca IVIII		-	Braw or connection	-					
				-			Pi	rovided	MR

.

	N			
15	Exit Signage	Required Pro	ovided	MR
16.	Provision of Lifts			
	Pressurization of Lift Shaft	NA	NA	NA
	Pressurization of lift lobby	NA	NA	NA
	Communication in lift Car	Required	Provided	MR
	Fireman's Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area			
	Total area	NA	NA	NA
	> Location	NA ·	NA	NA
19.	Fire control room			
	Detector system panel	Required	Provided	MR
	Flow SwitchPanel	Required	Provided	MR
	PA SystemPanel	Required	Provided	MR
	Battery backup	Required	Provided	MR
	Building Floor Plans	NA	NA	NA
20.	Special Fire Protection	HT, LT &	Co ₂ flooding	MR
	Systems for Protection	Transformer	system Provided	
	of special Risks, if any;		in electric panel	
			& functional	

Note:- Shortcomings issued by this department vide letter No. F6/DFS/MS/2020/SZ/Hospital/3193 dated 30/12/2020 have been complied.

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/2017/SZ/1182 dated 08/08/2017 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name: A.K. Jaiswal

Designation: A.D.O. (S.J.)

DofBD)

Rive

DOFO(52)

10/2