GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/School/2021/NDZ/

Dated: 11/2/21

FIRE SAFETY CERTIFICATE

Certified that the Govt. Girls. Sr. Sec. School located at New Jafrabad, Delhi-110032 comprised of ground plus one upper floor (first, second and third block) & ground floor (fourth block) owned/occupied by Govt. Girls Sr. Sec. School was issued FSC vide letter No. F.6/DFS/MS/School/2017/NDZ/1730 dated 01/12/2017. The school building have complied with the fire prevention and fire safety requirements in accordance with circular No-F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated-01/03/11 issued by the Director of Education and verified by the officers concerned of this department on dated 27/01/2020 in the presence of Mrs. Indrawati, Principal of the school and found that the school building is fit for occupancy class "B" 'Educational Building' for ground plus one floor with effect from for a period of three years, in accordance and further subject with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on. 11 2 at New Delhi by

Note:- This Fire Safety Certificate does not cover the new building blocks (Ground plus three storey building) for which Shortcomings was issued vide letter no F6/DFS/MS/2018/1436 dated 06/04/2018 by this department.

(Dr. S. K. Tomar) Dy. Chief Fire Officer

of As

To,

The Principal, Govt. Girls Sr. Sec. School, New Jafrabad, Delhi-110032

Copy:-

The Joint Director of Education (Land & Estate), Directorate of Education, Lucknow Road, Delhi-54

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry

| | INSPECT | ION REPORT | | | | | |
|-----------------|---|---|---------------------|-------------------|--|--|--|
| 1. | 1. Name & address of the building : Govt. Girls. Sr. Sec. School, New Jafrabad, | | | | | | |
| | | Delhi-110032 | | | | | |
| 2. | Building is comprised of | : G+1 upper floor (Th | ree Blocks) & | | | | |
| | | (Block 4 th G floor) : Educational : Renewal : F6/DFS/MS/School/2017/NDZ/1730 dated 01/12/2017 | | | | | |
| 3. | Type of Occupancy | | | | | | |
| 4. | | | | | | | |
| 5. | Details of Previous NOC letter | | | | | | |
| | | | | | | | |
| 6. | Fire Safety direction letter No. | : F16/Estate/CC/Fire Safety/2011/3298 to 3398 | | | | | |
| | | dated- 01/03/11 : 27/01/2021 | | | | | |
| 7. | | | | | | | |
| 8. | 1 | : ADO Nagender Singh | | | | | |
| 9. | | M. I. I | 1 | | | | |
| 1.0 | from the building side | : Mrs. Indrawati, Principal | | | | | |
| 10. | | : 2013 | am datad 14/1/20 | 121 | | | |
| 11. | | : vpshah662@gmail.com dated 14/1/2021 on Circular Provided at Ren | | | | | |
| r. | Minimum Standards on Fire Prevention | | Site | Remarks MR/NMR | | | |
| No. | and Fire Safety U/R33 | Requirement | Site | IVIN/INIVIR | | | |
|)1 | Access to Building | | | | | | |
| | Road width | 06m | 08m | MR | | | |
| | • Gate width | N/A | N/A | N/A | | | |
| | • Width of internal road | N/A | N/A | N/A | | | |
|)2 | Number, Width, Type and Arrangement | | 11111 | 11/12 | | | |
| 12 | Number, width, Type and Arrangement | OI LAILS | | | | | |
| | a. Number of Staircases | THE REAL PROPERTY OF THE PARTY | - | 175 | | | |
| | • Upper floor | 01 nos. | 02 nos. each | MR | | | |
| | | | block | 1 | | | |
| | Basement | N/A | N/A | N/A | | | |
| | B. Width of Staircases | | | | | | |
| | Upper floor | 1.50m | 1.50m | MR | | | |
| 1. | Basement | N/A | N/A | N/A | | | |
| | c. Protection of Exits | | | | | | |
| | • Fire check door | N/A | N/A | N/A | | | |
| | Pressurization | N/A | N/A | N/A | | | |
| | d. No. of Continuous Staircases to | N/A | N/A | N/A | | | |
| and a second | Terrace | | | | | | |
| | e. Width of Corridor | 1.50m | 1.50m | MR | | | |
| | f. Door Size | 01m | 01m | ·MR | | | |
|)3 | Compartmentation. | | | | | | |
| - | A contract of the contract of | NT/A | 31/4 | 27/4 | | | |
| | • Fire check door | N/A | N/A | N/A | | | |
| | • Sealing of electrical shafts | N/A | N/A | N/A | | | |
| | Fire rating of shaft door | N/A | N/A | N/A | | | |
| | Water curtain | N/A | N/A | N/A | | | |
| | • Fire dampers | N/A | N/A | N/A | | | |
|)4 | Smoke Management System. | | | | | | |
| | Basement | N/A | N/A | N/A | | | |
| | • Upper floor | N/A | N/A | N/A | | | |
|)5. | Fire Extinguishers | 1 1/71 | IN/A | IN/A | | | |
| | THE DAMISHOIS | | | | | | |
| | Total numbers | 11 nos. | 11 nos. | MR | | | |
| and the second | | | | | | | |
| eendon to above | • Types | ABC/CO ₂ | ABC/CO ₂ | MR | | | |

| 06 F | First-Aid-Hose Reels. | | | | | | |
|--------|---|-----|---------|-----|--|--|--|
| | Total numbers on each floor | N/A | N/A | N/A | | | |
| 3 - 1 | Length of hose reel hose | N/A | N/A | N/A | | | |
| | Nozzle diameter | N/A | | N/A | | | |
| 7 A | Automatic Fire Detection and Alarming Syste | em. | | | | | |
| | Type of detectors | N/A | N/A | N/A | | | |
| | Location of main panel | N/A | N/A | N/A | | | |
| | Location of repeater panel | N/A | N/A | N/A | | | |
| | Alternate source of power | N/A | N/A | N/A | | | |
| | • Hooter | N/A | N/A | N/A | | | |
| 8 N | MOEFA | N/A | N/A | N/A | | | |
|)9 F | Public Address System. | N/A | N/A | N/A | | | |
| 10 . A | Automatic Sprinkler System. | | | | | | |
| | Basement | N/A | N/A | N/A | | | |
| | • upper floor | N/A | N/A | N/A | | | |
| | sprinkler above false ceiling | N/A | N/A | N/A | | | |
| 11 I | Internal Hydrants | | - 000 · | | | | |
| | size of riser/down-comer | N/A | N/A | N/A | | | |
| 2 | Number of hydrants per floor | N/A | N/A | N/A | | | |
| | Hose box | N/A | N/A | N/A | | | |
| 12 | Yard Hydrants. | | | | | | |
| | Total number of hydrants | N/A | N/A | N/A | | | |
| | Hose box | N/A | N/A | N/A | | | |
| 13 | Pumping Arrangements. | | | | | | |
| | > Ground Level | | | | | | |
| | Discharge of main pump | N/A | N/A | N/A | | | |
| | Head of main pump | N/A | N/A | N/A | | | |
| | Number of main pumps | N/A | N/A | N/A | | | |
| | Jockey pump out put | N/A | N/A | N/A | | | |
| | Jockey pump head | N/A | N/A | N/A | | | |
| | Standby pump out put | N/A | N/A | N/A | | | |
| | Standby pump head | N/A | N/A | N/A | | | |
| | Auto starting /manual stopping | N/A | N/A | N/A | | | |
| | Pump house access | N/A | N/A | N/A | | | |
| | > Terrace Level | | | | | | |
| | Discharge of pump | N/A | N/A | N/A | | | |
| | Head of the pump | N/A | N/A | N/A | | | |
| | • Power supply | N/A | N/A | N/A | | | |
| | Auto starting of pump | N/A | N/A | N/A | | | |
| 14 | Captive Water Storage for Fire Fighting. | | | | | | |
| | Underground tank capacity | N/A | N/A | N/A | | | |
| | Draw-off connection | N/A | N/A | N/A | | | |
| | Fire service inlet | N/A | N/A | N/A | | | |
| | Access to tank | N/A | N/A | N/A | | | |
| | Overhead tank capacity | N/A | N/A | N/A | | | |
| 15 | Exit Signage. | N/A | N/A | N/A | | | |

| 16 | Provision of Lifts. | | | | | |
|----|--|-----|-----|-----|--|--|
| | Pressurization of lift shaft | N/A | N/A | N/A | | |
| | Pressurization of lift lobby | N/A | N/A | N/A | | |
| | Communication in lift car | N/A | N/A | N/A | | |
| | Firemen's grounding switchLift signage | N/A | N/A | N/A | | |
| | | N/A | N/A | N/A | | |
| 17 | Standby Power Supply | N/A | N/A | N/A | | |
| 18 | Refuge Area. | | | | | |
| | Total area | N/A | N/A | N/A | | |
| | Location | N/A | N/A | N/A | | |
| 19 | Fire Control Room | | | | | |
| | Detector system panel | N/A | N/A | N/A | | |
| | Flow switch panel | N/A | N/A | N/A | | |
| | PA system panel | N/A | N/A | N/A | | |
| | Battery backup | N/A | N/A | N/A | | |
| | Building floor plans | N/A | N/A | N/A | | |
| 20 | Special Fire Protection Systems for Protection of Special Risks, if Any: | N/A | N/A | N/A | | |

Note:- This Fire Safety Certificate does not cover the new building blocks (Ground plus three storey building) for which Shortcomings was issued vide letter no F6/DFS/MS/2018/1436 dated 06/04/2018 by this department.

The Fire protection systems provided in the building were Tested/Checked and found functional, at the time of inspection.

Keeping in view of the compliance of the minimum standards of fire prevention and fire safety measures required as per circular No.F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated-01/03/11, FSC may please be renewed leaving out new building blocks as per past practice.

(Nagender Singh ADO(Shahdara)

DO(ED)

DY. CAN HON

DOCKD) MIZ

FT is submitted please