## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/BNQT/2021/SZ/ )/6

Dated: 12/02/202/

## FIRE SAFETY CERTIFICATE

Certified that Shyama Banquets (A unit of Shyama Infotech Pvt. Ltd.) located at RZ-1738/37, Tugalakabad Extension, New Delhi comprised Ground + 01 Upper floor. The premises was inspected by officer concerned of this department on 18/01/2021 in the presence of Mr.Umesh Singh(Manager) of the banquet hall and observed that said banquet hall have complied with the fire safety and fire prevention requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class A "Banquet Hall" with effect from 1.2.2.2.1.......... for a period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued 12/02/2021 at New Delhi by

Director
Delhi Fire Service

Copy to: -

- 1. The Executive Engineer (Bldg), SDMC, Jal Vihar, Lajpat Nagar, New Delhi-110024
- 2. Sh.Ranjit Singh (Director), Shyama Banquets, RZ-1738/37, GF & FF, Tughlakabad Extn. New Delhi-110019.

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1	Name	& Address of the Building	Shyama Banquets (A unit of Shyama Infotech Pvt. Ltd.) at Ground and First floor at RZ- 1738/37, Tughlakabad Extension, New Delhi				
2	Type	of Occupancy	Group-D, Assembly Building				
3	Build	ing Comprised of	Ground + 01 upper floor				
4	Type of Case		New				
5	Details of Previous NOC		Nil				
6	Fire Safety Directives Letter No		Nil				
7	Date of	Date of Inspection 18/01/2021					
8	8 Name of the Inspecting Officers ADO Avtar Singh				2		
9	from t	& Designation of Officers he building side	Mr. Umesh Singh (Manager)				
10		of construction	2019				
11	Applicant letter No. Application no. 2020101907854 dated 17/12/2020						
S. No		um standards on Fire Prevention re Safety U/R 33	BBL/NBC Requirement	Provided at Site	Remarks MR/NMR		
1	Access to Building.						
	•	Road width	6 m	7 m	MR		
	•	Gate width	4.5 m	4.5 m (02 nos)	MR		
	•	Width of internal road	-N/A-	-N/A-	-N/A-		
2	Numb	er, width, type & arrangement					
	a) Number of Staircase						
	>	Upper floors	02	02	MR		
	>	Basement	-N/A-	-N/A-	-N/A-		
	b) W	idth of Staircase		× .	2		
	>	Upper floors	1.50 m & 2.0 m	1.50 m & 2.0 m	MR		
	7	Basement	-N/A-	-N/A-	-N/A-		
	c) Pr	otection of exits					
		Fire check door	Required	Provided	MR		
		Pressurization	-N/A-	-N/A-	-N/A-		
	d) No. of continuous staircase to terrace		Two	Two	MR		
		idth of corridor	-N/A-	-N/A-	-N/A-		
		or size	02 nos of 02 m	02 nos of 02 m	MR		
3	Comp	artmentation.					
	•	Fire check door.	Required	Provided	MR		
	•	Sealing of electrical shafts. Fire rating of shaft door.	Required	Provided	MR		
		Water curtain	-N/A-	-N/A-	-N/A-		
	•	Fire dampers.	-N/A-	-N/A-	-N/A-		
	C		-N/A-	-N/A-	-N/A-		
4.	Smok	e Management system.		Т	w - 2 h		
		Basement	-N/A-	-N/A-	-N/A-		
	T71 -	Upper floors	12 ACPH	Provided	MR		
5.							
		Total numbers	10 nos	10 nos	MR		
		Types	ABC & CO <sub>2</sub>	ABC, & Co2	MR		
	E	ISI Marking	ISI marked	Provided	MR		
6.	First Aid Hose Reels.						
		Total numbers on each floor	01	Provided	MR		
	•	Length of hose-reel hose.	30 m	Provided	MR		

	Type of detectors	-N/A-	-N/A-	-N/A-			
	Location of Main Panel	-N/A-	-N/A-	-N/A-			
	<ul> <li>Location of Repeater Panel</li> </ul>	-N/A-	-N/A-	-N/A-			
	Alternate source of power	-N/A-	-N/A-	-N/A-			
	Hooter's location	-N/A-	-N/A-	-N/A-			
8.	MOEFA	Required	Provided	MR			
9.	Public Address System	-N/A-	-N/A-	-N/A-			
10.	Automatic Sprinkler System						
	Basement.	-N/A-	-N/A-	-N/A-			
	Upper floors	-N/A-	-N/A-	-N/A-			
	<ul> <li>Sprinkler above false ceiling</li> </ul>	-N/A-	-N/A-	-N/A-			
11.	Internal Hydrants.						
	Size of Riser / Down-comer	100 mm	Provided	MR			
	<ul> <li>Number of Hydrant per floor</li> </ul>	Required	Provided 01 no	MR			
	<ul> <li>Hose box.</li> </ul>	Required	Provided 01 no	MR			
12.	Yard Hydrants.						
	Total number of hydrants.	-N/A-	-N/A-	-N/A-			
	<ul> <li>Hose box.</li> </ul>	-N/A-	-N/A-	-N/A-			
13.	Pumping arrangements.						
	Ground Level						
	Discharge of main pump.	-N/A-	-N/A-	-N/A-			
	<ul><li>Head of main pump.</li></ul>	-N/A-	-N/A-	-N/A-			
	Number of main pumps.	-N/A-	-N/A-	-N/A-			
	Jockey Pump output.	-N/A-	-N/A-	-N/A->			
	Jockey Pump head.	-N/A-	-N/A-	-N/A-			
	Standby Pump output.	-N/A-	-N/A-	-N/A-			
	Standby Pump head.	-N/A-	-N/A-	-N/A-			
	Auto Starting/Manual stopping.	-N/A-	-N/A-	-Ñ/Á-			
	Pump house access.	-N/A-	-N/A-	-N/A-			
	Terrace Level	1.00.2.2					
	<ul><li>Discharge of pump.</li></ul>	900 LPM	900 LPM	MR			
	<ul><li>Head of pump.</li></ul>	35 m	35 m	MR			
	Power supply.	Required	Provided	MR			
	> Auto starting of pump.	Required	Provided	MR			
14.	Captive water storage for firefighting.						
	<ul> <li>Underground tank capacity.</li> </ul>	-N/A-	-N/A-	-N/A-			
	Draw-off connection.	-N/A-	-N/A-	-N/A-			
	Fire Service Inlet.	-N/A-	-N/A-	-N/A-			
	> Access to tank.	-N/A-	-N/A-	-N/A-			
	Overhead tank capacity.	20,000 ltrs	Provided	MR			
15.	Exit Signage.	Required	Provided	MR			
16.	Provision of Lifts.						
	Pressurization of lift shaft.	-N/A-	-N/A-	-N/A-			
	<ul> <li>Pressurization of lift lobby.</li> </ul>	-N/A-	-N/A-	-N/A-			
	Communication in lift car.	-N/A-	-N/A-	-N/A-			
	• Fireman's switch.	-N/A-	-N/A-	-N/A-			
	Lift signage.	-N/A-	-N/A-	-N/A-			
17	Standby Power Supply	Required	Provided	MR			
18.	Refuge Area	<u> </u>		1,00			

-		Compared to the control of the contr						
	•	Lift signage.	-N/A-	-N/A-	-N/A-			
17	Standby Power Supply		Required	Provided	MR			
18.	Refu	efuge Area						
	•	Total area	-N/A-	-N/A-	-N/A-			
	•	Location	-N/A-	-N/A-	-N/A-			
19.	Fire (	Control Room.						
:	•	Detector System Panel.	-N/A-	-N/A-	-N/A-			
	•	Flow Switch Panel.	-N/A-	-N/A-	-N/A-			
		PA system Panel. Battery backup	-N/A-	-N/A-	-N/A-			
		Building floor plan	-N/A-	-N/A-	-N/A-			
		Zonanig neor plan	-N/A-	-N/A-	-N/A-			
20.		rial Fire Protection System for rotection of special Risk, if any.	Required	Provided 02 ABC type fire extinguishers near elect. Panel	MR			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 37 of the Delhi Fire Service Rules 2010.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name : Avtar Singh Designation: ADO (MR)

DO (SD)

On CML + DIOH

DUPOSES

CFO.

21/1

- 11119n

P15862

016/52