GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No. F6/DFS/MS/GH/2021/BHOT) 128

Dated: 18/02/2021

FIRE SAFETY CERTIFICATE

Certified that the **Raj Vatika** (**A unit of Khurana Hospitality**) located at 876 East Park Road,, Khajoor Road (opposite main gate Ajmal Khan Park), Karol Bagh , New Delhi-05, comprised of ground floor having party hall, office, kitchen and 02 store room at mezzanine floor only, was earlier granted FSC by this department vide letter No.F6/DFS/MS/BANQ/2015/NDZ/729 dated 18/04/2018. The premises was re-inspected by the officer concerned of this department on **08/02/21** in the presence of Mr. Varun and found that the said banquet hall has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class – Assembly, **Banquet hall (Ground floor only)** with effect from -18/02/2121--for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- 18/-2/3-2-) at New Delhi by.

(Dr. S. K. Tomar)
Dy. Chief Fire Officer
Delhi Fire Service

an

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager,

Raj Vatika (A unit of Khurana Hospitality), located at 876 East Park Road, Khajoor (opposite main gate, Ajmal Khan Park), Karol Bagh, New Delhi-05

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. The flammable material use for interior decoration, if any, shall strictly be prohibited.

INSPECTION REPORT					
1. Name & address of the building		Raj Vatika located at 876, East Park Road			
		Khajoor Road (opposite Ajmal khan park			
) Karol Bagh, New Delhi			
2.	Type of occupancy:-	Assembly – Banquet at ground floor.			
3	Type of case:-	Renewal			
4	Details of previous FSC:-	No. F6/DFS/MS/BANQ/2015/NDZ/729			
-	Details of previous 155	dated 18/04/18.			
5	Fire safety directives No	N/A			
6	Date of inspection:-	08.02.2021			
7	Name of the inspecting officer:-	Sh. Ravinder singh (ADO/CC)			
'		Sh. Rajinder Atwal, DO (CD)			
10		8			
8	Name & designation of officer	Mr, Varun			
	From the building side:-				
9	Year of construction:-	2011-12			
10	Applicant's letter No:-	Email khuranahospitalities 1@gmail.com			
		dated 27.01.21			

Building is comprised of ground floor having party hall, kitchen, office and two store room at mezzanine floor.

Old case

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			1160
	1) Road width	09mtr	20mtr.	MR
	2) Gate width	06 mtrs	Directly approaches from amin road	MR
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arrar	gement of Exits		is the second se
	A. Number of staircases			27/4
	1. Upper floors	N/A	N/A	N/A
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	N/A	N/A	N/A
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	02 mtr.	2.10, 2.0 & 1.50 mtr.	MR
3.	Compartmentation			
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A



4) Water curtain 5) Fire Dampers Smoke Management System 1) Basements 2) Upper floors Fire Extinguishers 1) Total numbers 2) Types 3) ISI marking	N/A N/A N/A 12 ACPH	N/A N/A N/A Natural	N/A N/A N/A MR
Smoke Management System 1) Basements 2) Upper floors Fire Extinguishers 1) Total numbers 2) Types 3) ISI marking	12 ACPH 10 Nos.		
1) Basements 2) Upper floors Fire Extinguishers 1) Total numbers 2) Types 3) ISI marking	12 ACPH 10 Nos.		
Fire Extinguishers 1) Total numbers 2) Types 3) ISI marking	10 Nos.	Natural	MR
1) Total numbers 2) Types 3) ISI marking			
1) Total numbers 2) Types 3) ISI marking		1	
2) Types 3) ISI marking		10 Nos.	MR
3) ISI marking	ABC & CO2	ABC & CO2	MR
	Required	Provided	MR
First-Aid Hose Reel			
1) Total number at each floor	04	04	MR
2) Length of hose reel hose	30 mtr.	30 mtr.	MR
3) Nozzle diameter	05 mm	05 mm	MR
Automatic Fire Detection & Ala	arming System		
1) Type of detectors	N/A	N/A	N/A
			N/A
			N/A
	N/A	N/A	N/A
			N/A
			MR
	*		MR
	Required	TTOVICCO	IVIIC
 	N/A	N/A	N/A
			N/A
			N/A
	14/11	1471	14/71
	100mm	Provided	MR, GF only
			MR, GF only
		- I - I - I - I - I - I - I - I - I - I	MR, GF only
	011103	TTOVICO	Tille, or only
	N/A	N/A	N/A
			N/A
	N/A	N/A	N/A
			N/A
	11/12		
	N/A	N/A	N/A
		N/A	N/A
			N/A
		N/A	N/A
, , , ,	N/A	N/A	N/A
		N/A	N/A
	N/A	N/A	N/A
	Commission Commission		
a) Discharge of pump	450 LPM	450 LPM	MR
b) Head of pump	30 mtr.	30 mtr.	MR
c) Power supply	Required	Provided	MR
d) Auto starting of pump	Required	Provided	MR
	Fighting		
Under ground tank	N/A	N/A	N/A
a) Draw-off connection	N/A	N/A	N/A
	2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump out put e) Jockey pump head f) Stand by pump head f) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire 1) Under ground tank capacity	2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Required Automatic Sprinkler System 1) Basement 2) Upper floors N/A 3) Sprinkler above false ceiling N/A 3) Sprinkler above false ceiling N/A Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Vard Hydrants 1) Total number of hydrants N/A 2) Hose box N/A Pumping Arrangement 1) Ground level A) Discharge of main pump b) Head of main pump C) Number of main pump A) Jockey pump out put C) Number of main pump N/A A) Jockey pump head N/A A) Jockey pump head N/A A) Jockey pump head N/A A) Auto starting/Manual stopping 2) Terrace level A) Discharge of pump A) Head of pump C) Power supply Auto starting of pump Required Captive Water Storage for Fire Fighting 1) Under ground tank capacity	2) Location of main panel N/A N/A 3) Location of repeater panel N/A N/A 4) Alternate source of power N/A N/A 5) Hooter's Location N/A N/A MOEFA Required Provided Public Address System Required Provided Automatic Sprinkler System 1) Basement N/A N/A 3) Sprinkler above false ceiling N/A N/A 1) Size of riser/down-comer 100mm Provided 2) Number of hydrants per floor 3) Hose box Provided Yard Hydrants 1) Total number of hydrants N/A N/A 2) Hose box N/A N/A Pumping Arrangement 1) Ground level N/A N/A a) Discharge of main pump N/A N/A c) Number of main pump N/A N/A d) Jockey pump out put N/A N/A c) Number of main pump N/A N/A h) A N/A c) Number of main pump N/A N/A h) A N/A c) Number of Main pump N/A N/A h) A N/A c) Number of main pump N/A N/A h) A N/A c) Number of main pump N/A N/A h) A N/A h) A N/A c) Terrace level a) Discharge of pump A 50 LPM b) Head of pump 30 mtr. c) Power supply Required Provided Captive Water Storage for Fire Fighting 1) Under ground tank N/A

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	10,000 ltr.	10,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	. N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for any: ABC & CO ²	N/A		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/BANQ/2015/NDZ/729 dated 18/04/18, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the inspecting officer

Signature of the Inspecting Officer

Name: - Rajinder Atwal Designation: - DO (CD)

Name: Ravinder Singh Designation: ADO (CC)

Dycho (MDZ)

(* Demy

12/2

As approvement pripat up for read ferred and En