## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2021/SZ/

Dated: 17 / 2 / 2021

## FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Co-ed Vidyalaya, Masjid Moth South-II, New Delhi- 110049 (ID- 1925246) comprised of ground plus three upper floors was granted Fire Safety Certificate by this department vide letter No F6/DFS/MS/School/2018/SZ/928 Dt. 04/05/2018. The said premises was reinspected by officer concerned of this department on 15/01/2021 in presence of Dr. Santhosh Kumar (Principal) of the school and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the building is fit for occupancy class "Educational Building Group – B" with effect from 17/2 / 2021 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 17 / 2-2021 at New Delhi by

(Sunil Chawdhary)
Dy. Chief Fire Officer (SZ)
Delhi Fire Service

Copy to: -

- 1. The Principal, Sarvodaya Co-ed Vidyalaya, Masjid Moth South-II, New Delhi- 110049
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi.

## Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. This certificate cannot be treated as regularization of unauthorized construction, if any.
- 5. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

	INSPECT	ON REPORT			
1	Name & Address of the Building	Sarvodaya Co-ed Vidyalaya Masjid Moth, South			
		Ex-II, New Delhi 110049 (ID-1925246)			
2	Type of Occupancy	Educational, Grou	up-B (School)		
3	Building Comprised of	Ground + three upper floors			
4	Type of Case	Renewal			
5	Details of Previous NOC	F6/DFS/MS/Scho	ool/2018/SZ/928 Dt. 04/0	5/2018	
6	Fire Safety Directives Letter No	Nil			
7	Date of Inspection	15/01/2021	i		
8	Name of the Inspecting Officers	Sh. Rajesh Kumar ADO (BCP)			
9	Name & Designation of Officers	Dr. Santhosh Kumar (Vice-Principal)			
	from the building side				
10	Year of construction	1985			
11	Applicant letter No.	Gmail Dated 13/01/2021			
S. No	Minimum standards on Fire Prevention	As Per Old	Provided at Site	Remarks	
	and Fire Safety U/R 33	NOC		MR/NMR	
1	Access to Building.				
	Road width	Required	6 mtr	MR	
	Gate width	-NA-	-NA-	-NA-	
	<ul> <li>Width of internal road</li> </ul>	-NA-	-NA-	-NA-	
2	Number, width, type & arrangement of exits.				
	a) Number of Staircase				
	Upper floors.	02 No's	Provided	MR	
	Basement floor.	-NA-	-NA-	-NA-	
	b) Width of Staircase				
	▶ Upper floors	1.50 m	1.40 mtr each	MR	
	Basement floor	-NA-	-NA-	-NA-	
	c) Protection of exits			***************************************	
	Fire check door	-NA-	-NA-	-NA-	
	Pressurization	-NA-	-NA-	-NA-	
	d) No. of continuous staircase to terrace	Required	Provided	MR	
	e) Width of corridor	1.50 mtr	Provided	MR	
	f) Door size	1 mtr	1 mtr	MR	
3	Compartmentation.	1 11101	/		
	Fire check door.	-NA-	-NA-	-NA-	
	Sealing of electrical shafts.	-NA-	-NA-	-NA-	
	Fire rating of shaft door.	-NA-	-NA-	-NA-	
	Water curtain	-NA-	-NA-	-NA-	
	• Fire dampers.	-NA-	-NA-	-NA-	
4.	Smoke Management system.	/			
7.	Basement	-NA-	-NA-	-NA-	
	Upper floors	-NA-	-NA-	-NA-	
5.	Fire Extinguishers.	-1477.	TALX	1477	
٥.	Total numbers	16 no's	17 Nos	MR	
	Total numbers     Types	ABC / co2	ABC & co2 Type	MR	
	ISI Marking	ISI mark	Provided	MR	
6	First Aid Hose Reels.	131 mark	TTOVICCO	IVIIC	
6.	- 1 1 A	02 No's	Provided	MR	
		30 m	Provided /	MR	
	Length of hose-reel hose.				
	Nozzle Diameter	5 mm	Provided -	MR	
7	Automatic fire detection & alarming system.		3		
	Type of detectors	-NA-	-NA-	-NA-	
	Location of Main Panel	-NA-	-NA-	-NA-	
	Location of Repeater Panel	-NA-	-NA-	-NA-	

		20 100 100 1000 1000 1000 1000 1000 100		
	Alternate source of power	-NA-	-NA-	-NA-
	<ul> <li>Hooter's location</li> </ul>	-NA-	-NA-	-NA-
8.	MOEFA	-NA-	-NA-	-NA-
9.	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System			
	Basement	-NA-	-NA-	-NA-
	<ul> <li>Upper floors</li> </ul>	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.			
	Size of Riser/Down-comer	-NA-	100 mm	-NA-
	Number of Hydrant per floor	-NA-	02 Nos	-NA-
	Hose box.	-NA-	02 Nos	-NA-
12.	Yard Hydrants.	1172	02 1103	-1421
A Art .	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	
12		-INA-	-IVA-	-NA-
13.	Pumping arrangements.			
	Ground Level	1	* * *	
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	> Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level			
	Discharge of pump.	450 LPM	Provided	MR
	Head of pump.	40 m	Provided	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.			
***************************************	Underground tank capacity.	-NA-	-NA-	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	10,000 ltrs	Provided	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	100001100	11011606	17110
2.00	Pressurization of lift shaft.	-NA-	-NA-	-NA-
17	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	Fireman's switch.	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Lift signage.  Standby Parent Sandby			
17.	Standby Power Supply	-NA-	-NA-	-NA-
18.	Refuge Area	BTA	TATA	
	Total area	-NA-	-NA-	-NA-
	Location	-NA-	-NA-	-NA-
19.	Fire Control Room.			
	Detector system panel.	-NA-	-NA-	-NA-
	• Flow switch panel.	-NA-	-NA-	-NA-
	PA system panel.	-NA-	-NA-	-NA-
	Battery backup.	-NA-	-NA-	-NA-
	- 1111	A 14 A	4.12 A	
	Building floor plan	-NA-	-NA-	-NA-

	$\mathcal{N}^{-6}$					
	pecial Fire Protection System for the rotection of special Risk, if any.	-NA-	-NA-	-NA-		
ound son revention 6/DFS/M	he fire protection systems provided me observations at the time of inspect Keeping in view of the de m and fire safety measures as req IS/School/2018/SZ/928 Dt. 04/05/2018 ecommended.	ction. emed compliance of uired under the rule	of the minimum stan	dard on fire		
A	ccordingly, DFA is put up for appro	val and signature ple	ease.			
			Signature of the Inspector Name: Sh. Raj Design: ADO (	esh Kumar		
	Decolor Surfaces  Decolor  Dec	PI PI	please	My 16/2		