FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE [Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE **NEW DELHI**

No.F6/DFS/MS/SZ/2021/ 12 \$

Dated: 17/02/2021

FIRE SAFETY CERTIFICATE

Certified that the building Sh. Mool Chand Dua Memorial Society, Plot No.1, Dwarka, New Delhi.comprised of ground plus one upper floor owned/ occupied by Sh. Mool Chand Dua Memorial Society was granted Fire Safety Certificate vide this office letter no F.6/DFS/MS/2017/SZ/1755 Dated 07/12/2017. The said building was re-inspected by the officer concerned of this department on 06/02/2021 in presence Sh Sanjay Gupta (representative) and found that the premises have deemed complied fire prevention & fire safety requirements in accordance with rule 33 of the Delhi Fire Service and that the building is fit for occupancy class D "Assembly building" (Temple) with effect __ for a period of three years, subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 as printed below.

Issued on ... 17 02 2021. at New Delhi by.

(Sunil Chaudhary) Dy. Chief Fire Officer, Delhi Fire Service.

Copy to:

- 1. Sh Sanjay Gupta. Mool Chand Dua Memorial Society, Plot No. Dwarka, New Delhi-110075
- 2. The Jt. Director (L&I) Bldg. DDA Building Section INA Vikas Sadan, New Delhi.

Following fire safety directives must be adhered to:-

- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

The trained staff should be available round the clock.

4 Any deviations w.r.t. construction shall be verified by the concerned building sanctioning

5 The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its

Basement shall be used strictly as per building bye laws.

The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

Re inspection to see the compliance of shortcomings communicated vide letter no. F6/DFS/MS/SZ/2020/3057dated 15/12/2020 are complied

INSPECTION REPORT

1. Name & address of the building: Sh. Mool Chand Dua Memorial Society, Located at Plot No.1, Dwarka, New Delhi.

: Assembly Building (Ground + 01 Upper Floors) 2. Type of Occupancy

: Renewal 3. Type of Case

4. Details of previous NOC : F.6/DFS/MS/2017/SZ/1755 Dated 07/12/2017

5. Fire Safety directives Letter No.: F6/DFS/MS/BP/2010/1180 dated 23-04-10

6. Date of inspection : 06-02-2021

7. Name of the Inspecting Officer: Udai vir singh, ADO (DWK)

8. Name and designation of Officer

from the building side : Sh Sanjay Gupta

No. of Students= 100 No. of rooms = Two Halls Plot area=361.11Sq.m² Covered area=138sqm²

9. Year of Construction : 2013

10. Applicant's letter No. : Email dated 01-02-2021

Access of building Road width	Requirements 9 m	site	MR/NMR		
 Road width 	9 m				
	9 m				
	7 111	9 m	MR		
 Gate width 	5 m	5 m	MR NA		
 Width of internal road 	NA	NA			
	ements of exits				
 Upper floors 			MR		
 Basements 	NA	NA	NA		
b. Width of staircases					
 Upper floors 			MR(old case		
	NA	NA			
c. Protection of exits					
 Fire check door 	NA	NA	NA NA NA		
 Pressurization 	NA	NA			
	NA	NA			
	NA	NA			
	2 m	Old case MR	IR(Being Old case).		
	 Aumber, width, Type & Arrang a. Number of staircases Upper floors Basements b. Width of staircases Upper floors Basements c. Protection of exits Fire check door 	Number, width, Type & Arrangements of exits a. Number of staircases • Upper floors • Basements b. Width of staircases • Upper floors • Basements c. Protection of exits • Fire check door • Pressurization d. No of continuous staircase to terrace e. Width Of Corridor	Number, width, Type & Arrangements of exits a. Number of staircases • Upper floors • Basements • Upper floors • Upper floors • Basements • Upper floors • Basements • C. Protection of exits • Fire check door • Pressurization d. No of continuous staircase to terrace e. Width Of Corridor A Arrangements of exits 2 Nos. NA NA NA NA NA NA NA NA NA N		

				1,0		•	
					1		
3.	Compartmentation	771		274		NA	
	Fire check door	NA			NA		
	Sealing of electrical	NA		NA		NA	
	shafts	NA		NA	-	NA	4
	• Fire Rating of shaft door	INA		INA		INA	
	Water Curtain	NA		NA		NA	
	Fire Dampers	NA		NA			1
	The Bampers						
4.	Smoke managements System	i.					
	• Basements	NA		NA		NA	-
	 Upper floors 	12 a/	c per hour	Natura			MR
_	Di Di i			Ventila	tion	1 0	
5.	Fire Extinguishers	(D!1	1	MI	
	• Total numbers	6 nos		Provide	au	MF	
	• Types		CO ₂ &ABC ISI marked		Provided		
6.	IS marking First – Aid Hose Reels	10111		Tiovide	- Cu	MF	
0.					Provided		3
-,	floor			1000		1411	
	 Length of hose reel 	36 m		36 m		MF	?
	hose	5 mn	n	5 mm			3
	 Nozzle diameter 						
7.	Automatic fire detection and ala	rming	system		red		
	 Type of detectors 		NA	NA		NA	
	 Location of Main Panel 		NA	NA		NA	
	 Location of Repeater Par 		NA	NA		NA NA	
	Alternate source of power	er	NA				
	Hooters' Location	NA				NA	
8.	MOEFA		Required			MR	
9.	Public Address System		Required	Provide	d	MR	
10.	Automatic Sprinkler System Basements	NA	*	NA		NA	
	Upper Floor	NA		NA NA		NA	
	Sprinkler above false	NA		NA		NA	
	ceiling					187	
11.	Internal Hydrants						
	Size of riser/down-come	er	100 mm		Prov	ided	MR
	Number of hydrants per	floor	One		One		MR
	Hose Box		Required		Required		MR
12.	Yard Hydrants						
	 Total number of hydrant 		-	NA		NA	
	Hose Box	NA	1	NA		NA	THE RESERVE OF THE PERSON OF T
					. 331		
				*	Ψ,		
					4		
					-		
				7			
			•				

13.	Pumping Arrangements							16. 3 8 . 5	
	Ground Level						/		
	 Discharge of main pump 		NA	NA			NA		
	> Head of main pump		NA NA NA NA NA NA NA NA		NA NA NA NA NA		NA NA NA NA NA NA NA		
	> Number of main pumps								
	Jockey pump out put								
	Jockey pump head								
	Standby Pump out put								
	Standby Pump Head								
	Auto Staring/Manual						NA		
	stopping				_	× 4	D.T.A		
-	Pump House Access		NA NA			A	NA	1	
	• Terrace level			0.01	_	Provided		MR	
	Discharge of pump		450 lpm,1	801pm	1		-	MR	
	> Head of the pump		35 m		35 m			MR	
	> Power supply		Required		Provided			MR	
	> Auto starting of pump Required			Provided			IVIR		
14.	Captive water Storage for fire fig	ghti	ng	l N	IA		NA	1	
	Under ground tank	NA	A	1	IA		INT	1	
	capacity	NA	Λ		IA		NA		
	> Draw of connection	NA NA			NA			NA	
	Fire service inlet	NA NA			JA		NA		
	Access to tank				Provided		MR		
	Overhead Tank 10,000 litres		1	Tiovided					
15	capacity Exit Signage	Re	equired		Provided		MR		
16.	Provision of Lifts	100							
10.	> Pressurization of Lift		NA		NA		N.	NA	
	Shaft						2 2 2 2 3		
	Pressurization of lift lobby		NA NA		NA		A		
distribution of the second									
AL PROPERTY OF THE PROPERTY OF	> Communication in lift C	ar	NA	1	NA		NA		
Lance Control	> Fireman's Grounding		NA		NA		NIA		
Carrotte	Switch						N	NA	
Party ACOnsole	➤ Lift Signage		27.4		NA		NA		
Constitution of			NA D		G Set 62		MR		
17.	Standby power supply		Tradition .				10.	IVIK	
	D. C. A.			KVA	7				
18.			NA	-	NA	3	N	IA .	
	Total areaLocation		NA NA		NA		NA		
19.			A 14. A						
19.	> Detector system panel	N	IA		N	4	N	IA	
1	> Flow Switch Panel	-	IA .		NA		NA		
	> PA System Panel	-	NA NA		NA		N	IA .	
	> Battery backup		NA		NA		NA		
	> Building Floor Plans NA			NA			NA		
2									
						-			

T

 Special Fire Protection Systems for Protection of	NA	CO2 Fire extinguisher provided near	MR
special Risks, if any;		electric panel	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F.6/DFS/MS/2017/SZ/1755 Dated 07/12/2017 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer Name

Designation

Designation

Dy con jen to top Jor Sign ple

Sin Ft letter is put up Jor Sign ple

Dycroks2

1

m,5. W