FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/GF/2021/SZ/ Andi 129

Dated 18/02/2021

FIRE SAFETY CERTIFICATE

Issued on Solly 2021 at New Delhi.

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER (S.Z.).

Copy to :-

- 1. Authorized Signatory, M/s Sirifort Auditorium Complex (Auditorium 1, 2, 3 & 4) located at August Kranti Marg, New Delhi-110049.
- 2. Join Commissioner of Police (Lic.), PS Defence Colony, New Delhi-110024.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on <u>WWW.dfs.Delhigovt.nic.in</u>

1, 2, 3 & 4) located at August Kranti Marg, New Delhi-110049. : Assembly Type of Occupancy 3. Building Comprised of : Basement (Storage & Services), ground plus one upper floor. (Auditorium-1 having 1865 seats at ground and first floor balcony only, Auditorium -2 having 72 seats at ground floor only). Audi-1, 3 & 4 are in same interconnected block and Audi-2 is in separate block. Both blocks are having basement but non interconnected. : Renewal 4. Type of Case 5. Details of previous NOC: F6/DFS/MS/2017/Audi/956 dated 04/07/2017 6. Fire Safety directives Letter No.: Nil : 09/02/2021 7. Date of inspection 8. Name of the Inspecting Officer: A.D.O. (S.J.) 9. Name and designation of Officer : Sh. Omparkash (Electrical Engineer) from the building side : 1982 10. Year of Construction : 69/21/2012-FFD (SF) dated 03/02/2021 11. Applicant's letter No. Provided at Remarks Requirements / Minimum standards on fire S MR/NMR **Existing Fire** site prevention and fire safety No Protection System U/R 33 Access of building 1. MR 15m 9_m Road width MR 5m 5m Gate width . N/A N/A N/A Width of internal road Number, width, Type & Arrangements of exits 2. a. Number of staircases 8 MR 8 Upper floors MR 6 6 Basements Width of staircases MR 1.5m 1.5m Upper floors . MR 1.5m 1.5m Basements c. Protection of exits MR Provided Required Fire check door N/A N/A N/A Pressurization 2 MR 2 No of continuous d. staircase to terrace N/A N/A N/A Width Of Corridor Audi-I=7 at GF & 8 at balcony MR Door Size Required level, Audi-II=4 at GF, Audi-III=2at GF & 2 at balcony level, Audi-IV=2 at GF level (Each exit door is 1.35m wide) Compartmentation 3. Provided MR Required Fire check door MR Provided Sealing of electrical Required shafts N/A N/A N/A Fire Rating of shaft N/A N/A N/A Water Curtain N/A N/A N/A Fire Dampers Smoke managements System 4. Mechanical Ventilation MR 30 a/c per **Basements** provided &functional hour Exhaust Fans Provided MR 12 a/c per Upper floors hour 5. Fire Extinguishers MR 200 200 Total numbers MR ABC / CO2 Provided Types

6.	First – Aid Hose Reels	t					
	Total numbers on		at MR				
	each floor	GF & 4 at 1 st Floor 1 st Floor		1.45			
	 Length of hose reel hose 	30 m	30 m	MR			
	 Nozzle diameter 	5 mm	5 mm	MR			
7.	Automatic fire detection and alarming system						
	 Type of detector 	Smoke, Heat & Bear		/A			
	 Location of Main 	Ground Floor	N/A N	/A			
	Panel						
	 Location of Repeater Panel 	N/A		/A			
	• Alternate source of power	Required	Provided N	1R			
	Hooters' Location	All Areas	All Areas N	1R			
8.	MOEFA	Required	Provided N	ЛR			
9.	Public Address System	Required	Provided MR				
10.	Fubile Address System						
IU.	P	Required	Provided	MR			
	Control of the party of the par	Required	Provided	MR			
	Upper Floor Sprinkler above false	Required	Provided	MR			
	Sprinkler above false ceiling	Required	Trovided				
11.	Internal Hydrants	150 mm	Provided	MR			
	• Size of riser/down-comer	1	•				
	Number of hydrants per floor	2 at basement, 9 at GF 2 at basement, 9 & 4 at 1 st Floor		MR			
	Hose Box	2 at basement, 9 at GF & 4 at 1 st Floor	2 at basement, 9 at GF & 4 at 1 st Floor	MR			
12.	Yard Hydrants						
	Total number of	10	10	MR			
	hydrants	10	10	MD.			
	Hose Box	10	10	MR			
13.	Pumping Arrangements			**			
	Ground Level	(1.45			
 Discharge of main pump 		2280 LPM	Provided MR				
	Head of main pump	55m		MR			
Number of main pumps		2		MR			
A	Jockey pump out put	225 LPM /		MR			
 Jockey pump head Standby Pump out put Standby Pump Head 		55m		MR			
		2280 LPM	11.1.2.2.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.	MR			
		55m		MR			
	Auto Staring/Manual stopping	Required	Provided	MR			
	> Pump House Access	Required	Provided	MR			
	Terrace level						
	Discharge of pump	N/A	N/A	N/A			
	> Head of the pump	N/A	N/A	N/A			
-	> Power supply	N/A	N/A	N/A			
	> Auto starting of pump	N/A	N/A	N/A			
14							
14	Underground tank	1,00,000 ltr	Provided	MR			
	capacityDraw of connection	Required	Provided	MR			
	Fire service inlet	Required	Provided	MR			

1.7	Exit Signage Required Provided				NAD
15			Required	Provided	MR
16.	Provision of Lifts				
	>	Pressurization of Lift Shaft	N/A	N/A	N/A
	>	Pressurization of lift lobby	N/A	N/A	N/A
		Communication in lift Car	Required	Provided	MR
	>	Fireman's Grounding Switch	Required	Provided	MR
	>	Lift Signage	Required	Provided	MR
17.	Standl	by power supply	Required	Provided	MR
18.	Refug	e Area	N/A	N/A	× **
	>	Total area	N/A	N/A	N/A
	>	Location	N/A	N/A	N/A
19.	Fire control room				
	>	Detector system panel	Required	Provided	MR
	>	Flow Switch Panel	N/A	N/A	N/A
	>	PA System Panel	Required	Provided	MR
	>	Battery backup	Required	Provided	MR
	>	Building Floor Plans	N/A	N/A	N/A
20.	Specia	al Fire Protection	CO2 floodi	ng Provided	MR
		ns for Protection of I Risks, if any;	system		A

Note:- Shortcomings issued by this department vide letter No. F6/DFS/MS/2020/SZ/Audi/3039 dated 14/12/2020 have been complied.

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/2017/Audi/956 dated 04/07/2017 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer
Name : Ashok Kumar Jaiswal

Designation: A.D.O. (S.J.)

Kir Joseph

F. J. p. levs

FIT is added please.