GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2021/ 112

Dated: 21/2/2/

FIRE SAFETY CERTIFICATE

Certified that the Ramayan Guest House located at 7880/A, Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (01 guest rooms + reception), 1st floor to 3rd floor (03 guest rooms at each floor), total 10 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2018/637 dated The premises was re-inspected by the officer concerned of this department on 18/02/21 in the presence of Sh. Majed (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above -Ground + 03 Upper floors, Ground floor (01 guest rooms + reception), 1st floor to 3rd floor (03 guest rooms at each floor) Total - 10 guest rooms only with effect from with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 2-6/2/21-at New Delhi by.

(Dr. S. K Tomar) Dy. Chief Fire officer Delhi Fire Service m

0x 10mm x5/2/21

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi online id no - 2021012209855 dated 07/02/2021.

2. The Manager, Ramayan Guest House at 7880/A, Arakashan Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

This clearance/ FSC shall stand canceled if guest house owner/occupier fails to comply all other condition mentioned in the gazette notification dated 27.05.2019 & clarification issued dated on 25.09.2019 & 17.12.2020 latest by 31.03.2021

2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

4. The trained fire fighting staff should be available round the clock.

5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	D ICD	COTION DEDO	271/V					
4		ECTION REPO		A rokoshon				
1.	Name & address of the building		uest House at 7880/Ar Ganj, New Delhi	A, Alakasilali				
2	Towns of a company	5	Sub Division-A-1					
2.	Type of occupancy:-			est rooms)				
	Gr. + 03 Upper floors (total 10 Guest rooms) Ground floor (Reception + 01 guest rooms), 1 st floor							
	to 3 rd floor (03 guest rooms at each floor)							
3.	Type of case:- Renewal							
	Details of previous FSC:- No. F6/DFS/MS/GH/NDZ/2018/637 dated							
	10/04/18.							
5.	Fire safety directives No N/A							
	Date of inspection:-	18/02/21						
	7. Name of the inspecting officer:- Sh. Ravinder Singh (ADO/CC)							
8.	8. Name & designation of officer							
	From the building side:-	Sh. Maje	d (Manager)					
9.	Year of construction:-	2001						
10.	Applicant's letter No:-	online id no - 20	21012209855 date	d 07/02/2021				
				Old Case				
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks				
	Prevention and fire safety	Existing fire		MR/NMR				
	U/R 33	safety arrangements						
1.	Access to Building	arrangements	-	7 8				
	1) Road width	N/A	03 mtr.	MR				
	2) Gate width	N/A	N/A	N/A				
		N/A	N/A	N/A				
	3)Width of internal road			IN/A				
2.	Number, Width Type & Arr	angement of Ex	alts					
	A. Number of staircases	01 N.	01 Nos.	MR				
	1. Upper floors	01 Nos.		N/A				
	2. Basements	N/A	N/A	IN/A				
	B. Width of staircase		1.0) (D)				
	1. Upper floors	0.80 mtr.	1.0 mtr.	MR				
	2. Basements	N/A	N/A	N/A				
	C. Protection of exits			77/1				
	1. Fire check door	N/A	N/A	N/A				
	2. Pressurization	N/A	N/A	N/A				
	D. No. of continuous	01	01	MR				
	staircase to terrace		1					
	E. Width of corridor	N/A	N/A	N/A				
	F. Door size	01 mtr.	01 mtr.	MR				
3.	Compartmentation							
	1) Fire check door	N/A	N/A	N/A				
	2) Sealing of electrical shafts	N/A	N/A	N/A				
	3) Fire rating of shaft door	N/A	N/A	N/A				
	4) Water curtain	N/A	N/A	N/A				
	5) Fire Dampers	N/A	N/A	N/A				
4.	Smoke Management System							
	1) Basements	30 ACPH	N/A	N/A				
	2) Upper floors	12 a/c per	Natural	MR				
	7 -11	hour						
5.	Fire Extinguishers							
	1) Total numbers	08 Nos.	08 Nos.	MR				
	2) Types	ABC & CO2	ABC & CO2	MR				
	3) ISI marking	Required	Provided	MR				

First-Aid Hose Reel) AD
1) Total number of eachfloor)1		MR
2) Length of hose reel hose			MR
3) Nozzle diameter			MR
Automatic Fire Detection & A	larming Syste	em	T4
1) Type of detectors CO type	Required as per G.N dated	Not provided	Last dt.31.03.21 of compliance extended vide order dt.
Z/ Location of main party			N/A
3) Location of repeater panel			N/A
4) Alternate source of power	N/A		N/A
	N/A	N/A	N/A
	N/A	N/A	N/A
	Required	Provided	MR
Automatic Sprinkler System			
	N/A	N/A	N/A
	N/A	N/A	N/A
3) Sprinkler above false	N/A	N/A	N/A
			N/A
	N/A	N/A	N/A
floor			DT/A
3) Hose box	N/A	N/A	N/A
Yard Hydrants		127/4	DT/A
1) Total number of hydrants			N/A
2) Hose box	N/A	N/A	N/A
Pumping Arrangement			DT/A
1) Ground level			N/A
a) Discharge of main pump	N/A		N/A
b) Head of main pump	N/A		N/A
	N/A		N/A
d) Jockey pump out put	N/A		N/A
e) Jockey pump head	N/A		N/A
f) Stand by pump output	N/A		N/A
g) Stand by pump head	N/A		N/A
h) Auto starting/Manual stopping	N/A	N/A	N/A
2) Terrace level) AD
a) Discharge of pump			MR
b) Head of pump			MR
c) Power supply			MR
d) Auto starting of pump	Required	Provided	MR
Captive Water Storage for I	Fire Fighting		DT/A
1 1	N/A	N/A	N/A
Under ground tank capacity	N/A	N/A	N/A
	1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & A 1) Type of detectors CO type 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & Alarming Syste 1) Type of detectors CO type 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Vard Hydrants 1) Total number of hydrants 2) Hose box N/A Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump pead h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump lequired	1) Total number of eachfloor 2) Length of hose reel hose 30 mtr. 05 mm 05 mm

	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2018/637 dated 10/04/18, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for up to third floor only.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

ADO/ce) As appoined Pripatup for Kun Perusalans
Sanghauft.