GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2021/SZ/ 17-3

Dated: 03/03/2021

FIRE SAFETY CERTIFICATE

Certified that the S. D.M. C. Nigam Pratibha School, Located at DDA Slum-1, Kalkaji, New Delhi 110019 comprised of ground plus first floor plus second floor was granted Fire Safety Certificate by this department vide letter No F.6/DFS/MS/2016/School/SZ/1252 Dated 09/08/2016. The said premises was re-inspected by officer concerned of this department on 23/02/2021 in presence of Smt. Sarestha (Principal) and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with DOE Circular dated 01/03/2011 and that the building is fit for occupancy class "Educational Building Group – B" with effect from 03/03/2011 for a period of Three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 03/03/2021 at New Delhi by

(Sunil Chawdhary)

Dy. Chief Fire Officer (SZ)

Delhi Fire Service

Copy to: -

- 1. The Principal, S. D.M. C. Nigam Pratibha School, Located at DDA Slum-1, Kalkaji, New Delhi 110019
- 2. The Director of Education, SDMC, Civic Centre Minto Road, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. This certificate cannot be treated as regularization of unauthorized construction, if any.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

	INSPECTI	ON REPORT			
1	Name & Address of the Building	S.D.M.C Nigam Pratibha Vidyalaya, DDA, Slum -1, Kalkaji			
		New Delhi 110019 (ID 195873)			
2	Type of Occupancy	Educational, Building Group-B			
3	Building Comprised of	Ground plus two upper floor			
4	Type of Case	Renewal			
5	Details of Previous NOC	F.6/DFS/MS/2016/School/SZ/1252 Dated 09/08/2016 DOE Circular dated 01/02/2011			
6	Fire Safety Directives Letter No		ed 01/02/2011		
7	Date of Inspection	23/02/2021	ADO (DCD)		
8	Name of the Inspecting Officers	Sh. Rajesh Kumar ADO (BCP)			
9	Name & Designation of Officers from the building side	Smt. Sarestha (Principal)			
10	Year of construction				
10		Letter No Nil Dated 30/01/2021			
11	Applicant letter No. Minimum standards on Fire Prevention	DOE Circular Provided at Site Remarks			
S. No		Requirement	riovided at Site	MR/NMR	
1	and Fire Safety U/R 33	Requirement		WHATTINE	
1	Access to Building.	Accessible	6mtr	MR	
	Road width	-NA-	-NA-	-NA-	
	Gate width	-NA-	-NA-	-NA-	
•	Width of internal road	-NA-	-11//1-	-14/1-	
2	Number, width, type & arrangement of exits.				
	a) Number of Staircase	Two	Two	MR	
	> Upper floors.				
	Basement floor.	-NA-	-NA-	-NA-	
	b) Width of Staircase	10.75	1.10	MD	
	Upper floors	1.50 m / 0.75 m	1.42 m each	MR	
	Basement floor	-NA-	-NA-	-NA-	
	c) Protection of exits			77.	
	Fire check door	-NA-	-NA-	-NA-	
	> Pressurization	-NA-	-NA-	-NA-	
	d) No. of continuous staircase to terrace	One	Two	MR	
	e) Width of corridor	1.5 m	2.1 m provided	MR	
	f) Door size	1 mtr	1 mtr	MR	
3	Compartmentation.				
				7.7.4	
	Fire check door.	-NA-	-NA-	-NA-	
	 Sealing of electrical shafts. 	-NA-	-NA-	-NA-	
	Fire rating of shaft door.	-NA-	-NA-	-NA-	
	Water curtain	-NA-	-NA-	-NA-	
	Fire dampers.	-NA-	-NA-	-NA-	
4.	Smoke Management system.				
	Basement	-NA-	-NA-	-NA-	
	Upper floors	-NA-	-NA-	-NA-	
5.	Fire Extinguishers.				
	Total numbers	09Nos	09 Nos	MR	
		ABC / Co2	ABC Type	MR	
	• Types	ADC / C02			
	ISI Marking	ISI mark	Provided	MR	
6.	First Aid Hose Reels.				
~ .	Total numbers on each floor.	Two nos	Provided	MR	
	Length of hose-reel hose.	30m		MR	
			30m		
	Nozzle Diameter	5mr	5mr	MR	

T T				
	 Type of detectors 	-NA-	-NA-	-NA-
	 Location of Main Panel 	-NA-	-NA-	-NA-
	 Location of Repeater Panel 	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	-NA-	-NA-
0 7	Hooter's location	-NA-	-NA-	-NA-
	OEFA	-NA-	NA-	-NA-
9. Pt	ublic Address System	-NA-	-NA-	-NA-
10. A	utomatic Sprinkler System		3//	
	Basement	-NA-	-NA-	-NA-
	Upper floors	-NA-	-NA-	-NA-
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA-
11. In	ternal Hydrants.	1 1 1	3	
	Size of Riser/Down-comer	-NA-	-NA-	-NA-
	 Number of Hydrant per floor 	-NA-	-NA-	-NA-
	 Hose box. 	-NA-	-NA-	-NA-
12. Ya	ard Hydrants.			
5-30	 Total number of hydrants. 	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13. Pu	mping arrangements.		- 1 & A	1471
	Ground Level			
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level		. 1721	-11/71-
	Discharge of pump.	450 LPM	450 LPM	MR
	Head of pump.	40mtr	40mtr	MR
	Power supply.	Required	Required	MR
	Auto starting of pump.	Required	Required	MR
14. Ca	ptive water storage for fire fighting.	Required	Required	IVIK
	Underground tank capacity.	-NA-	-NA-	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	10,000 ltr	10,000 ltr	-NA-
15. Exi	it Signage.	Required	Provided	MR
	ovision of Lifts.	Required	riovided	MR
	Pressurization of lift shaft.	-NA-	-NA-	NTA
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
	• Lift signage.	-NA-		-NA-
17. Sta	ndby Power Supply		-NA-	-NA-
	Tuge Area	-NA-	-NA-	-NA-
IV. IXCI	Total area	NTA	* T 4	
		-NA-	-NA-	-NA-
10	• Location	-NA-	-NA-	-NA-
19. Fire	e Control Room.	,		
	Detector system panel.		NIA	NTA.
		-NA-	-NA-	-NA-

	Flow switch panel.PA system panel.	-NA-	-NA-	-NA-
	Battery backup.	-NA-	-NA-	-NA-
	Building floor plan.	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
20.	Special Fire Protection System for the Protection of special Risk, if any.	-NA-	-NA-	-NA-

found functional at the time of inspection.

keeping in view of the deemed compliance of the minimum standard on fire prevention and safety measures as required under the rules, the FSC issued vide letter no F.6/DFS/MS/2016/School/SZ/1252 Dated 09/08/2016, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

As approved, F.T. Lettel is fourth