GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110 001.**

No.F.6/DFS/MS/School/2021/SZ/179

Dated: 03/03/2021

FIRE SAFETY CERTIFICATE

Certified that the Kamal Public Sr. Sec. School, D-Block, Vikas Puri, New Delhi-110018, comprised of two blocks namely Block-A and Block-B. Block-A is comprised of two separate basements, ground floor plus three upper floors and Block-B is comprised of ground floor plus one upper floor, owned/occupied by Kamal Educational & Welfare Society was issued Fire Safety Certificate by this department vide letter F6/DFS/MS/School/2016/SZ/1661 dated 11/11/2016. The School building was re-inspected by the officer concerned of this department on 23/02/2021 in the presence of Sh. B.N. Dutta (Admn. Officer) and found that Kamal Educational & Welfare Society have deemed complied the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class 'Educational' for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed as below. Issued on_at New Delhi.

> (Sunil Chawdhary) Dy. Chief Fire Officer

Copy to:-

- 1. Sh. R.K. Tandon (General Secretary), Kamal Public Sr. Sec. School, D-Block, Vikas Puri, New Delhi-110018.
- 2. Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054. Following fire safety directives must be adhered to:-
 - 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
 - 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
 - 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
 - 4. The trained staff should be available round the clock.
 - 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning
 - 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
 - 7. Basement shall be used as per the building bye laws.
 - 8. The owner/occupier shall submit a declaration every year in the form 'K provided in the first schedule of Delhi Fire Service Rules 2010, form is available www.dfs.delhigovt.nic.in.
 - 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

Name & address of the building: Kamal Public Sr. Sec. School, D-Block, Vikas Puri, New Delhi-18 Building is Comprised of A & B Block(Block- A having two separate basement, G+3 upper floors & Block- B having Ground plus one upper floor) 3. Type of Occupancy Educational 4. Type of Case Renewal 5. Details of Previous NOC F6/DFS/MS/School/2016/SZ/1661 dated 11/11/2016 6. Fire Safety directives letter No : N/A 7. Date of inspection 23/02/2021 8. Name of Inspecting Officer A.D.O. R.K YADAV 9. Name and designation of officers From the building side Sh. B.N. Dutta (Admn. Officer) 10. Year of Construction 2007-2008 11. Applicant's letter No. Nil dated 18/02/2021 S. No. Minimum Standards on fire prevention and fire Requirement as Provided at Remarks per FSC dt. safety U/R 33 site MR/NMR 11.11.2016 1. Access to building Accessible (06 mtrs.) Road width 18 mtrs MR Gate width Old case 4.9 & 4.2 mtrs MR, being old case N/A Width of internal road N/A N/A 2. Number, Width, Type & Arrangement of Exits Number of staircases Upper Floors 02 No's in Blk-A 02 No's in Blk-A MR 02 no. Blk-B 02 no. Blk-B Basements 02 No's in each 02 No's in each MR b. Width of staircases basement of Blk-A basement of Blk-A Upper Floor 1.37 & 1.51 m in Blk-MR, being old case Old case A & 1.53 & 1.5 m in Basements Blk-B Old case 1.37 & 1.15 m MR, being old case 1.51 & 1.13-1.24 m c. Protection of exits Fire check door N/A N/A N/A Pressurization N/A N/A N/A d. No. of continuous staircases to terrace Two in Blk-A & One in Required MR Blk-B e. Width of Corridor 2.28-2,32 m in Blk-A & 1.50 m MR 2.00 m in Blk-B Door Size 1.12 m 1.0 m MR 3. Compartmentation Fire check door N/A N/A N/A Sealing of electrical shafts N/A N/A N/A Fire Rating of shaft door N/A N/A N/A Water Curtain N/A N/A N/A Fire Dampers N/A N/A N/A 4. Smoke Management System Basements Exhaust fans are MR Required provided Upper floors Required Natural MR ventilation 5. Fire Extinguishers Total numbers 26 no.'s Provided MR Types Provided ABC/CO₂ type MR IS marking ISI marked ISI marked MR

6.	First-Aid Hose Reels			
	Total numbers on each floor	02 no.'s in Bl	k-A Provided	
	Length of hose reel hose Nozzle diameter	30 mtrs	Trovided	MR
	1 tozzic diameter	5 122 122	Provided	MR
7.	Automatic fire detection and alarming syst	tem	Provided	MR
	 Type of detectors 	N/A	N/A	
	Location of Main Panel Location of Revenue	N/A	N/A	N/A
	Location of Repeater PanelAlternate source of power	N/A	N/A	N/A
	Hooters' Location	N/A	N/A	N/A
2		N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	Provided	N/A
LO.	Automatic Sprinkler System		Frovided	MR
	Basement Ground Floor	Required	Provided	840
	 Ground Floor Sprinkler above false ceiling	N/A	N/A	MR
1.		N/A	N/A	N/A N/A
ols e	Internal Hydrants		1,/,	IN/A
	Size of riser/down-comer Number of hydronia	N/A	100 mm	MR
	Number of hydrants per floorHose Box	N/A	Two	MR
2.		N/A	Two	MR
-	Yard Hydrants			IVIN
	Total number of hydrantsHose Box	N/A	One	MR
		N/A	One	MR
	Pumping Arrangements			IVII
	 Ground Level Discharge of main Pump 			
	Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump headStandby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	Auto Starting/Manual Stopping	N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
	Pump House Access			, ,
	 Terrace level Discharge of pump 	Old case	450 LPM & 180	MR, being old case
	Head of the pump	40	LPM provided	
	Power Supply	40 mtrs	Provided	MR
	➤ Auto Starting of pump	Required	Provided	MR
		N/A	N/A	N/A
	Captive Water Storage for fire fighting			
	Underground tank capacity	50,000 ltrs	Dravid	
	Draw-off connection	N/A	Provided	MR
	Fire service inlet Access to tank	N/A	N/A Provided	N/A
	Overhead Tank capacity	N/A	Provided	MR
		5000 ltrs	N/A 10,000 ltrs	. N/A
	Exit Signage.	Required		MR
		required	Provided	MR

.6.	Provision of Lifts.	N/A	N/A	N/A			
	 Pressurization of Lift Shaft Pressurization of Lift lobby 	N/A	N/A	N/A			
	Pressurization of Lift foody Communication In lift Car	N/A	N/A	Old lift			
	Fireman's Grounding Switch	N/A	N/A	Old lift			
	Lift Signage	N/A	Provided	MR			
17.	Standby power supply	Required	Provided	MR			
18.	Refuge Area.						
18.							
	> Total Area	N/A	N/A				
	> Location	N/A	N/A	N/A			
19.	Fire Control Room N/A N/A						
1.7.	Detector System Panel	N/A	N/A				
	Flow Switch Panel	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
	Battery backup	N/A	N/A	N/A			
	Building Floor Plans	N/A	N/A	N/A			
20.	Special Fire Protection System for Protect	ion of N/A	N/A	N/A			
	special Risks, if any:						

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the Fire Safety Certificate issued vide letter number F6/DFS/MS/School/2016/SZ/1661 dated 11.11.2016 renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of Inspecting Officer

Name:- R.K. YADAV

Designation:- Asstt. Divisional Officer

D.O. (South West)

m/02/02/2021

Dy cfo(g/2)

A DO DKM