GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2021/ | 68

Dated :-----

FIRE SAFETY CERTIFICATE

Certified that the M/s The MOB (A Unit of Shreem Restaurants & Beverages Pvt. Ltd.) located at M-43/44/92, (Half Portion)/133, Outer Circle, Connaught Place, New Delhi comprises of Ground + Mezzanine + 02 upper floor was earlier granted FSC by this department vide letter No. F6/DFS/MS/EH/2017/795 dated 05.06.2017 The premises was re-inspected by officers concerned of this department on dated 08/03/21 in the presence of Sh. Naveen Sachdeva and found that the said premises has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D Restaurant at Ground and 2 upper floor, mezzanine (storage only) with effect from [2007.2402]—for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued -12/03/2021 -- at New Delhi by.

(Dr. S.K.Tomar)

Dy. Chief Fire Officer

Delhi Fire Service

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID No 2020110208226 dated 24/12/2020.
- The Manager, M/S The MOB (A Unit of Shreem Restaurants & Beverages Pvt. Ltd.) M-43/44/92, (Half Portion)/133, Outer Circle, Connaught Place, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority. Use of mezzanine floor shall be only for storage purpose.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.
- 9. Flammable material if any for interior decoration shall be strictly prohibited.

INSPECTION REPORT

1. Name & address of the building:- The MOB (A Unit of Shreem Restaurants &

Beverages Pvt. Ltd.) located at M-43/44/92, (Half Portion)/133, Outer Circle, Connaught Place,

New Delhi.

2. Type of occupancy:-

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-

6. Date of inspection:-7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Group - D Assembly Building Gr. + Mezzanine + 2 upper floor

Renewal F6/DFS/MS/EH/2017/795 dated 05.06.2017

N/A 08/03/21

Sh. Ravinder Singh ADO/CC) & Sh. Rajinder Atwal (DO/CD)

Mr. Naveen Sachdeva

Old Heritage

ID No 2020110208226 dated 24/12/2020

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	6 mtr.	09 mtr.	MR	
	2) Gate width	N/A	Directly accessible from main road	MR	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases				
	1. Upper floors	02 Nos.	02 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	1.5 & 0.80 mtr.	1.5m. 0.80 m upto upper floor &01 of 0.80 mtr. upto mezzanine	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	01	01	MR	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	2 mtr.	2 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	N/A	N/A	N/A	
	2) Upper floors	12 a/c per	Natural	MR	
5.	Fire Extinguishers				

4/13

	1) Total numbers	10 Nos.	10 Nos.	MR				
	2) Types	ABC & CO		MR				
	3) ISI marking	ISI	Provided	MR				
6.	First-Aid Hose Reel			X				
	1) Total number	01	01	MR				
	2) Length of hose reel hose	30 m	30 m	MR				
	3) Nozzle diameter	5 mm	5 mm	MR				
7.	Automatic Fire Detection & Alarming System							
	1) Type of detectors	N/A	N/A	N/A				
	2) Location of main panel	N/A	N/A	N/A				
	3) Location of repeater panel	N/A	N/A	N/A				
	4) Alternate source of power	N/A	N/A	N/A				
	5) Hooter's Location	N/A	N/A	N/A				
3.	MOEFA	Required	Provided	MR				
).	Public Address System	N/A	N/A	N/A				
10.	Automatic Sprinkler System		,					
LU.	1) Basement	N/A	N/A	N/A				
	2) Upper floor	N/A	N/A	N/A				
	3) Sprinkler above false	N/A	N/A	N/A				
	ceiling	1 1/1 1	2005					
11.	Internal Hydrants		в					
11.	1) Size of riser/down-comer	100 MM	100 MM	MR				
	2) Number of hydrants per	01	01	MR				
	floor			s e				
	3) Hose box	01	01	MR				
12.	Yard Hydrants							
12.	1) Total number of hydrants	N/A	N/A	N/A				
	2) Hose box	N/A	N/A	N/A				
13.	Pumping Arrangement	14/14	1,112					
13.	1) Ground level	N/A	N/A	N/A				
	a) Discharge of main	N/A	N/A	N/A				
	,	14/74	1 4/ 2 %					
	b) Head of main pump	N/A	N/A	N/A				
			N/A	N/A				
		1	N/A	N/A				
	d) Jockey pump out pu	N/A N/A	N/A	N/A				
	e) Jockey pump head		N/A	N/A				
	f) Stand by pump out		N/A	N/A				
	g) Stand by pump hea	75	N/A	N/A				
	h) Auto starting/Manu	iai in/A	1 1/1 1	1077				
	stopping			*				
	2) Terrace level	450 LP	M 450 LPM	MR				
	a) Discharge of pump	30 mtr.	Provided	MR				
	b) Head of pump	Require		MR				
				MR				
	d) Auto starting of pur Captive Water Storage for		IVIIC					
	Cantive Water Storage to		N/A	N/A				
14.				IN/IN				
14.	Under ground tank	N/A	14/11	7				
14.	Under ground tank capacity			N/A				
14.	Under ground tank		N/A N/A	N/A N/A				

	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	10,000 ltrs.	10,000 Ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syst Risk, if any:	em for Protect	ion of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/EH/2017/795 dated 05.06.2017, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the Inspecting Officer

Name :- Rajinder Atwal Designation :- DO (CD) Signature of the Inspecting Officer

Name:- Ravinder Singh

Designation :- ADO (CC)

Dycho Corozi

02 January

Boeco)

Assoles As approved, for is portup for Icens
Recused and Supple