GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No. F6/DFS/MS/GH/NDZ/2021/

Dated: 30/3/2

FIRE SAFETY CERTIFICATE

Issued on .30/3/2.......at New Delhi by

(**Dr. S.K. Tomar**)

Dy. Chief Fire Officer

Tel: 011-23412025

Copy to:-

- 1. The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi
- 2. The Licensee, M/s Duke Guest House located at 5043 44, Netaji Subhash Marg, Daryaganj, Delhi-06.

Condition for the validity of fire safety certificate

- 1. This clearance/FSC shall stand cancelled if guest house owner/occupier fails to comply all other conditions mentioned in the gazette notification dated 27.05.2019 and any violation of clarification issued on 25.09.2019 & 17.12.2020 latest by 31.03.2021
- 2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub Rule (I) of Rule 37] along with a copy of this Certificate, six month prior to its expiry".

 Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained there to before occupancy of the same.

		INSPECTION REPORT					
1	Name & address of the building	M/s Duke Guest H	M/s Duke Guest Houese located at 5043 - 44/8 Neta				
2	D 1111	Subhash Marg, New	Delhi-06				
2	Building is comprised of	Ground + mezzanin	ie + 03 upper floo	rs (total 12 gu			
		rooms)	Ground + mezzanine + 03 upper floors (total 12 gu rooms)				
		Ground floor - commercial					
		Mezzanine – other's business occupancy					
		1 st floor- 06 guest room	ns + reception				
		Low height Store bety	ween 1 st and 2 nd flo	or – sealed w			
		Low height Store between 1 st and 2 nd floor – sealed w masionary wall. 2 nd floor – 06 guest rooms. 3 rd floor – other's business occupancy					
3	Type of Occupancy	Residential Group A-1		y			
4	Type of Case	Renewal					
5	Details of Previous FSC	F6/DFS/MS/GH/2017/1	F6/DFS/MS/GH/2017/1698 dated 23.11.2017				
6	Fire Safety direction letter No	Nil					
7	Date of Inspection	22.03.2021					
8	Name of the Inspecting Officers						
9	Name of the designation of Officer	Rajesh Kumar Shukla ADO (SPM)					
	from the building side	Shri Rajender Kumar (manager)					
	Year of Construction	Old		*			
	Applicant's letter No	4000000	001001111				
S.No		Online application no2021031111191 dated 12.03.2021					
341.0	Standards on mic	1 Tovided at Site Reins					
	Prevention and fire safety requirements U/R 33			MR/NMR			
1	Access to building	arrangements		8			
•	Road width		¥				
	Gate width	06 meters	09 meters	MR			
	Width of internal road	NA	NA	NA			
		NA	NA	NA			
	Number, Width, Type and Arra A. Number of Staircases	ingement of Exits					
	Upper Floor	0.1					
	Basement	01 no.	02 nos	MR			
	B. Width of Staircases	NA	NA	NA			
	Upper Floor	00					
		80 cms	88 to 90 cms and 80 – 109 cms	MR			
	Basement	NA	NA	NA			
	C. Protection of exits						
	Fire check door	Required as per GN dated 27.05.2021	Not provided	Last date of compliance			
	Pressurization	NA	NA	is 31.03.2021 NA			
	D. No. of continuous staircases to terrace	01 no.	01 no.	MR			
	E. Width of Corridor	NA	NA	NIA			
	G. Door size	1 m	1 m	NA			
	Compartmentation	- ***	1 111	MR			
	Fire check door	NA	NA	NIA			
	Sealing of electrical shafts	NA	NA	NA NA			
	Fire rating of shaft door	NA	NA				
	Water curtain	NA	NA	NA			
	Fire Dampers	NA	NA	NA			
	Smoke Management System.	NA NA NA					
	Basement	30a/cper hour	NA	NIA			
	Upper floor	Natural / Mechanical	Natural	NA MR			
			INICITIES	4 4 1 1			



5.	Datinguisher	7.1					
	Total numbers	06 no.	17				
	Types	CO ₂ & ABC	17 nos	MR			
	IS marking	Required	CO ₂ & ABC	MR			
6	First-aid-Hose Reels.	Required	ISI marked	MR			
	Total numbers of each floor						
	Length of hose reel hose	01 no.	Provided	MR			
	Nozzle diameter	30 m	30 m	MR			
7		5 mm	5 mm	MR			
	Type of detection and alarming system.						
	Type of detectors	CO detectors (required as per G dated 27.05.2019)	Not Provided	Last date of compliance extended till 31.03.2021 vid order dated			
	Location of main panel	At reception	Not Provided	Last date of compliance extended till 31.03.2021 vid order dated			
	Location of repeater panel	NA	NA	17.12.2020			
	Alternate source of power	NA	NA NA	NA			
3	Hooters MOEFA	NA	NA	NA NA			
)		NA	Provided	NA NA			
	Public address System.	NA	Provided				
10	Automatic Sprinkler System.						
	Basement	NA	NA	NA			
	Upper Floor	NA	NA				
	Sprinkler above false ceiling	NA		NA			
1	Internal Hydrants		NA	NA			
	size of riser/down-comer						
	Number of hydrants per floor	NA NA	NA	NA			
	Hose Box		NA	NA			
2	Yard Hydrants.	NA	NA	NA			
	Total number of 1						
	Hose Box	NA	NA	NA			
	DATE OF BOOKS	NA	NA	NA			
	Tumping Arrangements.						
-	• Ground Level Discharge of main Pump						
-	The first of that it ullip	NA	NA	NA			
-	> Head of Main Pump	NA	NA	NA			
-	Number of main pumps	NA	NA				
	Jockey pump out put	NA	NA	NA			
	Jockey pump head	NA	NA	NA			
-	Standby pump out put	NA	NA	NA NA			
-	Standby pump Head	NA	NA	NA NA			
-	Auto Starting /Manual stopping Pump House Access	NA	NA	NA NA			
-	Pump House AccessTerrace Level	NA	NA	NA			
-							
-	be or pump	225 LPM	225 LPM	MR			
-		30 m	30 m	MR			
-	> Power supply	Required	Provided	MR			
	Auto Starting of pump	Required	A S COMMON	TATT			

14	Captive Water Storage for Fire Fighting.				
	Underground tank capacity	NA	NA	NA	
	Draw-off connection	NA	NA	NA	
	Fire service inlet	NA	NA	NA	
	Access to tank	NA	NA	NA	
	Overhead Tank capacity	2500 ltrs	2500 ltrs	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
	Pressurization of Lift Shaft	NA	NA	NA	
	Pressurization of Lift lobby	NA	NA	NA	
	Communication in lift car	NA	NA	NA	
	Firemen's grounding switch	NA .	NA	NA	
	Lift Signage	NA	NA	NA	
17	Standby power supply	Required	Provided	MR	
18	Refuge Area.				
	Total area	NA	NA	NA	
	Location	NA	NA	NA	
19	Fire Control Room				
	Detector system panel	NA	NA	NA	
	Flow switch panel	NA	NA	NA	
	PA system panel	NA	NA	NA	
	Batter backup	NA	NA	NA	
	Building Floor Plans	NA	NA	NA	
20	Special Fire Protection systems for protection of special		NA	NA	
	Risks, if any:				

The guest house management has sealed the low hieght floor used for starage between 1^{st} and 2^{nd} floor and guest house is running only on 1st and 2^{nd} floor of the building. The building is approachable from two sides with independent staircases with access to all the floors.

The guest house management has submitted an affidavit stating that the 3rd floor has been sold to an advertising agency.

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No. F6/DFS/MS/GH/2017/1698 dated 12.03..2018 only for 1st and 2nd floor with 12 guest rooms is recommended to be renewed under Rule 35 of the Delhi Fire Service Rules 2010.

If agreed, we may clear the online application no. 2021031111191 dated 12.03.2021 from fire safety point of view. Accordingly, DFA of FSC is put up for signatures please.

Signature of the Inspecting Officer

Name: Rajesh Kumar Shukla

Designation ADO (SPM)

DO (CD)

D. No. 678