GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/NDZ/2021/ 187

Dated: 26 .03.2021

FIRE SAFETY CERTIFICATE

Certified that the M/s River Side Club at Mayur Vihar Phase-I, Delhi comprises of Basement + Ground + 02 Upper floor respectively owned/occupied by Riverside Sports & Recreation Club was granted FSC by this department vide letter No. F6/DFS/MS/NDZ/2018/649 dated 10/04/2018. The premises was inspected by the Divisional Officer(ED) & Asstt. Divisional Officer(LN) of this department on 05/03/2021 in the presence of Mr. Manoj Kumar (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy "Assembly Building" Class "D" with effect from -26[03]2021 for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below. 26 03 2021 at New Delhi by.

(Dr. S.K Tomar) Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Asstt. Commissioner (Club), GNCT of Delhi, L&N Block, Vikas Bhawan, IP Estate, Delhi-110002.
- 2. Sh. Manoj Kumar,

Manager,

M/s River Side Club, Mayur Vihar, Phase-I, Delhi. online application ID . 2021021310420, 2021021310422, 2021012910003, 2020062905541 dated 15/02/2021.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INIC	DE	CTI	ON	RE	PC	R	ſ
LIND	FL		UN	IVL		/1/	ı

Riverside Sports and Recreation Club at Mayur 1. Name & address of the building

Vihar Phase- 1, Delhi-110091. Assembly (Club Building) 2. Type of occupancy:-

B + Gr. + 02 floors

3. Type of case:-Renewal

F6/DFS/MS//NDZ/2018/649 dated 4. Details of previous FSC:-10/04/18.

F.6/DFS/MS/BP/97/481 dated 01/05/1997 5. Fire safety directives No.-

05/03/21 6. Date of inspection:-

7. Name of the inspecting officer:-

Sh. Francis Brown (DO/ED) & Sh. Manoj Kumar Sharma (ADO/LN)

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Mr. Manoj Kumar (Manager)

1999

2021021310420, 2021021310422, 2021012910003,

2020062905541 dated 15/02/2021

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement NBC-IV/UBBL	Provided at site	Remarks MR/NMR			
1.	Access to Building						
1 1 1 1 1 1 1	1) Road width	12 mtr.	30 mtr.	MR			
	2) Gate width	4.5 mtr.	6 mtr.	MR			
	3) Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arrangement of Exits						
	A. Number of staircases			1 200			
	1. Upper floors	02 Nos.	02 Nos.	MR			
	2. Basements	02 Nos.	02 + 01 ramp	MR			
	B. Width of staircase						
	1. Upper floors	1.25 mtr.	1.4 mtr. & 80 cm	MR			
	2. Basements	1.25 mtr.	1.4 mtr. & 80 cm + ramp	MR			
	C. Protection of exits						
	1. Fire check door	Required	Provided	MR			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	01 Nos.	01 Nos.	MR			
	staircase to terrace						
	E. Width of corridor	1.5 M	1.5 M	MR			
	F. Door size	1.0 m	1.0 m	MR			
3.	Compartmentation						
	1) Fire check door	Required	Provided	MR			
	2) Sealing of electrical shafts	Required	Provided	MR			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System						
	1) Basements	Required	Provided	MR			
	2) Upper floors	N/A	N/A	N/A			
5.	Fire Extinguishers						
	1) Total numbers	15 Nos.	20 Nos.	MR			
	2) Types	ABC & CO2	ABC & CO2	MR			
	3) ISI marking	Required	Provided	MR			

j.	First-Aid Hose Reel	01		0.1		MR		
	1) Total number of eachfloor		01			MR		
	2) Length of hose reel hose	30 mt		30 mt		MR		
	2) Neggle diameter	05 mr		05 mr	n	IVIIC		
7.	Automatic Fire Detection & A	Alarming System			N/A			
•	1) Type of detectors		N/A		V/A		V/A	
	2) Location of main panel			N/A		N/A		
	3) Location of repeater panel			N/A	1 1	MR		
	4) Alternate source of power		ired	Provi	ded	N/A		
	5) Hooter's Location			N/A				
0	MOEFA	Requ	ired	Provi		MR		
8.	Public Address System	Requ	ired	Provi	ided	MR	20	
9.	Automatic Sprinkler System					1		
10.	1) Basement	Requ	iired	Prov	ided	MR		
		N/A		N/A		N/A		
	2) Upper floors	N/A		N/A		N/A	4	
	3) Sprinkler above false							
	ceiling							
11.	Internal Hydrants		100 mm		100 mm		MR	
	1) Size of riser/down-comer	01		01			MR	
	2) Number of hydrants per floor	01		01		MR		
	3) Hose box	01						
12.	Yard Hydrants	N/A		N/A	N/A		N/A	
	1) Total number of hydrants		N/A				Α	
***	2) Hose box			1 1/12				
13.	Pumping Arrangement		27/4		N/A		N/A	
	1. Ground level		N/A		N/A		N/A	
	a) Discharge of main		N/A					
	pump					N	I/A	
	b) Head of main pump	N/A N/A		N/A N/A			I/A	
	c) Number of main		1	INTE	1			
	pump				N/A		N/A	
	d) Jockey pump out put		t N/A				N/A	
	e) Jockey pump head		N/A		N/A		N/A	
	f) Stand by pump	N/A	A	N/A	A	1	1/11	
	output			771		. 7	N/A	
	g) Stand by pump head		N/A		N/A		N/A N/A	
	h) Auto		N/A		N/A			
	starting/Manual	>						
	stopping							
	Terrace level Discharge of pump						MR	
			0 LPM		0 LPM			
	b) Head of pump		60 mtr.		60 mtr.		MR	
	c) Power supply		Required		Provided		MR	
	d) Auto starting of		Required		ovided		MR	
	numn				1/2			
	YYY Chamaga fo	r Fire	Fighting	5			1 M	
14.	1) Under ground tank		50,000 L	ts.	50,000 Lts	S.	MR	
			50,000 2				1 (1)	
	a) Draw-off connection	on	Required Provided			MR		
100	a) Draw-off connection b) Fire service inlet	/11	Required Provided			MR		

	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	10,000 ltr.	12,500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
1	d) Battery backup	N/A	N/A	N/A
-	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System if any:	m for Protection	on of special Risk,	N/A

The fire protection system provided in the school building were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/NDZ/2018/649 dated 10/04/2018, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- Francis Brown

Designation : DO (ED)

Signature of the Inspecting Officer

Name: - M.K. Sharmal 7 3 Designation: - ADO (LN)