c-52

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2021/ 173

Dated: -61/04/202

FIRE SAFETY CERTIFICATE

Certified that the Rajdeep Guest House located at 5611-12, Basant Road, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (02 guest rooms + Reception + 01 office), 1st floor to 3rd floor (04 guest rooms at each floor), total 14 guest rooms owned/occupied by Rajdeep Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2018/1043 dated 14/05/18. Now, The premises was reinspected by the officer concerned of this department on 22/03/21 in the presence of Mr. Paramjeet and found that the said guest house building having not using any floor above third floor as per affidavit submitted by applicant dated 23.10.2019, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as, Ground floor (02 guest rooms + Reception + 01 office), 1st floor to 3rd floor (04 guest rooms at each floor), total 14 guest rooms with effect from - Cold -

Issued 61/04/2021 at New Delhi by.

(S.K.Tomar)

(S.K.Tomar)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The commissioner, North MCD,: With a request to verify the temporary rooms constructed at terrace which was not in earlier Inspection.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Online id no. 2021022710816 dated 28.02.2021
- 3. The Manager, Rajdeep Guest House at 5611-12, Basant Road, Pahar Ganj, New Delhi. Condition for the validity of fire safety certificate
 - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
 - 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
 - 3. The trained fire fighting staff should be available round the clock.
 - 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
 - 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
 - 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
 - 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
 - 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
 - 9. The owner shall not use any floor above third floor for any purpose and same shall remain closed/locked

INSPECTION REPORT

Rajdeep Guest House at 5611-12, Basant 1. Name & address of the building

Road, Pahar Ganj, New Delhi.

Residential, Sub Division-A-1 2. Type of occupancy:-

Ground + 03 Upper floors (total 35 guest rooms) Ground floor (02 guest rooms + Reception + 01 office), 1st floor to 3rd floor (04 guest rooms at each floor) and 02 temporary room for staff at terrace and **not using any** Floor above third floors as per affidavit 23.10.2019.

3. Type of case:-

No. F6/DFS/MS/GH/NDZ/2018/1043 dated 4. Details of previous FSC:-

14/05/18

5. Fire safety directives No.-N/A 22/03/21

6. Date of inspection:-

Sh. Ravinder Singh(ADO/CC) 7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

Mr. Paramjeet

9. Year of construction:-1981

Online id no. 2021022710816 dated 28 02 2021

	in ppinounce of record		21022710816 date	Old Case		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR		
1.	Access to Building					
	1) Road width	N/A	06 mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases	The same of				
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	0.80 mtr.	1.01 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	01	MR		
	staircase to terrace					
	E. Width of corridor	01 mtr.	01 mtr.	MR		
	F. Door size	01 mtr.	01 mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers					
	1) Total numbers	08 Nos.	08 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel			1.00		
	1) Total number of eachfloor	01	01	MR		

	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection & A		em	
	1) Type of detectors CO type	Required	Provided	MR
	2) Location of main panel	Ground floor	provided	MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Required	Provided	MR
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	Provided	N/A
10.	Automatic Sprinkler System			
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling			
11.	Internal Hydrants			
11.	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	11/11	11/11	
	3) Hose box	N/A	N/A	N/A
12	Yard Hydrants	14/11	11/12	
12.	1) Total number of hydronts	N/A	N/A	N/A
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	IN/A	IN/A	10/11
13.	Pumping Arrangement	27/4	NI/A	N/A
	1) Ground level	N/A	N/A	N/A N/A
	a) Discharge of main	N/A	N/A	N/A
	pump	77/4	27/4	NT/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping	La Fall Control		
	2) Terrace level			
	a) Discharge of pump	180 LPM	180 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
14.	Captive Water Storage for I	Fire Fighting		
	1) Under ground tank	N/A	N/A	N/A
	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank	2500 ltr.	2500 ltr.	MR
	capacity			
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1.00		
10.		DT/A	NI/A	NI/A
	a) Pressurization of lift	N/A	N/A	N/A

HIZY

	shaft			
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
9.	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	ection System for Protection of special		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2018/1043 dated 14/05/18, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended up to third floor only.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

Sycho Comoz) F. T. P'.

end Sayonshaft,

Pl. npeak.

Pl. npeak.

Dyefi compy

The comments of the period of th