GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/Petrol/2021/SZ/ 215

Dated: 08 04 /2021

FIRE SAFETY CERTIFICATE

Certified that M/s Qutab Service Station (Retail outlet of I.O.C.L Petroleum Class A & B), Opp. STC & MMTC, Housing Colony, Mehrauli Road, New Delhi 110017, comprised of ground & one upper floor was issued FSC by this department vide letter No. F.6/DFS/MS/2018/SZ/1629 Dated 13/07/2018. The premises was re-inspected by the officer concerned of this department on 30/03/2021 in the presence of Sh. Dinesh Jain (Partner) of the said filling station and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Group-J, Hazardous Building as above with effect from 08/04/2021 for a period of three years in accordance with rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010.

Issued on 08/04/2021 at New Delhi by

(Sunil Chaudhary) Dy. Chief Fire Officer Delhi Fire Service

Copy to: -

- 1. The Administrative Officer, South Zone, South MCD, Green Park, New Delhi-110016
- 2. M/s Qutab Service Station (Retail outlet of I.O.C.L Petroleum Class A & B), Opp. STC & MMTC, Housing Colony, Mehrauli Road, New Delhi 110017.

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. Any deviation, with regard to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

| | | | IV/ | | | |
|-------|------|--|--|--|-------------------|--|
| | | INSPECTION | ON REPORT | | | |
| 1 | Naı | me & Address of the Building | M/s Qutab Service Station (Retail outlet of I.O.C.L Petroleum Class A & B), Opp. STC & MMTC, | | | |
| 2 | Tyr | pe of Occupancy | Housing Colony, Mehrauli Road, New Delhi 110017. Hazardous Building (Group-J) (Filling Station) | | | |
| 3 | 1 - | ilding Comprised of | Ground plus one upper floor | | | |
| 4 | - | pe of Case | Renewal | | | |
| 5 | 1 1 | tails of Previous NOC | F6/DFS/MS/Petrol/2018/SZ/1629 Dated 13/07/2018 | | | |
| 6 | Fire | e Safety Directives Letter No | Nil | | | |
| 7 | | te of Inspection | 30-03-2021 | | | |
| 8 | | me of the Inspecting Officers | Sh. Rajesh Kumar ADO (BCP) | | | |
| 9 | Na | me & Designation of Officers m the building side | Sh. Dinesh Jain (Partner) | | | |
| 10 | | ar of construction | 1971 | | | |
| 11 | Ap | plicant letter No. | Through Gmail Dated 19-03-2021 | | | |
| S. No | | nimum standards on Fire | Old NOC requirements | Provided at Site | Remarks MR/NMR | |
| 1 | | cess to Building. | requirements | | IVERVI VIVERS | |
| 1 | 7 1 | Road width | Required | 12 mtr | MR | |
| | | Gate width | -NA- | -NA- | -NA- | |
| | | Width of internal road | -NA- | -NA- | -NA- | |
| 2 | Nu | mber, width, type and arrangements of | of exits. | And the second of the second o | | |
| | a. | Number of Staircase | - 1 | | | |
| | | Upper floors | Required | 01 No | MR | |
| | | Basement floor | -NA- | -NA- | -NA- | |
| | b. | Width of Staircase | | | | |
| | | Upper floors | Required | 0.92 mtr | MR | |
| | | Basement floor | -NA- | -NA- | -NA- | |
| | c. | Protection of exits | | -NA- | | |
| | | Fire check door | -NA- | -NA- | -NA- | |
| | | Pressurization | -NA- | -NA- | -NA- | |
| | | No. of continuous staircase to terrace | -NA- | -NA- | -NA- | |
| | | Width of corridor | -NA- | -NA- | -NA- | |
| | | Door size | 1 mtr | 01 mtr | MR | |
| 3 | | | 1 mu | or mu | IVIIC | |
| 3 | - | ompartmentation. | -NA- | -NA- | -NA- | |
| | | Fire check door.Sealing of electrical shafts. | -NA- | -NA- | -NA- | |
| | | Fire rating of shaft door. | -NA- | -NA- | -NA- | |
| | | Water curtain | -NA- | -NA- | -NA- | |
| | | • Fire dampers. | -NA- | -NA- | -NA- | |
| 4. | Sn | noke Management system. | | -NA- | | |
| | | Basement | -NA- | -NA- | -NA- | |
| | | • Upper floors | -NA- | -NA- | -NA- | |
| 5. | Fi | re Extinguishers. | | | | |
| | | Total numbers | | 16 nos + 08 Fire Buckets | MR | |
| | | • Types | ABC/CO2/DCP | CO ₂ (4.5 kg) ABC & Foam | MR | |
| | | ISI Marking | Required | Provided | MR | |
| 6. | Fi | rst Aid Hose Reels. | | | 77. | |
| | | Total numbers on each floor. | -NA- | -NA- | -NA- | |
| | | Length of hose-reel hose. | -NA- | -NA- | -NA- | |
| | | Nozzle Diameter | -NA- | -NA- | -NA- | |

| 7 | Automatic Fire Detection and Alarming | system. | ha en siñ he zerousk ek es | |
|--|---|--|----------------------------|--------|
| | Type of detectors | -NA- | -NA- | -NA- |
| | Location of Main Panel | -NA- | -NA- | -NA- |
| | Location of Repeater Panel | -NA- | -NA- | -NA- |
| | Alternate source of power | -NA- | -NA- | -NA- |
| | Hooter's location | -NA- | -NA- | -NA- |
| 8. | MOEFA | -NA- | -NA- | -NA- |
| 9. | Public Address System | -NA- | -NA- | -NA- |
| 10. | Automatic Sprinkler System | | | |
| | Basement | -NA- | -NA- | -NA- |
| D. 100-100-100-100-100-100-100-100-100-100 | Upper floors | | -NA- | -NA- |
| | Sprinkler above false ceiling | | | - |
| 11. | Internal Hydrants. | -NA- | -NA- | -NA- |
| | Size of Riser / Down-comer | NIA | NIA | NIA |
| | | | -NA- | -NA- |
| | Number of Hydrant per floor | | -NA- | -NA- |
| 12. | Hose box. Voud Hardworts | -NA- | -NA- | -NA- |
| 12. | Yard Hydrants. | 27.4 | | |
| | Total number of hydrants. | | -NA- | -NA- |
| 12 | Hose box. | -NA- | -NA- | -NA- |
| 13. | Pumping arrangements. | | | |
| | Ground Level | | | |
| | Discharge of main pump. | | -NA- | -NA- |
| | Head of main pump. | | -NA- | -NA- |
| | Number of main pumps. | | -NA- | -NA- |
| | Jockey Pump output. | | -NA- | -NA- |
| | Jockey Pump head. Standby Pump output | | -NA- | -NA- |
| | Standby Pump output.Standby Pump head. | | -NA- | -NA- |
| | Auto Starting/Manual Stopping. | | -NA- | -NA- |
| | Terrace Level | mI/VJ m | -NA- | -NA- |
| | Discharge of pump. | -NA- | -NA- | -NA- |
| | Head of pump. | | -NA- | -NA- |
| | Power supply. | | -NA- | -NA- |
| | Auto starting of pump. | -NA- | -NA- | -NA- |
| 14. | Captive water storage for fire-fighting. | peater Panel ce of power -NANANANANANANANA | | |
| | Underground tank capacity. | -NA- | -NA- | -NA- |
| | Draw-off connection. | | -NA- | -NA- |
| | > Fire Service Inlet. | | -NA- | -NA- |
| | > Access to tank. | A. Carrier and Car | -NA- | -NA- |
| | Overhead tank capacity. | | -NA- | -NA- |
| 15. | No Smoking Signage (Hindi & English) | Required | Provided (Hindi & English) | MR |
| 16. | Provision of Lifts. | | X X | |
| | Pressurization of lift shaft. | -NA- | -NA- | -NA- |
| | Pressurization of lift lobby. | | -NA- | -NA- |
| | Communication in lift car. | | -NA- | -NA- |
| | • Fireman's switch. | -NA- | -NA- | -NA- |
| | Lift signage. | -NA- | -NA- | -NA- |
| 17 | Standby Power Supply | -NA- | -NA- | -NA- |
| 18. | Refuge Area | | of to diame To a | 1111 |
| | Total area | -NA- | -NA- | -NA- |
| | • Location | | -NA- | -NA- |
| | | -11/7- | =INA | -1//A- |

| 19. | Fire Control Room. | | | |
|-----|--|------|------|------|
| | Detector System Panel. | -NA- | -NA- | -NA- |
| | Flow Switch Panel. | -NA- | -NA- | -NA- |
| | PA system Panel. | -NA- | -NA- | -NA- |
| | Battery backup | -NA- | -NA- | -NA- |
| | Building floor plan | -NA- | -NA- | -NA- |
| 20. | Special Fire Protection System for the Protection of special Risk, if any. | NA | NA | MR |

The fire protection system such as fire extinguisher of different type and capacity, Fire buckets filled with loose dry sand & water provided at suitable places in the retail outlet area were checked and found functional at the time of inspection. "No Smoking" sign board were found displayed both Hindi & English at conspicuous places. No loose electrical wiring was seen in the premises.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under rules, renewal of the FSC issued vide letter No. F6/DFS/MS/Petrol/2018/SZ/1629 Dated 13/07/2018 under rules 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar Designation: ADO(BCP)

DO (SD) ~ on leave

Dy CASE2

As epproved, F.T. Letter in forth for your

Synature OI

Dy CASE2

Dy CASE2