GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/MS/School/2021/NDZ / 123

Dated: | 6 | 4 | 21

FIRE SAFETY CERTIFICATE

Issued on....at New Delhi by

(Dr. S.K.Tomar)
Dy. Chief Fire Officer

To,

The Manager,
Delhi International Sec. School,
Loni Raod, Jawahar Nagar,
Johripur, Delhi -110094

Copy:-

The Dy. Director of Education, B–Block, Yamuna Vihar, Delhi-110053

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry

ADOTP. (forces)

1. Name & address of the building

2. Building is comprised of

3. Type of Occupancy

4. Type of Case

5. Details of Previous NOC letter

6. Fire Safety directive letter No.

7. Date of Inspection

8. Name of the Inspecting officers

9. Name and designation of Officer from the building side

10. Year of Construction

11. Applicant's letter No

: Delhi International Sec. School,

Main Road Jawahar Nagar, Johripur, Delhi -94

: Ground plus two upper floors

: Educational

: Renewal

: F6/DFS/MS/School/2017/NDZ/75 dated 18/01/17

: Circular No. 262-362 dated 17/01/2005 issued by the Director of Education

: 21/03/21

: ADO Mehmood

: Mr. Rajeev Kumar (Manager)

: 2001

: E-mail, Dated- 13/03/2021

| Sr. | Minimum Standards on Fire | Circular | Provided at Site | Remarks MR/NMR | | | | |
|-----------|--|----------------------|------------------------------|---------------------|--|--|--|--|
| No. 01 | Prevention and Fire Safety U/R33 Access to Building. | Requirement | | IVIIX/INIVIIX | | | | |
| O I | | | | | | | | |
| | Road width | 06 mtr. | 24 mtr. | MR | | | | |
| | Gate width | N/A | N/A | N/A | | | | |
| | Width of internal road | N/A | N/A | N/A | | | | |
| 02 | Number, Width, Type and Arrangement of Exits. | | | | | | | |
| | a. Number of Staircases | | | | | | | |
| | Upper floor | 1 No. | 2 No. | MR | | | | |
| | Basement | N/A | N/A. | N/A | | | | |
| | b. Width of Staircases | | | | | | | |
| | Upper floor | 1.50 mtr. | 1.40 mtrs & 0.75 mtrs (Iron) | MR (Old) Accepte | | | | |
| | Basement | N/A | N/A | N/A | | | | |
| | c. Protection of exits | | Ř. | | | | | |
| | Fire check door | N/A | N/A | N/A | | | | |
| | Pressurization | N/A | N/A | N/A | | | | |
| | d. No. of Continuous Staircases to Terrace | 01 no. | 01 no. | MR | | | | |
| | e. Width of Corridor | 1.50 mtr. | 1.70 mtr. | MR | | | | |
| | f. Door Size | 01 mtr. | 01 mtr. | MR | | | | |
| 03 | Compartmentation. | | | | | | | |
| | Fire check door | N/A | N/A | N/A | | | | |
| | Sealing of electrical shafts | N/A | N/A | N/A | | | | |
| | Fire rating of shaft door | N/A | N/A | N/A | | | | |
| | Water curtain | N/A | N/A | N/A | | | | |
| | Fire dampers | N/A | N/A | N/A | | | | |
| 04 | Smoke Management System. | | | | | | | |
| | Basement | N/A | N/A | N/A | | | | |
| | Upper floor | N/A | N/A | N/A | | | | |
| 05. | Fire Extinguishers. | | | | | | | |
| | Total numbers | 08 nos. | 18 nos. | MR | | | | |
| | Types | ABC /CO ₂ | Provided | MR | | | | |
| | IS marking | ISI marked | Provided | MR | | | | |

| 06 | First-Aid-Hose Reels. | | | | | | |
|----|--|------------|------------|-----|--|--|--|
| | Total numbers on each floor | 01 No. | 01 no. | MR | | | |
| | Length of hose reel hose | 30 mtr. | 30 mtrs | MR | | | |
| | Nozzle diameter | 05 mm | 05 mm | MR | | | |
| 07 | Automatic Fire Detection and Alarming System. | | | | | | |
| | Type of detectors | N/A | N/A | N/A | | | |
| | Location of main panel | N/A | N/A | N/A | | | |
| | Location of repeater panel | N/A | N/A | N/A | | | |
| | Alternate source of power | N/A | N/A | N/A | | | |
| | Hooter's location | N/A | N/A | N/A | | | |
| 08 | MOEFA | N/A | N/A | N/A | | | |
| 09 | Public Address System. | N/A | Provided | MR | | | |
| 10 | Automatic Sprinkler System. | | L | , | | | |
| | Basement | N/A | N/A | N/A | | | |
| | upper floor | N/A | N/A | N/A | | | |
| | sprinkler above false ceiling | N/A | N/A | N/A | | | |
| 11 | Internal Hydrants | | | 1 | | | |
| | size of riser/down-comer | 100 mm | 100 mm | MR | | | |
| | Number of hydrants per floor | 01 no. | 01 no. | MR | | | |
| | Hose box | 01 no. | 01 no. | MR | | | |
| 12 | Yard Hydrants. | | | | | | |
| | Total number of hydrants | N/A | N/A | N/A | | | |
| | Hose Box | N/A | N/A | N/A | | | |
| 13 | Pumping Arrangements. | | = | | | | |
| | ➢ Ground Level | | | | | | |
| | Discharge of main pump | N/A | N/A | N/A | | | |
| | Head of Main pump | N/A | N/A | N/A | | | |
| | Number of main pumps | N/A | N/A | N/A | | | |
| | Jockey pump out put | N/A | N/A | N/A | | | |
| | Jockey pump head | N/A | N/A | N/A | | | |
| | Standby pump out put | N/A | N/A | N/A | | | |
| | Standby pump head | N/A | N/A | N/A | | | |
| | Auto Starting /Manual stopping | N/A | N/A | N/A | | | |
| | Pump house access | N/A | N/A | N/A | | | |
| | > Terrace Level | | | | | | |
| | Discharge of pump | 450 lpm | 450 lpm | MR | | | |
| | Head of the pump | 40 M | 40 M | MR | | | |
| | Power supply | Required | Provided | MR | | | |
| | Auto Starting of pump | Required | Provided | MR | | | |
| 14 | Captive Water Storage for Fire Fighting. | | | | | | |
| | Underground tank capacity | N/A | N/A | N/A | | | |
| | Draw-off connection | N/A | N/A | N/A | | | |
| | Fire service inlet | N/A | N/A | N/A | | | |
| | Access to tank | N/A | N/A | N/A | | | |
| | Overhead tank capacity | 5,000 ltrs | 5,000 ltrs | MR | | | |
| 15 | Exit Signage. | Required | Provided | MR | | | |
| 16 | Provision of Lifts. | | | | | | |
| | Pressurization of lift shaft | N/A | N/A | N/A | | | |
| | Pressurization of lift lobby | N/A | N/A | N/A | | | |
| | Communication in lift car | N/A | N/A | N/A | | | |
| | Firemen's grounding switch | N/A | N/A | N/A | | | |
| | Lift signage | N/A | N/A | N/A | | | |

| 17 | Standby Power Supply | N/A | N/A | N/A | | |
|----|--|-----|-----|-----|--|--|
| 18 | Refuge Area. | | | | | |
| | Total area | N/A | N/A | N/A | | |
| | Location | N/A | N/A | N/A | | |
| 19 | Fire Control Room | | | | | |
| | Detector system panel Flow switch panel PA system panel Battery backup | N/A | N/A | N/A | | |
| | | N/A | N/A | N/A | | |
| | | N/A | N/A | N/A | | |
| | | N/A | N/A | N/A | | |
| | D. Il-line flaggariano | N/A | N/A | N/A | | |
| 20 | Special Fire Protection Systems for Protection of Special Risks, if any: | N/A | N/A | N/A | | |

The fire protection systems provided in the building were tested/checked at the time o inspection.

Keeping in view the deemed compliance of the minimum standards on fire preventior and fire safety required under the circular No. 262-362 dated 17/01/2005 issued by the Director of Education, it is recommended to issue Fire Safety Certificate.

Signature of the Inspecting Officer

Name

:- Mehmood

Designation :- A.D.O (T.Pur)

DO(ED)

Recd on SINIL

A G. of Julia post, my to Sight tone Blean

Sommed

12 (4120)

Apo(T0)

Thomas

(1314)21

M.S.Cell