GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/CNG/2021/SZ/ 241

Dated: 28 /04 /2021

FIRE SAFETY CERTIFICATE

Certified that CNG Filling Station located at Nelson Mandela Marg, New Delhi comprised of ground floor only owned/occupied by M/s Indraprastha Gas Limited, was granted FSC by this department vide letter no. F6/MS/DFS/CNG/2018/SZ/1014 Dated 10/05/2018. The premise was reinspected by the officer concerned of this department on 14.04.2021 in the presence of Mr. Raj Kumar Dutt (Manager) of the said filling station and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Storage (CNG Pump) as above with effect from 28 / 64 / 2021 for a period of three years in accordance with rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010.

Issued on 28 / 04 /2021 at New Delhi by

(Sunil Chawdhary)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to: -

1. The Joint C.P (Lic.) First Floor, PS Defence Colony, New Delhi 110049.

2. Sh. Ajay Khatri, DGM-(Fire & Safety) (IGL) LGL Bhawan, Plot No 4, Community Centre, R. K Puram, Sector- 09, New Delhi 110049

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting system.

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

	I AFA	N	ame & Address of the Building		Nelson Mandela Marg s Ltd, Retail outlet)	, New Delhi	
	2	Ty	pe of Occupancy	Hazardous "Group –J (CNG Pump)			
-	3	В	uilding Comprised of	Ground floor only			
-	4	Ty	vpe of Case	Renewal			
1	5	D	etails of Previous NOC	F6/MS/DFS/CNO	G/2018/SZ/1014 Dated 1	0/05/2018	
	6	Fi	re Safety Directives Letter No	Nil			
-	7	D	ate of Inspection	14-04-2021			
-	8	N	ame of the Inspecting Officers	Mr. Rajesh Kuma			
1	9		ame & Designation of Officers	Mr. Raj Kumar Dutt (Manager)			
-	10		om the building side ear of construction	2002		anders som and an experimental system of the south of the	
	11		oplicant letter No.	Gmail Dated 12-04-2021			
-			inimum standards on Fire	Old NOC	Provided at Site	Remarks	
	S. No	10000	revention and Fire Safety U/R 33	Requirement	Provided at Site	MR/NMR	
1	1	-	ccess to Building.				
-			Road width	09 mtr	Provided	MR	
			Gate width	-NA-	-NA-	-NA-	
-			Width of internal road	-NA-	-NA-	-NA-	
	2	N	umber, width, type and arrangements (of exits.			
1		a.	Number of Staircase				
			Upper floors	-NA-	-NA-	-NA-	
			Basement floor	-NA-	-NA-	-NA-	
		b.	Width of Staircase				
			Upper floors	-NA-	-NA-	-NA-	
			Basement floor	-NA-	-NA-	-NA-	
		c.	Protection of exits				
			Fire check door	-NA-	-NA-	-NA-	
			Pressurization	-NA-	-NA-	-NA-	
		d.	No. of continuous staircase to terrace	Required	Provided 0.70 m	MR	
		e.	Width of corridor	-NA-	-NA-	-NA-	
and the same of th		f.	Door size	-NA-	-NA-	-NA-	
	3	C	ompartmentation.				
			Fire check door.	-NA-	-NA-	-NA-	
			Sealing of electrical shafts.	-NA-	-NA-	-NA-	
			Fire rating of shaft door.	-NA-	-NA-	-NA-	
			Water curtain	-NA-	-NA-	-NA-	
	4.	G.	• Fire dampers. moke Management system.	-NA-	-IVA-	-IN/A-	
	٦.	131		-NA-	-NA-	-NA-	
			Basement Hange floors	-NA-	-NA-	-NA-	
	5.	W.	Upper floors	-1//-	-IN/X-	-1ALX-	
	5.	H	re Extinguishers.	D	20 No.	MR	
			Total numbers	Required	30 Nos DCP/75 kg- 4, DCP/10kg		
			• Types	ISI Marked	$-20 \& CO_2 - 06$	MR	
No. of Street, or other Persons and Street, o			ISI Marking		Provided	MR	
	6.	F	irst Aid Hose Reels.	1000			
	1		Total numbers on each floor.	-NA-	-NA-	-NA-	
	100		Length of hose-reel hose.	-NA-	-NA-	-NA-	
			Nozzle Diameter	-NA-	-NA-	-NA-	

	Type of detectors	Gas & Flame	Provided in compressors	MR
	 Location of Main Panel 	-NA-	-NA-	-NA-
	 Location of Repeater Panel 	-NA-	-NA-	-NA-
	 Alternate source of power 	-NA-	-NA-	-NA-
	Hooter's location	-NA-	-NA-	-NA-
	1OEFA	-NA-	-NA-	-NA-
	ublic Address System	-NA-	-NA-	-NA-
10. A	utomatic Sprinkler System			
	Basement	-NA-	-NA-	-NA-
and the second s	• Upper floors	-NA-	-NA-	-NA-
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA-
11. Ir	nternal Hydrants.			
	Size of Riser / Down-comer	-NA-	-NA-	-NA-
	Number of Hydrant per floor	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
12. Y	Hose box. /ard Hydrants.	11/21	1111	1112
		D.T.A.	D.T.A.	NT A
	 Total number of hydrants. 	-NA-	-NA-	-NA-
10	Hose box.	-NA-	-NA-	-NA-
13. P	umping arrangements.		La Rica	
	Ground Level			27.1
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	> Standby Pump output.	-NA-	-NA-	-NA-
	> Standby Pump head.	-NA-	-NA-	-NA-
-	Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	Terrace Level			
	Discharge of pump.	-NA-	-NA-	-NA-
	Head of pump.	-NA-	-NA-	-NA-
	Power supply.	-NA-	-NA-	-NA-
	Auto starting of pump.	-NA-	-NA-	-NA-
14.	Captive water storage for fire-fighting.			
	Underground tank capacity.	-NA-	-NA-	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	-NA-	-NA-	-NA-
15. N	No Smoking signage	Required	Provided in Hindi &	MR
16. P	Provision of Lifts.		English	-
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
17 5	Lift signage. Standby Power Supply	NA	Provided (DG Set)	NA
		1111	(2000)	
18.	Refuge Area			
	Total area	-NA-	-NA-	-NA-
	• Location	-NA-	-NA-	-NA-

19.	Fire Control Room.					
	Detector System Panel.	-NA-	-NA-	-NA-		
	Flow Switch Panel.	-NA-	-NA-	-NA-		
	PA system Panel.	-NA-	-NA-*	-NA-		
	Battery backup	-NA-	-NA-	-NA-		
	Building floor plan	-NA-	-NA-	-NA-		
20.	Special Fire Protection System for the Protection of special Risk, if any.	NA	Co2 flooding system connected through detectors provided in each compressor unit	MR		

"No Smoking" Sign boards were found displayed both in Hindi & English at conspicuous places. No loose electric wiring was seen in the premises.

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under rules, renewal of the FSC issued vide letter No. F6/MS/DFS/CNG/2018/SZ/1014 Dated 10/05/2018 under rules 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA is put up for perusal and signature please.

Signature of the Inspecting Officer

Name: Mr. Rajesh Kumar Designation: ADO (BCP)

As approved, F.T. Jettel is July synature Pl