## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

Dated: -13./0.4/2021

## FIRE SAFETY CERTIFICATE

Certified that the DDCA Bar located at Arun Jaitley Stadium, Ferozshah Kotla Ground, New Delhi comprised of Ground floor only was granted FSC by this department vide letter No.F6/DFS/MS/EH/2017/1435 dated 29/09/17 The premises was re-inspected by the officer concerned of this department on 12/04/21 in the presence of Mr A.K. Chaurasia & Neeraj Sharma and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D with effect from 13 104 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 13 04 2021 New Delhi by.

(Dr. S.K. Tomar) Dy.Chief Fire officer Delhi Fire Service

0x10xm

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Delhi. Id No. 2021032611693 dated 30/03/2021.
- 2. The Manager DDCA, Ferozshah Kotla Ground, New Delhi

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of

unauthorized construction, if any.

The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

8. Inflammable material, if any for interior decoration, shall strictly be prohibited

INSPECTION REPORT

DDCA Bar located at Arun Jaitley Stadium 1. Name & address of the building:-Ferozshah Kotla Ground, New Delhi

Group - D Assembly Building 2. Type of occupancy:-

Ground floor only

3. Type of case:-

4. Details of previous FSC:-5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10 Applicant's letter No:-

Renewal

F6/DFS/MS/EH/2017/1435 dated 29/09/17

N/A 12/04/21

Sh. Ravinder Singh (ADO/CC)

Sh. Rajinder Atwal (DO/CD)

Mr. A.K. Chaurasia & Sh. Neeraj Sharma

2010 Id No. 2021032611693 dated 30/03/2021

| S.No. | Minimum Standards on fire<br>Prevention and fire safety<br>U/R 33 | Requirement<br>Existing | Provided at site | Remarks<br>MR/NMR |
|-------|---|-------------------------|------------------|-------------------|
| 1.    | Access to Building  |                         |                  |                   |
|       | 1) Road width   | 4.5 mtr.                | 4.5 mtr.         | MR                |
|       | 2) Gate width   | 4.5 mtr.                | 6.0 mtr.         | MR                |
|       | 3)Width of internal road  | N/A                     | N/A              | N/A               |
| 2.    | Number, Width Type & Arra   | angement of Ex          | its              |                   |
| 2.    | A. Number of staircases   | · ·                     |                  |                   |
|       | 1. Upper floors   | N/A                     | N/A              | N/A               |
|       | 2. Basements  | N/A                     | N/A              | N/A               |
|       | B. Width of staircase   |                         |                  | 27/4              |
|       | 1. Upper floors   | N/A                     | N/A              | N/A               |
|       | 2. Basements  | N/A                     | N/A              | N/A               |
|       | C. Protection of exits  |                         |                  | 1.00              |
|       | 1. Fire check door  | Required                | Provided         | MR                |
|       | 2. Pressurization   | N/A                     | N/A              | N/A               |
|       | D. No. of continuous staircase to terrace                         | N/A                     | N/A              | N/A               |
|       | E. Width of corridor  | N/A                     | N/A              | N/A               |
|       | F. Door size  | 2 mtr.                  | 2 mtr.           | MR                |
| 3.    | Compartmentation  |                         |                  |                   |
| J.    | 1) Fire check door  | N/A                     | N/A              | N/A               |
|       | 2) Sealing of electrical shafts                                   | N/A                     | N/A              | N/A               |
|       | 3) Fire rating of shaft door                                      | N/A                     | N/A              | N/A               |
|       | 4) Water curtain  | N/A                     | N/A              | N/A               |
|       | 5) Fire Dampers   | N/A                     | N/A              | N/A               |
| 4.    | Smoke Management System   |                         |                  | The sales         |
| 4.    | 1) Basements  | 30 a/c per hour         | N/A              | N/A               |
|       | 2) Upper floors   | 12 a/c per<br>hour      | Natural          | MR                |
| 5.    | Fire Extinguishers  | *                       |                  | 1.00              |
| J.    | 1) Total numbers  | 10 Nos.                 | 12 Nos.          | MR                |
|       | 2) Types  | ABC & CO2               | ABC & CO2        | MR                |
|       | 3) ISI marking  | Required                | Provided         | MR                |
| 6.    | First-Aid Hose Reel   |                         | 1                | ) (D              |
| 0.    | 1) Total number   | 02                      | 02               | MR                |



## N/20

|     | 2) I (1 C1 11                 |                  |               |            |
|-----|-------------------------------|------------------|---------------|------------|
|     | 2) Length of hose reel hose   | 30 m             | 30 m          | MR         |
| _   | 3) Nozzle diameter            | 5 mm             | 5 mm          | MR         |
| 7.  | Automatic Fire Detection &    |                  |               |            |
|     | 1) Type of detectors          | N/A              | Provided      | MR         |
|     | 2) Location of main panel     | N/A              | N/A           | N/A        |
|     | 3) Location of repeater panel |                  | N/A           | N/A        |
|     | 4) Alternate source of power  | N/A              | N/A           | N/A        |
|     | 5) Hooter's Location          | N/A              | N/A           | N/A        |
| 8.  | MOEFA                         | Required         | Provided      | MR         |
| 9.  | Public Address System         | N/A              | N/A           | N/A        |
| 10. | Automatic Sprinkler System    |                  |               |            |
|     | 1) Basement                   | N/A              | N/A           | N/A        |
|     | 2) Gr. + Mezzanine floor      | N/A              | N/A           | N/A        |
|     | 3) Sprinkler above false      | N/A              | N/A           | N/A        |
|     | ceiling                       |                  |               |            |
| 11. | Internal Hydrants             |                  |               |            |
|     | 1) Size of riser/down-comer   | 100 MM           | 100 MM        | MR         |
| -   | 2) Number of hydrants per     | 02               | 02            | MR         |
|     | floor                         |                  |               |            |
|     | 3) Hose box                   | 02               | 02            | MR         |
| 12. | Yard Hydrants                 |                  |               | 1,122      |
|     | 1) Total number of hydrants   | N/A              | Provided      | N/A        |
|     | 2) Hose box                   | N/A              | Provided      | N/A        |
| 13. | Pumping Arrangement           | 1                | 11011404      | 1771       |
|     | 1) Ground level               |                  |               |            |
|     | a) Discharge of main          | 2250 LPM         | 2250 LPM      | MR         |
|     | pump                          | 2200 BINI        | ZZZO BI WI    | , IVIIC    |
|     | b) Head of main pump          | 40 mtr.          | 40 mtr.       | MR         |
|     | c) Number of main             | 01               | 01            | MR         |
|     | pump                          |                  |               | IVIIC      |
| y . | d) Jockey pump out put        | 180 LPM          | 180 LPM       | MR         |
|     | e) Jockey pump head           | 40 mtr.          | 40 mtr.       | MR         |
|     | f) Stand by pump              | N/A              | N/A           | N/A        |
|     | output                        | 11/11            | 14/11         | IVA        |
|     | g) Stand by pump head         | Required         | Provided      | MR         |
|     | h) Auto starting/Manual       | Required         | Provided      | MR         |
|     | stopping                      | - to quitou      | TTOVIGOR      | IVIIC      |
|     | 2) Terrace level              |                  |               |            |
|     | a) Discharge of pump          | N/A              | N/A           | N/A        |
|     | b) Head of pump               | N/A              | N/A           | N/A        |
|     | c) Power supply               | N/A              | N/A           | N/A        |
|     | d) Auto starting of           | N/A              | N/A           | N/A<br>N/A |
|     | pump                          | 1 1/1 1          | 11//1         | IV/A       |
| 14. | Captive Water Storage for Fi  | re Fighting      |               | 7.         |
|     | 1) Under ground tank          | 2,00,000         | 2,00,000 ltr. | MR         |
|     | capacity                      | 2,00,000<br>ltr. | 2,00,000 111. | IVIIX      |
|     | a) Draw-off connection        | Required         | Provided      | MR         |
|     | b) Fire service inlet         | Required         | Provided      | MR         |
|     | c) Access to tank             | Required         | Provided      |            |
|     | d) Over head tank capacity    | A                | N/A           | MR         |
| 15. | Exit Signage.                 |                  |               | N/A        |
| 13. | DAIL SIGHAGE.                 | Required         | Provided      | MR         |



| 16.  | Provision of Lifts.             |          |          |     |
|--|---------------------------------|----------|----------|-----|
|  | a) Pressurization of lift shaft | N/A      | N/A      | N/A |
|  | b) Pressurization of lift lobby | N/A      | N/A      | N/A |
|  | c) Communication in lift car    | N/A      | N/A      | N/A |
|  | d) Fireman's switch             | N/A      | N/A      | N/A |
|  | e) Lift signage                 | N/A      | N/A      | N/A |
| 17.  | Stand by Power Supply           | Required | Provided | MR  |
| 18.  | Refuge Area                     | N/A      | N/A      | N/A |
|  | Total area location             | N/A      | N/A      | N/A |
| 19.  | Fire Control Room               | N/A      | N/A      | N/A |
|  | a) Detector system panel        | N/A      | N/A      | N/A |
|  | b) Flow switch panel            | N/A      | N/A      | N/A |
|  | c) PA system panel              | N/A      | N/A      | N/A |
|  | d) Battery backup               | N/A      | N/A      | N/A |
|  | e) Building floor plan          | N/A      | N/A      | N/A |
| 20. Special Fire Protection System for Protection of sp<br>Risk, if any: |                                 |          |          | N/A |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/EH/2017/1435 dated 29/09/17 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the Inspecting Officer

Name: - Sh. Rajinder Attwal

Designation: - DO (CD)

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

sapporomed Pri pertrap for les Perusel and Sepholoff

024 -6106-021