GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/School/2021/NDZ/ 350

Dated: 03/05/2021

FIRE SAFETY CERTIFICATE

Certified that the Queen Global International School located at C-Block, Dilshad Garden, Delhi-10095, comprised of ground plus three upper floors, owned/occupied by No. vide letter FSC issued School. was International Global Queen F6/DFS/MS/School/2018/611. The school building was re-inspected by the officer concerned of this department in the presence of Mr. Anoop Minocha, Chairmen of the school and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and observed that the school building fit for occupancy class "B" 'Educational Building' for Ground plus three floor only with effect from 0.3×10^{-5} for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on ... 0.3 \ 0.5 \ 20.2 \ ... at New Delhi by.

(Dr.S.K.Tomar)
Dy. Chief Fire Officer

To,

The Manager, Queen Global International School C-Block, Main Road, Dilshad Garden, Delhi-10095

Copy:-

The Dy. Director of Education, B- Block, Yamuna Vihar, Delhi-110053

Conditions for the validity of Fire Safety Certificate

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

C-Block, Main Road, Dilshad Garden, Delhi-10095

2. Building is comprised of : Ground plus three upper floor only

3. Type of Occupancy : Educational

4. Type of Case : Renewal

5. Details of Previous FSC letter : F6/DFS/MS/School/2018/611 Dt.06/04/18

6. Fire Safety directive letter No : NBC Part IV7. Date of Inspection : 19/04/2021

8. Name of the Inspecting officers : ADO Mehmood

9. Name and designation of Officer

from the building side : Mr.Anoop Minocha(Chairmen)

10. Year of Construction : 2014

11. Applicant's letter No : Email , dated 05/04/2021

Sr.	Minimum Standards on fire	NBC Part IV	Provided at Site	Remarks MR/NMR				
No 01	prevention and fire safety U/R33 Access to building.	Requirement		IVITATIVITA				
01	Access to building.							
	Road width	06 mtr.	30 mtr.	MR				
	 Gate width 	4.5 mtr.	4.5 mtr.	MR				
	 Width of internal road 	N/A	N/A	N/A				
02	Number, Width, Type and Arrangement of Exits.							
	a. Number of Staircases			/-				
	 Upper Floor 	02 no	02 no.	MR				
	 Basement 	N/A	N/A	N/A				
	B. Width of Staircases		8					
	 Upper Floor 	1.50 mtr	1.5 mtr. each	MR				
	 Basement 	N/A	N/A	N/A				
	c. Protection of exits		- E					
	 Fire check door 	N/A	· N/A	N/A				
	 Pressurization 	N/A	N/A	N/A				
	d. No. of continuous staircases to terrace	01 no.	02 no.	MR				
	e. Width of Corridor	1.50 mtr.	02.63 mtr	MR				
	f. Door Size class room	01 mtr.	01 mtr.	MR				
03	Compartmentation.							
	Fire check door	N/A	N/A	N/A				
	Sealing of electrical shafts	N/A	N/A	N/A				
	Fire rating of shaft door	N/A	N/A	N/A				
	Water curtain	N/A	N/A	N/A				
	Fire Dampers	N/A	N/A	N/A				
04	Smoke Management System.							
	Basement	N/A	N/A	N/A				
	 Upper floor 	N/A	N/A	N/A				
05.	Fire Extinguishers.							
	Total numbers	10 nos.	12 nos.	MR				
	• types	ABC /CO ₂	ABC /CO ₂	MR				
	IS marking	ISI marked	ISI marked	MR				

06	First-aid-Hose Reels.						
	Total numbers on each floor	02 no.	02 no.	MR			
	 Length of hose reel hose 	30 mtr	30 mtr	MR			
	Nozzle diameter	05 mm	05 mm	MR			
07	Automatic fire detection and alarming system.						
	Type of detectors	N/A	N/A	N/A			
	 Location of main panel 	N/A	N/A	N/A			
	 Location of repeater panel 	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	Hooter's location	N/A	N/A	N/A			
08	MOEFA	N/A	N/A	N/A			
09	Public address System.	N/A	N/A	N/A			
10	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	upper floor	N/A	N/A	N/A			
	sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	size of riser/down-comer	N/A	Provided	MR			
	Number of hydrants per floor	N/A	Provided	MR			
	Hose Box	N/A	Provided	MR			
12	Yard Hydrants.	· ·					
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level	N/A	N/A	N/A			
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main Pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby pump out put	N/A	N/A	N/A			
	Standby pump Head	N/A	N/A	N/A			
	Auto Starting /Manual stopping	N/A	N/A	N/A			
	Pump House AccessTerrace Level	N/A	N/A	N/A			
	Terrace Level Discharge of pump	450 Lpm.	450 Lpm.	MR			
	Head of the Pump	40 mtr	40 mtr	MR			
	> Power supply	Required	Provided	MR			
	> Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for Fire Fighting.	. toquii ou					
	Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	N/A	N/A			
	Access to tank	Required	Provided	MR			
	Overhead Tank capacity	10,000 Ltr.	10,000 Ltr	MR			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication in lift car	N/A	N/A	N/A			
	- Communication in lift cal						
	 Firemen's grounding switch 	N/A	N/A	N/A			

	. 1	N/A	N/A	N/A
17	Standby power supply	IVA		,
18	Refuge Area.		2	
10	,	N/A	N/A	N/A
	Total area	N/A	N/A	N/A
	Location	IN/A		
19	Fire Control Room			
10		N/A	N/A	N/A
	Detector system panel	N/A	N/A	N/A
	 Flow switch panel 		N/A	N/A
	PA system panel	N/A	- MATERIAL .	N/A
		N/A	N/A	
	Battery backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection systems	IN/A		
	for protection of special Risks, if			
	any:			

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the substantial deemed compliance of the minimum standards on fire prevention and fire safety required under the NBC Part IV, it is recommended to renew Fire Safety Certificate.

Signature of the Inspecting Officer

Name Designation

: Mehmood : ADO (TP)

Dy. CEO(NDZ) F. M. p1.

ADOCTO)

A B. T Letter prol y for legrostine bleamed

So 1472007

April 17

Dy 180 (002)

M.S.Cell