GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2021/ 186

Dated 2.2.1.4/2021

FIRE SAFETY CERTIFICATE

Certified that the **Tushar Continental Guest House** located at **2677**, **Gali no. 8**, **Chuna Mnadi, Pahar Ganj, New Delhi** comprised of Ground + 03 Upper floors, Ground floor (02 guest rooms), 1st floor to 3rd floor (04 guest rooms at each floor), total 14 guest rooms owned/occupied by Tushar Guest House was granted FSC by this department vide letter No.F6/DFS/MS/GH/NDZ/2018/718 dated **17/04/18**. The premises was re-inspected by the officer concerned of this department on **12/04/21** in the presence of Sh. Ramesh Sikka and found that the said guest house building deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class **Residential**, **Sub Division-A-1 Ground floor (02 guest rooms)**, **1st floor to 3rd floor (04 guest rooms at each floor)**, **total 14 guest rooms only** with effect from **2214** 4 **124** - **24** - **25** - **26** -

Issued 22/4/21—at New Delhi by.

(**Dr. S.K.Tomar**)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi online id 2021032711710 dated 27.03.2021
- 2. The Manager,

Tushar Guest House at 2677 Gali no. 8, Chuna Mnadi, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building Tushar Guest House at 2677/8, Gali no. 8,

Chuna Mnadi, Pahar Ganj, New Delhi.

2. Type of occupancy:-Residential, Sub Division-A-1

> Gr. + 03 Upper floors (total 14 Guest rooms) Ground floor (02 guest rooms), 1st floor to 3rd floor

(04 guest rooms at each floor)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/NDZ/2018/718 dated

17/04/18.

5. Fire safety directives No.-N/A

6. Date of inspection:-12/04/21

7. Name of the inspecting officer:-Sh. Ravinder Singh(ADO/CC)

8. Name & designation of officer

From the building side:-Sh. Ramesh sikka

9. Year of construction:-OLD

10. Applicant's letter No:online id 2021032711710 dated 27.03.2021

		-	*	Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	06 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases		5		
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	1.25 mtr.	1.25 mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	01	01	MR	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation	-	<u> </u>		
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 ACPH	Required exhaust fan	Provided	
5.	Fire Extinguishers			** · · · ·	

	1) 70 . 1			Telling Control		
	1) Total numbers	20 Nos.	20 Nos.	N. Z-		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
_	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors Co Type	Required	Provided	MR		
	2) Location of main panel Gr. Floor	Required	Provided	MR		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	Required	Provided	MR		
	5) Hooter's Location	Required	Provided	MR		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System		Tiovided	IVIIX		
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling	14/71	IN/A	IN/A		
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A			
	floor	IV/A	IN/A	N/A		
	3) Hose box	N/A	N/A	NT/A		
12.	Yard Hydrants	11/74	IN/A	N/A		
	1) Total number of hydrants	N/A	N/A	DT/A		
	2) Hose box	N/A	N/A N/A	N/A		
13.	Pumping Arrangement	IVA	IN/A	N/A		
101	1) Ground level	NI/A	77/4	27/4		
	a) Discharge of main	N/A	N/A	N/A		
	pump	N/A	N/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping					
	2) Terrace level					
	a) Discharge of pump	225 LPM	225 LPM	MR		
	b) Head of pump	30 mtr.	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fi	re Fighting				
	1) Under ground tank	N/A	N/A	N/A		

1/22

	capacity		DT/A	N/A
	a) Draw-off connection	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	N/A
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	2		
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
10.	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
17.	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any:	stem for Prote	ection of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2018/718 dated 17/04/18 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: Ravinder Singh Designation: ADO (CC)

20 (co)
Rud
194

F.G. P1.

Dycho (2002)

OK 10 mex