GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS : DELHI FIRE SERVICE : NEW DELHI - 110001**

No. F6/DFS/MS/NDZ/2021/ 270

Dated:.../2021 22 06

FIRE SAFETY CERTIFICATE

Certified that the State Bank Of India Building located at 11 Sansad Marg, New Delhi, comprising of A- block (G+ Mezzanine and four upper floor), B- block (ground and first floor), C- block (basement, ground and eight upper floor) and D-block (basement, ground and 13th upper floor) owned/occupied by SBI was granted NOC by this department vide letter No. F6/DFS/MS/91/901 dated 21.05.91. The premises was re-inspected by the officer concerned of this department on 14/06/21 in the presence of Sh. P.K. Gupta CM(P&E) and Sh. Geetam Singh, fire officer and found that the block -D has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises (block -D except basement) is fit for occupancy class Business Building, with effect from 2.2/25. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 29/06/202/at New Delhi by.

Delhi Fire Service

Copy to:-

1. The Chief Architect, NDMC, Palika Kendra, New Delhi

2. Sh. Y.P Matta, AGM (P & I), SBI, 11 Sansad Marg, New Delhi.

Condition for the validity of fire safety certificate

1. This FSC is valid only for D- block except basement.

2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

4. The trained fire fighting staff should be available round the clock.

5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized

construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first The form is available on schedule of Delhi Fire Service Rules 2010. www.dfs.delhigovt.nic.in

8. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case

of an emergency. 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

| | 4 | | |
|-----|----|-----|--|
| _ 1 | T. | 1 6 | |
| V | 1 | 18 | |
| | | | |

| | INSPECTION | ON REPORT |
|----|---|---|
| 1. | Name & address of the building | State Bank Of India ,11 Sansad Marg, New Delhi |
| 2. | Type of occupancy: - | Business occupancy – Block -D comprised of combined basement beneath block C & D, Ground and thirteen upper floors. |
| 3 | Type of case: - | Renewal |
| 4 | Details of previous FSC: - | F6/DFS/MS/91/901 dated 21.05.91 |
| 5 | Fire safety directives No | N/A |
| 6 | Date of inspection: - | 14.06.2021 |
| 7 | Name of the inspecting officer: - | Sh. Rayinder Singh (ADO/CC) Sh. Rajinder Atwal, DO (CD) |
| 8 | Name & designation of officer From the building side (joint Inspection) | Sh. P.K Gupta CM (P& E) Sh. Geetam Singh, Fire Officer |
| 9 | Year of construction:- | 1973 |
| 10 | Applicant's letter No:- | Agmpre.ihodel@sbi.co.in dated 26.03.21 |

SBI Building having four block naming A(Mezzanine and four upper floor),B (Ground and first floor),C(Basement ,ground and eight floor) and D (basement, ground and thirteen upper floor).

| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement/ Existing fire safety arrangements | Provided at site | Remarks MR/NMR |
|-------|---|---|--|-------------------|
| 1. | Access to Building | | | |
| | 1) Road width | 09 meter led | Provided | MR |
| | 2) Gate width | N/A | N/A | N/A |
| | 3)Width of internal road | Accessible | Front side accessible | MR |
| 2. | Number, Width Type & Arrai | ngement of Exits | | |
| 21 | A. Number of staircases | | The state of the s | |
| | 1. Upper floors | 02 Nos. | 02 Nos | MR |
| | 2. Basements | 02 Nos.& ramp | 02Nos & ramp | MR |
| | B. Width of staircase | | | ; |
| | 1. Upper floors | 1.20 mtr. | 1.20 mtr. | MR |
| | 2. Basements | 1.20 mtr . | 1.20mtr . | MR |
| | C. Protection of exits | | | |
| | 1. Fire check door | N/A | Provided | MR |
| | 2. Pressurization | N/A | N/A | N/A |
| | D. No. of continuous staircase to terrace | N/A | N/A | N/A |
| | E. Width of corridor | N/A | N/A | N/A |
| | F. Door size | N/A | N/A | N/A |
| 3. | Compartmentation | | | |
| 3. | 1) Fire check door | Required | Provided | MR |
| | 2) Sealing of electrical shafts | Required | Provided | MR |
| | 3) Fire rating of shaft door | Required | Provided | MR |
| | | N/A | N/A | N/A |
| | 4) Water curtain | N/A | N/A | N/A |
| 4. | 5) Fire Dampers Smoke Management System | A 1/ 4 K | | |

MII9

| | 1) Basements | 12 ACPH | Mechanical | MR |
|-----|--|-----------------|--------------|-------|
| | 2) Upper floors | 12 ACPH | Natural | MR |
| | | | | |
| | Fire Extinguishers | (0,,,,, | Provided | MR |
| | 1) Total numbers | 60nos | Piovided | IVIIC |
| | | ABC & CO2 | ABC & CO2 | MR |
| | 2) Types | Required | Provided | MR |
| | 3) ISI marking | Required | Trovided | |
| • | First-Aid Hose Reel 1) Total number at each floor | 01 | Provided | MR |
| | 1) Total number at each moor | O1 | 1101100 | A |
| | × | | 8 | - |
| | 2) Length of hose reel hose | 30 mtr. | 30 mtr. | MR |
| | 3) Nozzle diameter | 05 mm | 05 mm | MR |
| - | Automatic Fire Detection & Ala | | | |
| • | 1) Type of detectors smoke type | Required | Provided | MR |
| | 2) Location of main panel | Required at gr. | Provided | MR |
| | 2) Location of main paner | floor | | |
| | 3) Location of repeater panel | Required | Provided | MR |
| | 4) Alternate source of power | Required | Provided | MR |
| | 5) Hooter's Location | Required at | Provided | MR |
| | 5) Hootel 3 Location | each floor | | |
| 8. | MOEFA | Required | Provided | MR |
| 9. | Public Address System | Required | Provided | MR |
| 10. | Automatic Sprinkler System | | | |
| 10. | 1) Basement | Required | Provided | MR |
| | 2) Upper floors | N/A | N/A | N/A |
| | 3) Sprinkler above false ceiling | N/A | N/A | N/A |
| 11. | Internal Hydrants | | | |
| 11. | 1) Size of riser/down-comer | 100 mm | 100 mm | MR |
| | 2) Number of hydrants per floor | 01 | Provided | MR |
| | 3) Hose box | 01 | Provided | MR |
| 12. | Yard Hydrants | | | |
| 12. | 1) Total number of hydrants | 04 nos | Provided | MR |
| | 2) Hose box | 04 nos | Provided | MR |
| 13. | Pumping Arrangement | | | |
| 15. | 1) Ground level | 2 | | No. |
| | a) Discharge of main | 2280 LPM | 2280 LPM | MR |
| | pump | | | |
| | b) Head of main pump | 100 meter | 100 meter | MR |
| | c) Number of main pump | 01 nos | 01 nos | MR |
| | d) Jockey pump out put | 180 LPM | 180 LPM | MR |
| | e) Jockey pump head | 100 meter | 100 meter | MR |
| | f) Stand by pump output | 2280 LPM | 2280 LPM | MR |
| | g) Stand by pump head | 100 meter | 100 meter | MR |
| | h) Auto starting/Manual | Required | Provided | MR |
| | stopping | | | MP |
| | 2) Terrace level | Required | Provided | MR |
| | a) Discharge of pump | 450LPM | 450LPM | MR |
| | b) Head of pump | 40m | 40m | 40m |
| | c) Power supply | Required | Provided | MR |
| | d) Auto starting of pump | Required | Provided | MR |
| 14. | Captive Water Storage for Fi | re Fighting | | I MD |
| 170 | 1) Underground tank | 50,000 liter | 50,000 liter | MR |
| | capacity | | 2 11 1 | MD |
| | a) Draw-off connection | Required | Provided | MR |
| | b) Fire service inlet | Required | Provided | MR |

| | c) Access to tank | Required | Provided | MR |
|-----|--|-------------|-------------|----------|
| | d) Overhead tank capacity | 20,000 ltr. | 20,000 ltr. | |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | - sequinou | Tiovided | MR |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | Required | Provided | MR |
| | d) Fireman's switch | Required | Provided | MR |
| 17. | e) Lift signage | Required | Provided | MR |
| | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | Provided | N/A |
| | a) Detector system panel | N/A | Provided | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | Required | Provided | MR |
| | d) Battery backup | Required | Provided | MR |
| | e) Building floor plan | N/A | N/A | N/A |
| 0. | Special Fire Protection System for Protection of special Risk, if any: ABC & CO ² | | | Provided |

The fire protection systems provided in the building were randomly tested, checked and found functional of block -D except basement at the time of inspection.

Further, Block A, B & C has not complied of shortcomings issued vide letter No F6/DFS/ADO/CC/831 dated 22.07.2019 in toto due pandemic situation and renovation work is under process (letter enclosed at C-118).

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures in D- block as required under the rules, if agreed, we may renew the FSC issued vide letter no. F6/DFS/MS/91/901 dated 21.05.91 for D-block only except basement, under rule 35 of the Delhi Fire Service rules 2010. Accordingly, DFA is prepared and put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name:-Rajinder Atwal

Designation :- DO (CD)

Signature of the Inspecting Officer

Name: - Ravinder Singh

Designation :- ADO (CC)

RFO (h.dm)

Link

had the

18)6

अतिरित हो तो कृपया लौटाएँ :