## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001 No. F6/DFS/MS/NDZ/2021/ 97 Dated: 2.5/.6.../2021

No. F6/DFS/MS/NDZ/2021/ 975

## FIRE SAFETY CERTIFICATE

Certified that the National Herald House located at 5-A, Bahadur Shah Zafar Marg, New Delhi, comprising of basement, ground and four upper floor, was granted NOC by this department vide letter no. F6/DFS/MS/2005/1234 dated 10.06.2005. The premises was re-inspected by the officer concerned of this department on 16/06/21 in the presence of Mr. Ran Vijay and found that the premises has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Business occupancy, with effect from under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 25/06/22 at New Delhi by.

Delhi Fire Service

## Copy to:-

1. The Chief Architect, NDMC, Palika Kendra, New Delhi

2. The Authorized Signatory , Associate Journals Limited, National Herald House, 5- A, Bahadur Shah Zafar Marg, New Delhi.

## Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.

3. The trained firefighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

1.	Name & address of the build		G1 4 =			
	reality and address of the build	iiiig	Marg, New Delhi		ır Shah Zafaı	
2.	Type of occupancy:-		Business building: basement, Ground ar four upper floor			
3	Type of case:-	e:- Renewa		(12 Points)		
4	Details of previous FSC:-		F6/DFS/MS/2005/1234 dated 10.06.2005			
5	Fire safety directives No					
6	Date of inspection:-			1		
7	Name of the inspecting officer:-		16.06.2021 Sh. Ravinder Singh (ADO/CC) Sh. Rajinder Atwal, DO (CD)			
8	Name & designation of office From the building side:-	& designation of officer Mr. Ran				
9	Year of construction:-		1973			
10	Applicant's letter No:-		Letter no. dated 12.04.2021			
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		Letter 110.	ualeu 12.04.2021	D	
					Renev	
S.No.	Minimum Standards on fire Prevention and fire safety U/R	per	quirement as	Provided at site	Remarks MR/NMR	
	Approach to Building	/IN	BC part-4			
	1) Road width	06	mtr	20 mtr	A A FD	
	2) Gate width	N/A		N/A	MR	
	3)Width of internal				N/A	
•		N/A		N/A	N/A	
•	Number, Width Type & Arran  A. Number of staircases	igeme	ent of Exits	- ,		
	1. Upper floors	02	Nos.	02.31	1	
	2. Basements		Nos.	02 Nos.	MR	
		02 1105.		02 Nos.( one ramp )	MR	
	B. Width of staircase					
	1. Upper floors	1.2.	5mtr	1.50 mtr & 1.25 mtr	MR	
	2. Basements	1.25mtr		1.50 mtr & 1.25 mtr .	MR	
	C. Protection of exits			1,		
	1. Fire check door	N/A		N/A	N/A	
	2. Pressurization	N/A		N/A	N/A	
	D. No. of continuous staircase to terrace		Nos	01 Nos	MR	
	E. Width of corridor	1.0m		1.50m	MR	
	F. Door size( room )	01 r	ntr.	01 mtr.	MR	
	Compartmentation				K	
	1) Fire check door at fire escape staircase.		uired	Provided	MR	
	2) Sealing of electrical shafts		uired	Provided	MR	
}	3) Fire rating of shaft door	N/A		N/A	N/A	
	4) Water curtain	N/A		N/A	N/A	
	5) Fire Dampers	N/A		N/A	N/A	
	Smoke Management System  1) Basements	12 A	СРН	Mechanical	MR	
			1	(exhaust)		

5.	Fire Extinguishers					
	1) Total numbers	1637				
	2) Types	15 Nos.	16Nos.	MR		
	3) ISI marking	ABC & CO2	ABC & CO2	MR		
6.		Required	Provided	MR		
0.	1) Total number at 1 G					
	1) Total number at each floor	01	01	MR		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
7	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & A					
	1) Type of detectors smoke type	Required	Provided	MR		
	2) Location of main panel	Required	Provided	MR		
		(ground floor)		IVIIC		
	3) Location of repeater panel	Required	Provided	MR		
	4) Alternate source of power	Required	Provided	MR		
	5) Hooter's Location	Required	Provided	MR		
3.	MOEFA	Required				
).	Public Address System	Required	Provided	MR		
0.	Automatic Sprinkler System	Required	Provided	MR		
	1) Basement	Required	D			
	2) Upper floors	N/A	Provided	MR		
	3) Sprinkler above false ceiling		Provided	N/A		
1.	Internal Hydrants	N/A	N/A	N/A		
	1) Size of riser/down-comer	1100				
	2) Number of hydroute and	100mm	100mm	MR		
	2) Number of hydrants per floor 3) Hose box	01	01	MR		
2.		01	01	MR		
۷.	Yard Hydrants	1				
	1) Total number of hydrants	02	02	MR		
2	2) Hose box	02	02	MR		
13.	Pumping Arrangement					
	Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump		4 4			
	b) Head of main pump	N/A	N/A	N/A .		
	c) Number of main pump	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	2280 LPM	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A N/A		
	stopping		1.1/2.1	I VA		
	2) Terrace level			+12		
	a) Discharge of pump	900 & 450	2280& 450 LPM	MR		
	C - F mmp	LPM	22000 TJU LFIVI	IVIIX		
	b) Head of pump	30 mtr.	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided			
	Captive Water Storage for Fire	Fighting	riovided	MR		
-	1) Underground tank	40,000liter	40.0001:4	100		
	capacity	40,000mer	40,000liter	MR		
		Required	Duovid - 1	MD		
			Provided	MR		
		Required	Provided	MR		
		Required	Provided	MR		
		20,000 ltr.	20,000 ltr.	MR		
		Required	Provided	MR		
	Provision of Lifts.	<u> </u>				
- 1						



	shaft		27/4	N/A
	b) Pressurization of lift lobby	N/A	N/A	
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System any: ABC & CO <sub>2</sub>	n of special Risk, if	N/A	

The fire protection systems provided in the building were randomly tested,

checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, the NOC issued vide letter No. F6/DFS/MS/2005/1234 dated 10.06.2005, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval please.

Signature of the Inspecting Officer

Name: - Sh. Rajinder Atwal Designation: - DO (CD) 14/12/613

Signature of the Inspecting Officer

Name: - Sh. Ravinder Singh Designation: - ADO (CC)

CFD (H.048)

Jes)

der 248

00/00

म (संदेश)