FORM'H

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/SZ/2021/Metro/

281

Dated: 95/06/202/

FIRE SAFETY CERTIFICATE

Issued on at New Delhi by.

(SUNIL CHAWDHARY)
DY. CHIEF FIRE OFFICER (S.Z.).

Copy to:

1. Sh. Vivek Srivastava (JGM/E&M), Metro Bhawan, Fire Brigade Lane, Barakhamba Road, New Delhi-110001.

Conditions for the validity of Fire Safety Certificate:-

- 1. All the means of escape / entry / exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided there in shall be maintained in good working conditions at all times.
- 3. Any Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 4. All the staff members must know the correct method of operation of fire fighting system.
- 5. This Fire Safety Certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3. of UBBL-2016), if any.
- 6. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 7. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 8. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on WWW.dfs.Delhigovt.nic.in.

INSPECTION REPORT 1. Name & address of the building: IGDA Underground Metro Station of Line-8. 2. Type of Occupancy : Assembly (Group –D) 3. Type of Case : Renewal (Undercroft+ Platform+ Concourse+ Ground Floor) 4. Details of previous NOC: F6/DFS/MS/Assembly(UG)/SZ/2018/276 dated 21/02/2018 5. Fire Safety directives Letter No.: Nil 6. Date of inspection : 11/06/2021 7. Name of the Inspecting Officers: ADO(S.J.) 8. Name and designation of Officer from the building side : Sh. Bhirgu (A.M. Fire) 9. Year of Construction : 2017 10. Applicant's letter received through email <u>ID-bhirgu_13302@dmrc.org</u> dated 23/03/2021 Minimum standards on fire NFPA / NBC Provided at Remarks prevention and fire safety U/R 33 Requirements site MR/NMR Access of building Road width Required 10m MR Gate width NA 6m NA Width of internal road Approachable Abut on Road MR Number, width, Type & Arrangements of exits Number of staircases Upper floors NA NA NA 1. Undercroft to Platform-3 Nos. Basements Provided MR 2. Platform to Concourse-7 Nos + 8 Escalator. (50%Capacit 3. Concourse to Ground -6 Nos + 3 Escalator. y of Escalators is counted for evacuation in NFPA) Width of staircases Upper floors NA NA NA Basements 2.4m & 1.2m 1. 1.25m x 3 MR 2.2.4m x 4, 2.85m & 1.25m x 2, 1m x 2. (maintenance 3. 2.85m x 4, 1.5m, 1.25m x 1 & 1m x 3Nos. staircase) Protection of exits Fire check door Required Provided MR Pressurization Required in Fireman Provided MR Staircase & Emergency Staircase d. No of continuous **Ancillary Building** 1.25m MR staircase to terrace Width Of Corridor 0.91m 1_m MR f. Door Size 0.91m 1_m MR Compartmentation Fire check door Required Provided MR Sealing of electrical Required Provided MR shafts Fire Rating of shaft door 30 minute & 3 Provided MR Hours Water Curtain N/A N/A N/A Fire Dampers Required se return to : Provided MR Smoke managements System Basements NA NA NA Upper floors NA NA NA Fire Extinguishers Total numbers 115 119 MR Types ABC/CO₂/W.Co₂ Provided MR

No

1.

2.

3.

4.

5.

	each floor	each floor Concourse & 09 Nos a		at each Platfo	orm Pro	vided	MR
	 Length of hose reel hose 		36 Mtr.	36 N	36 Mtr.		MR
7	Nozzle diame	6 mm	0 111111		N		
7.		ion and	d alarming system				
	Type of detect		Smoke & Heat Provided			MR	
	• Location of M		Station Control Room Provided			MR	
	 Location of Repeate Panel 			Provid	Provided		MR
	Alternate source power	Required	Provided			MR	
	Hooters' Locate	tion	All Area	Provide	ed		MR
8.	MOEFA		Required	Provide	Provided		MR
9.	Public Address System		Required		Provided		MR
10.	Automatic Sprinkler S	ystem					IVIK
	Basements		Required	Provide	ed	MR	
	 Upper Floor 		N/A	N/A		N/A	
	 Sprinkler above 	false	N/A	N/A		N/A	
	ceiling					14/74	
11.	Internal Hydrants						
	Size of riser/dov comer	wn-	150 mm			150 mm	
	Number of hydr	ante	2 No. in ancillary bu	:ld: 42 N			
	per floor	ants	2 No. in ancillary building. 12 Nos at Concourse & 09 Nos at each				MR
	a Harr D	II D		Platform.			
	Hose Box		2 No. in ancillary building. 12 Nos Provided				MR
			at Concourse & 09 N Platform.	os at each			
12.	Yard Hydrants						
	• Total number of 3 hydrants			Provided	Provided MR		
	 Hose Box 	2 at a	ncillary building & 1	Provided		MR	
13.	Pumping Arrangements	Nos a	t each tunnel portal			IVII	
•	Ground Level						
•	Discharge of main pun		2020 151				
A		пр	2839 LPM	Provided		MR	
	or main pump		90 m for Hydrant & 56 for Sprinkler	Provided	k	MR	
7	runnoci oi mam pump	S	2	Provided	1	B A Fa	
A	Jockey pump out put		189 LPM x 2	Provided		MR	
			90 m for Hydrant &	Provided		MR	
	Ct.: 41 -		56 for Sprinkler	Trovided		MR	
Standby Pump out put			2839 LPM x 2	Provided	Provided MR		
A			90 m for Hydrant & 56 for Sprinkler	·····		MR	
	Auto Staring/Manual stopping		Required	Provided	Provided MR		
>	Pump House Access		Required	Drovida I	Provided MR		
•	Terrace level		1	riovided	Provided MR		
>	Discharge of pump	Digate C		N/A	/Λ		
>	Hand Ca		N/A N/A	N/A N/A N/A			
7	Power supply		V/A	N/A N/A		I/A	
-	Auto starting of nump		1/4	17/7		I/A	

四年中(明年)

ामिटेड
重
(इंडिया)
田田
压
王

			41-1	1				
14.	Captive water Storage for fire fighting							
,	Under Ground tank			NA	NA			
	capacity				MR			
	> Draw of connection	Requi		Provided				
	> Fire service inlet	Requi		Provided	MR			
	> Access to tank	2 x 1,00,000 ltr		Provided	MR			
	Overhead Tank capacity			Provided	MR			
15	Exit Signage	Requi	red	Provided	MR			
16.	Provision of Lifts							
	> Pressurization of Lift S	haft	N/A	N/A	N/A			
	Pressurization of lift lol	oby	N/A	N/A	N/A			
	> Communication in lift (Car	Required	Provided	MR			
	Fireman's Grounding Switch		Required	Provided	MR			
	> Lift Signage		Required	Provided	MR			
17.	Standby power supply	Standby power supply		Provided	MR			
18.	Refuge Area							
	> Total area		N/A	N/A	N/A			
	> Location		N/A	N/A	N/A			
19.	Fire control room							
	> Detector system panel R		ired in SCR	Provided	MR			
	Flow Switch Panel F		ired	Provided	MR			
	> PA System Panel		ired	Provided	MR			
	Battery backup		ired	Provided	MR			
	➤ Building Floor Plans		ired	Provided	MR			
20.	Special Fire Protection		Agent	Provided local	MR			
	Systems for Protection of		ing system	application	,			
	special Risks, if any;		ectrical	with				
	Pan			NOVEC1230				
	Tran		former					

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire rules the NOC issued vide letter under the safety required F6/DFS/MS/Assembly(UG)/SZ/2018/276 dated 21/02/2018 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Name

Signature of the Inspecting Officer : Ashok Kumar Jaiswal

Designation: A.D.O. (S.J.)

F.T. is adoled for si