GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2021/SZ/ 411

Dated: 28/6/2021

FIRE SAFETY CERTIFICATE

Certified that St. Vincent Pallotti School located at L – 1501/9, Church Colony, Sangam Vihar, New Delhi- 110062 comprised of Basement, Ground plus one upper floor was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/2018/SZ/1461 Dated 21-06-2018. The said premise was re-inspected by officer concerned of this department on 22/06/2021 in presence of Fr. George kutty (Manager) of the school and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with DOE Circular 262-362 dated 17/01/2005 issued by Director of Education, Govt. of NCT of Delhi, and that the building is fit for occupancy class "Educational Building Group — B" with effect from 28 / 6 / 2021 for a period of Three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 28/6 2021 at New Delhi by

(Sunil Chawdhary) Dy. Chief Fire Officer (SZ) Delhi Fire Service

Copy to: -

- 1. The Principal, St. Vincent Pallotti School located at L 1501/9, Church Colony, Sangam Vihar, New Delhi- 110062
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 2. All the staff members must know the correct method of operation of firefighting system.
- 3. This certificate cannot be treated as regularization of unauthorized construction, if any.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

	INSPECTION	ON REPORT			
1	Name & Address of the Building	St. Vincent Pal	lotti School at L - 150	1/9. Church	
		Colony, Sangam Vihar, New Delhi- 110062			
2	Type of Occupancy	Educational, Group-B (School)			
3	Building Comprised of	Basement, Ground + one upper floor.			
4	Type of Case	Renewal			
5	Details of Previous NOC	F6/DFS/MS/School/2018/SZ/1461 Dated 21-06-2018			
6	Fire Safety Directives Letter No	Circular No F.	16//Estate/CC/Fire		
		Safety/2011/32	298 to 3398 dated 01/03	3/2011	
7	Date of Inspection	22/06/2021			
8	Name of the Inspecting Officers	Sh. Rajesh Kumar ADO (BCP)			
9	Name & Designation of Officers	Fr. George kutty (Manager)			
10	from the building side				
10	Year of construction	2003			
S. No.	Applicant letter No. Minimum standards on Fire Prevention	Gmail- dated 08/06/2021			
S. INO.	and Fire Safety U/R 33	Old NOC	Provided at Site	Remarks	
1.	Access to Building.	requirements		MR/NMR	
1.	Road width	Required	6 mtr	MD	
	Gate width	-NA-	4.5 mtr	MR	
	Site, Discounting City, Pro-Carlot Sept. 11			-NA-	
	Width of internal road	-NA-	-NA-	-NA-	
2.	Number, width, type & arrangement of ex	its.			
	a) Number of Staircase				
	> Upper floors.	02 Nos	Provided	MR	
	Basement floor.	02 Nos	Provided	MR	
	b) Width of Staircase				
	> Upper floors	1.5 m /0.75 m	1.54 m each	MR	
	Basement floor	1.5 m /0.75 m	1.54 m & 1.75 m	MR	
	c) Protection of exits				
	Fire check door	-NA-	-NA-	-NA-	
	> Pressurization	-NA-	-NA-	-NA-	
	d) No. of continuous staircase to terrace	Required	02 No	MR	
	e) Width of corridor f) Door size	-NA-	-NA-	-NA-	
3.	f) Door size Compartmentation.	1 m	Provided	MR	
		NIA	NT A	. 374	
	Fire check door. Sealing of electrical shafts	-NA-	-NA-	-NA-	
	Sealing of electrical shafts.Fire rating of shaft door.	-NA-	-NA-	-NA-	
	Water curtain	-NA-	-NA-	-NA-	
	Fire dampers.	-NA-	-NA-	-NA-	
4.	Smoke Management system.	-11/4-	_1A\[\frac{1}{2}_{\text{-}}\]	-1N/A-	
	Basement	30 ACPH	Exhaust fan provided	MR	
	Upper floors	12 ACPH	Natural Ventilation	MR	
5.	Fire Extinguishers.	12 ACITI	Natural Ventifation	IVIK	
J.	Total numbers	Poquiesd	00 Mac	MD	
		Required	08 Nos	MR	
	• Types	ABC / CO2	ABC & W.CO2 type	MR	
	ISI Marking	ISI marked	Provided	MR	
6.	First Aid Hose Reels.				
	 Total numbers on each floor. 	Two	Provided	MR	
	 Length of hose-reel hose. 	30mtr	Provided	MR	
	Nozzle Diameter	5mm	Provided	MR	
	Automatic fire detection & alarming system.	1	1		

	 Location of Repeater Panel Alternate source of power 	-NA-	-NA-	-NA-
	Hooter's location	-NA-	-NA-	-NA-
8.	MOEFA	-NA-	-NA-	-NA-
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			· ·
	Basement	Required	Provided	MR
	Upper floors	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.			
	Size of Riser/Down-comer	NA	-NA-	NA
	Number of Hydrant per floor	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
12.	Yard Hydrants.			
	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.			
	Ground Level	***	NTA .	D.T.A
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.Jockey Pump head.	-NA-	-NA- -NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level	1471		
	Discharge of pump.	450 lpm	Provided	MR
	Head of pump.	40 mtr	Provided	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.			
A. Fo	Underground tank capacity.	-NA-	-NA-	-NA-
ATTO				-NA-
A.780	Draw-off connection.	-NA-	-NA-	
.A. T 0	Draw-off connection.Fire Service Inlet.	-NA-	-NA-	-NA-
A.T.	 Draw-off connection. Fire Service Inlet. Access to tank. 	-NA- -NA-	-NA-	-NA-
	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. 	-NA- -NA- 5,000 ltr	-NA- -NA- Provided	-NA- -NA- MR
15.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage.	-NA- -NA-	-NA-	-NA-
15. 16.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts.	-NA- -NA- 5,000 ltr Required	-NA- -NA- Provided Provided	-NA- -NA- MR MR
15.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. 	-NA- -NA- 5,000 ltr Required	-NA- Provided Provided	-NA- -NA- MR MR
15.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. 	-NA- -NA- 5,000 ltr Required -NA- -NA-	-NA- -NA- Provided Provided -NA- -NA-	-NA- -NA- MR MR -NA-
15.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. 	-NA- -NA- 5,000 ltr Required -NA- -NA-	-NA- Provided Provided -NA- -NA-	-NA- MR MR MR -NA- -NA-
15.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. 	-NA- -NA- 5,000 ltr Required -NA- -NA- -NA-	-NA- Provided Provided -NANANANA-	-NA- MR MR -NA- -NA- -NA-
15.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. 	-NA- -NA- 5,000 ltr Required -NA- -NA-	-NA- Provided Provided -NA- -NA-	-NA- MR MR -NA- -NA- -NA- -NA-
15.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. 	-NA- -NA- 5,000 ltr Required -NA- -NA- -NA-	-NA- Provided Provided -NANANANA-	-NA- NR MR MR -NA- -NA- -NA-
15. 16.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. 	-NANANANANANANANA-	-NANANANANANANANA-	-NA- NA- MR MR -NA- -NA- -NA- -NA- -NA-
15. 16.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply 	-NA- -NA- 5,000 ltr Required -NA- -NA- -NA- -NA-	-NANANANANANANANA-	-NANANANANANANANA-
15. 16.	 Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area 	-NANANANANANANANA-	-NANANANANANANANA-	-NA- -NA- -NA- -NA- -NA- -NA- -NA-

 PA system panel. Battery backup. Building floor plan. D. Special Fire Protection System for the	-NA-	-NA-	-NA-
	-NA-	-NA-	-NA-
	-NA-	-NA-	-NA-
D. Special Fire Protection System for the	-NA- Protection of special	F	-NA- -NA- Risk, if any.

The fire protection systems provided in the premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under DOE Circular dated 01/03/2011, the FSC issued vide letter No. F6/DFS/MS/School/2018/SZ/1461 Dated 21-06-2018, renewal under rule 37 of the Delhi Fire Service Rules,

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

approved, F.T. tetter is