GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE

NEW DELHI- 110001

No.F6/DFS/MS/School/2021/SZ/ 410

Dated: 28/06/2/

FIRE SAFETY CERTIFICATE

Certified that the **New Delhi Public School**, A-Block, Vikaspuri, New Delhi-110018, comprised of ground floor plus three upper floors, owned/occupied by New Delhi Public School was issued FSC by this department vide letter no. F6/DFS/MS/School/2018/SZ/1400 dated 14/06/2018. The School building was re-inspected by the officer concerned of this department on 16/06/2021 in the presence of Sh. Naresh Sharma (Manager) and found that School building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building is fit for occupancy class "Educational" w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed as below.

Issued on. 28/06/21. at New Delhi.

(Sunil Chawdhary)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to:-

- The Principal,
 New Delhi Public School,
 A-Block, Vikaspuri, New Delhi-110018.
- Director of Education, GNCT of NCT of Delhi, Old Secretariat, New Delhi-110054.

INSPECTION REPORT

1. Name & address of the building

: New Delhi Public School, A-Block, Vikaspuri, New Delhi-18.

2. Building is comprised of

: Ground plus three upper Floors

3. Type of Occupancy

: Educational

4. Type of Case

: Renewal

5. Details of Previous NOC

: F.6/DFS/MS/school/2018/SZ/1400 Dt.- 14/06/2018

6. Fire Safety direction letter No

: Nil

7. Date of Inspection

: 15/06/2021

8. Name of the Inspecting Officers:

: ADO R.K. YADAV

9. Name of the designation of Officer

from the building side

: Sh. Naresh Sharma (Manager)

10. Year of Construction

: 2003-2004

11 Applicant's letter No. : Nil Dated 09/06/2021

S.No	Minimum Standards on fire prevention	Requirement	Provided at Site	Remarks MR/NMR		
	and the safety requirements of Koo					
1	Access to building					
	Road width	6 m	06 m	MR		
	Gate width	4.5 mtrs.	4.5 mtrs.	MR		
	Width of internal road	N.A.	N.A.	N.A.		
2	Number, Width, Type and Arrangement of Exits					
	a. Number of Staircases	03 no.	03 no.	MR		
	Upper Floor	05 110.	05110.			
	Basement	N.A.	N.A.	N.A.		
	B. Width of Staircases	N.A.	N.A.	N.A.		
	Upper Floor	1.50 m	1.60,1.60 &1.70 m	MR		
	Basement	N.A.	N.A.	N.A.		
	c. Protection of exits		*, **n			
	Fire check door	N.A.	N.A.	N.A.		
	Pressurization	N.A.	N.A.	N.A.		
	e. No. of continuous staircases to terrace	01 no.	01 no.	MR		
	g. Width of Corridor	1.50 m	2.15 & 2.10 m	MR		
	h. Door Size	1.0 m	1.12 m	MR		
3	Compartmentation.					
	Fire check door	N.A.	N.A.	N.A.		
	Sealing of electrical shafts	N.A.	N.A.	N.A.		
	Fire rating of shaft door	N.A.	N.A.	N.A.		
	Water curtain	N.A.	N.A.	N.A.		
	Fire Dampers	N.A.	N.A.	N.A.		
4	Smoke Management System.					
	Basement	N.A.	N.A.	N.A.		
	Upper floor	Required	Natural Ventilation	MR		

type IS m 6 First Tota Leng Noz 7 Auto Type Loca Alte Hoo 8 MOI 9 Pub 10 Auto base uppe sprin 11 Inte size Num Hose 12 Yaro Tota Hose 13 Pum	narking t-aid-Hose Reels. al numbers of each floor gth of hose reel hose zle diameter	16 Nos. CO ₂ & ABC ISI marked 01 Nos. 30 m	16 Nos. CO ₂ & ABC ISI marked	MR MR MR						
First Tota Leng Noz Auto Typo Loca Loca Alte Hoo MOI Pub 10 Auto base uppo sprir 11 Inte size Num Hose 12 Yard Tota Hose 13 Pum	narking t-aid-Hose Reels. al numbers of each floor gth of hose reel hose zle diameter	ISI marked 01 Nos. 30 m	ISI marked	5.01.05.00						
First Tota Leng Noz Type Loca Loca Alte Hoo MOI Pub 10 Auto base upprint 11 Inte size Num Hose 12 Yard Tota Hose 13 Pum	t-aid-Hose Reels. al numbers of each floor gth of hose reel hose zle diameter	01 Nos. 30 m		MR						
7 Auto Type Loca Alte Hoo 8 MOI 9 Pub 10 Auto base uppe sprir 11 Inte Size Num Hose 12 Yard Tota Hose 13 Pum	al numbers of each floor gth of hose reel hose zle diameter	30 m								
7 Auto 7 Type Loca Alte Hoo 8 MOI 9 Pub 10 Auto base uppe sprin 11 Inte size Num Hose 12 Yaro Tota Hose 13 Pum	gth of hose reel hose zle diameter	30 m		First-aid-Hose Reels.						
7 Auto Typo Loca Alte Hoo 8 MO 9 Pub 10 Auto base uppo sprir 11 Inte Size Num Hose 12 Yaro Tota Hose 13 Pum	zle diameter		Provided	MR						
7 Auto Type Loca Loca Alte Hoo 8 MOI 9 Pub 10 Auto base uppe sprin 11 Inte size Num Hose 12 Yard Tota Hose 13 Pum			30 m	MR						
Type Loca Alte Hoo 8 MOI 9 Pub 10 Auto base uppe sprin 11 Inte size Num Hose 12 Yard Tota Hose 13 Pum	omatic fire detection and alarming sys	05 mm	05 mm	MR						
Loca Loca Alte Hoo 8 MOI 9 Publ 10 Auto base uppo sprir 11 Inte size Num Hose 12 Yard Tota Hose 13 Pum	Automatic fire detection and alarming system.									
Loca Alte Hoo Alte Hoo Pub 10 Auto base uppo sprir 11 Inte Size Num Hose 12 Yard Tota Hose 13 Pum	e of detectors	N.A.	N.A.	N.A.						
Alte Hoo MOI Pub Auto base uppe sprin Inte size Num Hose 12 Yard Tota Hose 13 Pum	ation of main panel	N.A.	N.A.	N.A.						
Hoo MOI Pub Auto base uppe sprin Inte size Num Hose Tota Hose 13 Pum	ation of repeater panel	N.A.	N.A.	N.A.						
8 MOI 9 Pub 10 Auto base uppe sprir 11 Inte size Num Hose 12 Yard Tota Hose 13 Pum	rnate source of power	N.A.	N.A.	N.A.						
9 Pub 10 Auto base uppo sprir 11 Inte size Num Hose 12 Yard Tota Hose 13 Pum	oters	N.A.	N.A.	N.A.						
9 Pub 10 Auto base uppo sprir 11 Inte size Num Hose 12 Yard Tota Hose 13 Pum	EFA	N.A.	N.A.	N.A.						
base upper sprint Interpresentation in the size of th	lic address System.	N.A.	N.A.	N.A.						
base uppe sprir 11 Inte size Num Hose 12 Yard Tota Hose 13 Pum	Automatic Sprinkler System.									
uppo sprint 11 Inte size Num Hose 12 Yard Tota Hose 13 Pum	ement	N.A.	N.A.	N.A.						
sprin Inte size Num Hose 12 Yard Tota Hose 13 Pum	er floor	N.A.	N.A.	N.A.						
11 Inte size Num Hose 12 Yard Tota Hose 13 Pum	nkler above false ceiling	N.A.	N.A.	N.A.						
size Num Hose 12 Yard Tota Hose 13 Pum	Internal Hydrants									
Num Hose 12 Yard Tota Hose 13 Pum	of riser/down-comer	100 mm	Provided	MR						
Hose Tota Hose Hose Hose	nber of hydrants per floor	01Nos.	Provided	MR						
Tota Hose	e Box	01Nos.	Provided	MR						
Tota Hose 13 Pum	Yard Hydrants.									
Hose 13 Pum	al number of hydrants	N.A.	N.A.	N.A.						
13 Pum	e Box	N.A.	N.A.	N.A.						
	Pumping Arrangements.									
	Ground Level	N.A.	N.A.	N.A.						
	 Discharge of main Pump 	N.A.	N.A.	N.A.						
	➤ Head of Main Pump	N.A.	N.A.	N.A.						
	Number of main pumps	N.A.	N.A.	N.A.						
	Jockey pump out put	N.A.	N.A.	N.A.						
3	Jockey pump head	N.A.	N.A.	N.A.						
	Standby pump out put	N.A.	N.A.	N.A.						
	Standby pump Head	N.A.	N.A.	N.A.						
	Auto Starting / Manual stopping	N.A.	N.A.	N.A.						
2	Pump House Access	N.A.	N.A.	N.A.						
	Terrace Level									
	Discharge of pump	450 & 180 LPM	450 & 180 LPM	MR						
2 9	Head of the Pump	40 m	40 m	MR						
	Power supply	Required	Provided	MR						
	Auto Starting of pump	Required	Provided	MR						

14	Captive Water Storage for Fire Fighting.				
	Underground tank capacity	N.A.	50,000 ltrs	MR	
	Draw-off connection Fire service inlet Access to tank Overhead Tank capacity	N.A.	N.A.	N.A.	
		N.A.	Two way	N.A.	
		N.A.	N.A.	N.A.	
		10,000 ltrs	30,000 ltrs	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.	
	Pressurization of Lift lobby Communication in lift car Firemen's grounding switch Lift Signage	N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
17	Standby power supply	N.A.	N.A.	N.A.	
18	Refuge Area.				
	Total area	N.A.	N.A.	N.A.	
	Location	N.A.	N.A.	N.A.	
19	Fire Control Room				
	Detector system panel	N.A.	N.A.	N.A.	
	Flow switch panel	N.A.	N.A.	N.A.	
	PA system panel Batter backup Building Floor Plans	N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
		N.A.	N.A.	N.A.	
20	Special Fire Protection systems for	N.A.	N.A.	N.A.	
	protection of special Risks, if any:				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire prevention and Fire safety measures as required under the rules the FSC issued vide letter no. F.6/DFS/MS/school/2018/SZ/1400 Dt.- 14/06/2018 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Office

Name Designation R K YADAV ADO (JKP)

DO(South West)

26/06/20

F. J. peler

ADO GRO

for signature Means