C-12

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

No.F.6/DFS/MS/School/2021/SZ/

Dated: 2 /7 / 2 |

FIRE SAFETY CERTIFICATE

Certified that the The New Universal Public School, CD-57/58, Mahavir Enclave, New Delhi-110045, comprised of basement ground & first floor was issued Fire Safety Certificate by this department vide letter No F.6/DFS/MS/School/2017/SZ/606 dated 28/04/2017. The school building was re- inspected by the officer concerned of this department on 21/06/2021 in the presence of Sh. Sanjay Sharma and found that the School building have deemed complied with the fire prevention and fire safety requirements in accordance with the Circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 issued by the Director of Education and that the building/ premises is fit for occupancy class "Educational" w.e.f. the date of issue of this certificate for a period of three years, subject to compliance of the conditions printed as under.

(Sunil Chawdhary) Dy. Chief Fire Officer

of co

Copy to:-

- The Principal, The New Universal Public School, CD-57/58, Mahavir Enclave, New Delhi-110045.
- Director of Education,
 Govt. of NCT of Delhi, Old Secretariat,
 New Delhi 110054.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

INSPECTION REPORT 1. Name & address of the building : The New Universal Public School, CD-57/58, Mahavir Enclave, New Delhi-110045. B+G+1 floor Building is comprised 3. Type of Occupancy Educational 4. Type of Case Renewal 5. Details of Previous NOC F.6/DFS/MS/School/2017/SZ/606 dated 28/04/2017 6. Fire Safety directives letter No F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 7. Date of inspection 21/06/2021

A.D.O. R.K. Yadav

Sh. Sanjay Sharma

10. Year of Construction : 2010

8. Name of Inspecting Officer

From the building side

9. Name and designation of officers

11. Applicant's letter No. : Nil dated29/05/2021

S. No.	Minimum Standards on fire prevention and fire	Requirement	Provided at	Remarks MR/NMR			
	safety U/R 33		site				
L.	Access to building						
	Road width	06 m	06 m	MR			
	Gate width	4.5 m Direct accessible on roa					
	Width of internal road	N/A	N/A	case N/A			
2.	Number, Width, Type & Arrangement of Exits			3			
	a. Number of staircases						
	Upper Floors	03 no.	03 no.	MR			
	Basements	02 no.	02 no.	MR			
	b. Width of staircases						
	Upper FloorBasements	1.50 m & .75	m 1.25, 1.0 & .78 m	MR old case			
	• Basements	.95 & .78 m	.95 & .78 m	MR			
	c. Protection of exits	N/A	N/A	N/A			
	Fire check door	N/A	N/A	N/A			
	Pressurization	IN/A	IN/A	N/A			
	d. No. of continuous staircases to	N/A	N/A	N/A			
	terrace	N/A	.75 M to 2.85 m	MR			
	e. Width of Corridor	1.0 m	1.0 m	MR			
	f. Door Size						
	Compartmentation		:				
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts Signal Control Sealing of electrical shafts	N/A	N/A	N/A			
	Fire Rating of shaft doorWater Curtain	N/A	N/A	N/A			
	• Fire Dampers	N/A	N/A	N/A			
	The Bumpers	N/A	N/A	N/A			
l.	Smoke Management System						
è	Basements	Required	Exhaust fans provided	MR			
	Upper floors	Required	Natural Ventilation provided	MR			
5.	Fire Extinguishers						
	Total numbers	06 No's	Provided	MR			
	• Types	ABC/CO ₂ typ		MR			
	• IS marking	ISI marked	ISI marked	MR			

6.	First-Aid Hose Reels						
	Total numbers on each floor	N/A	one		MR		
	 Length of hose reel hose 	N/A	30 m		MR		
	Nozzle diameter	N/A	05mm	-	MR		
7.	Automatic fire detection and alarming system						
	Type of detectors	N/A	N/A		N/A		
	 Location of Main Panel 	N/A	N/A		N/A		
	 Location of Repeater Panel 	N/A	N/A		N/A		
	 Alternate source of power 	N/A	N/A		N/A		
	 Hooters' Location 	N/A	N/A	-	N/A		
3.	MOEFA	N/A	Provided		MR		
9.	Public Address System	N/A	Provided		MR		
LO.	Automatic Sprinkler System						
	Basement	Required	Provided		MR		
	Ground Floor	N/A	N/A		N/A		
	 Sprinkler above false ceiling 	N/A	N/A		N/A		
.1.	Internal Hydrants						
	Size of riser/down-comer	N/A	100 mm		MR		
	 Number of hydrants per floor 	N/A	one		MR		
	Hose Box	N/A	one		MR		
2.	Yard Hydrants						
	 Total number of hydrants 	N/A	N/A		N/A		
	Hose Box	N/A	N/A		N/A		
.3.	Pumping Arrangements						
	Ground Level			-			
	Discharge of main Pump	N/A	N/A		N/A		
	> Head of Main pump	N/A	N/A		N/A		
	Number of main pumpsJockey Pump out put	N/A	N/A		N/A		
	> Jockey pump head	N/A	N/A	100	N/A		
	Standby Pump out put	N/A	N/A	1 2 2 2 2	N/A		
	Standby Pump Head	N/A	N/A		<u> </u>		
	Auto Starting/Manual Stopping				N/A		
		N/A	N/A	1.1	N/A		
		N/A	N/A		N/A		
	Dump House Access	N/A	N/A		N/A		
	Pump House AccessTerrace level						
	Discharge of pump	450 LPM	450 LPM		MR		
	> Head of the pump	40 M	40 M		MR		
	Power Supply	Required	Provided	055	MR		
	➤ Auto Starting of pump	Required	Provided		MR		
4.	Captive Water Storage for fire fighting		L	1			
	Underground tank capacity	N/A	N/A		N/A		
	> Draw-off connection	N/A	N/A		N/A		
	> Fire service inlet	N/A	N/A		N/A		
	> Access to tank	N/A	N/A		N/A		
	Overhead Tank capacity	5000 Liters	5000 Liters	-	MR		
I E	Evit Signago	Required	Provided	-	MR		
15.	Exit Signage.	Required	Frovided		IVIIV		

16.	Provision of Lifts. (No Lift)						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift CarFireman's Grounding Switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
		N/A	N/A	N/A			
17.	Standby power supply	N/A	N/A	N/A			
18.	Refuge Area.						
	> Total Area	N/A	N/A	N/A			
	> Location	N/A	N/A	N/A			
19.	Fire Control Room						
	Detector System Panel	N/A	N/A	N/A			
	• Flow Switch Panel	N/A	N/A	N/A			
	PA System PanelBattery backup	N/A	N/A	N/A			
	Building Floor Plans	N/A	N/A	N/A			
		N/A	N/A	N/A			
20.	Special Fire Protection System for Protection of special Risks, if any:	N/A	N/A	N/A			

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter number F.6/DFS/MS/School/2017/SZ/606 dated 28/04/2017 renewal in accordance with the Circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 issued by the Director of Education is recommended.

Signature of Inspecting Officer

Name:- R.K.Yadav

Designation:- Asstt. Divisional Officer

Divisional Officer (South West)

2)

ADO (KP)