C133

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/EH/2021/SZ/) 2 3

Dated: 1 7 /2021

FIRE SAFETY CERTIFICATE

Certified that the Eating House in the name & style of Ms Dramz Whisky Bar and Lounge Private Limited, at ground & two upper floors in the building comprised of Basement (Sealed With Brick Wall), ground and two upper floors at premise located at 1580, Ward No 1, Kalka Das Marg, Mehrauli, New Delhi 110030, have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Delhi Fire Service on 25/06/2021 in the presence of Sh. Harjinder Singh / Manager and that the premises is fit for occupancy class "Group–D Assembly" (Restaurant for Ground & Two upper floors) with effect from the date of issue of this certificate for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ___/ ___/2021 at New Delhi by

Copy to: -

- 1. The Dy. Health Officer, SDMC, Public Health Department, Green Park, Aurobindo Marg, New Delhi 110016. (Ref. ID No 2021061213797 dated 12-06-2021)
- 2. The Joint Commissioner of Police (Lic.), 1st Floor, P.S. Defence Colony, New Delhi-110049
- 3. Ms Dramz Whisky Bar & Lounge Pvt. Ltd, at 1580, Ward No 1, Kalka Das Marg, Mehrauli, New Delhi 110030

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire-fighting system.
- 4. The owner/occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

1	Name & Address of the Building	ON REPORT Ms Dramz Whis	sky Bar & Lounge Pvt.	Ltd. at 1580	
4.		Ward No 1, Kalka Das Marg, Mehrauli, New Delh			
2	Type of Occupancy	Assembly 'Group-D' Ground plus 02 upper floors			
3	Building comprised of	Basement, (Sealed with brick wall) Ground plus 0 upper floors (Height 9.50m)			
4	Type of Case	New	igitt 7.50iii)		
5	Details of Previous NOC	Nil			
6	Fire Safety Directives Letter No	UBBL 2016/ NB	C Port IV		
7	Date of Inspection	25/06/2021	CIMITY		
8	Name of the Inspecting Officers				
9		DO (South) & ADO (BCP)			
	Name & Designation of Officers from the building side	Sh. Harjinder Singh / Manager			
10	Year of construction/ date of conversion	2010/2013		× ×	
11	Applicant letter No.	Online Id 2021061213797 dated 12-06-2021			
S. No.	Minimum standards on Fire Prevention	UBBL/ NBC	Provided at Site	Remarks	
1	and Fire Safety U/R 33 Access to Building.	Requirement	1 TOVIGEG AT SITE	ixcinal no	
	3	26	/	7	
	Road width Gate width	06m	12m	MR	
	Width of internal road	NA	NA	-NA-	
2	Number, width, type & arrangement of e	NA	NA	-NA-	
	m. Number of Staircase	XIIS			
	Upper floors	2 Nos	02	1 (1)	
	Basement floor	-NA-	03 nos	MR	
	n. Width of Staircase	=1VA=	01	-NA-	
	Upper floors	1.50 m each	2.0m & 1.50 m (Steel	1.40	
	Basement floor		staircases) and 1.35m	MR	
	o. Protection of exits	-NA-	NA .	-NA-	
	Fire check door	NA	NA	NA	
	Pressurization	-NA-	NA NA	-NA-	
	p. No. of continuous staircase to terrace	01	01	MR	
	q. Width of corridor	N/A	N/A	N/A	
	r. Door size	1.50m each	1.50m each	MR	
3	Compartmentation.			In the second se	
	Fire check door.	Required	Provided at kitchen	MR	
	Sealing of electrical shafts.	N/A	N/A	N/A	
	• Fire rating of shaft door.	N/A	N/A	N/A	
	Water curtain	N/A	N/A	N/A	
	Fire dampers.	N/A	N/A	N/A	
4	Smoke Management system.				
	Basement	30 ACPH	N/A	N/A	
	TT O	12 ACPH	Natural ventilation	MR	
	Upper floors			1	
5	Fire Extinguishers.				
5	Fire Extinguishers. • Total numbers	06 Nos	08 Provided	MR	
5	Fire Extinguishers. • Total numbers • Types	ABC / CO2	ABC & Co2	MR MR	
	Fire Extinguishers.Total numbersTypesISI Marking				
5	Fire Extinguishers. • Total numbers • Types • ISI Marking First Aid Hose Reels.	ABC / CO2 ISI marked	ABC & Co2 Provided	MR MR	
	Fire Extinguishers. • Total numbers • Types • ISI Marking First Aid Hose Reels. • Total numbers on each floor.	ABC / CO2 ISI marked One	ABC & Co2 Provided Provided	MR MR	
	Fire Extinguishers. • Total numbers • Types • ISI Marking First Aid Hose Reels. • Total numbers on each floor. • Length of hose-reel hose.	ABC / CO2 ISI marked One 30m	ABC & Co2 Provided Provided Provided	MR MR MR MR	
	Fire Extinguishers. • Total numbers • Types • ISI Marking First Aid Hose Reels. • Total numbers on each floor.	ABC / CO2 ISI marked One	ABC & Co2 Provided Provided	MR MR	

	Location of Main Panel	NA	Provided	NA
	 Location of Repeater Panel 	N/A	NA	N/A
	Alternate source of power	N/A	NA	N/A
0	Hoofer's location	N/A	NA	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System	-NA-	Provided	-NA-
10	Automatic Sprinkler System		-	
	Basement	N/A	N/A	N/A
	 Upper floors 	N/A	N/A	N/A
	 Sprinkler above false ceiling 	N/A	N/A	N/A
11	Internal Hydrants.			
	Size of Riser/Down-comer	Required	Provided	MR
	 Number of Hydrant per floor 	Required	Provided	MR
	Hose box.	Required	Provided	MR
12	Yard Hydrants.			
	 Total number of hydrants. 	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13	Pumping arrangements.			
	Ground Level			
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
	> Pump House Access	-NA-	-NA-	-NA-
	Terrace Level		e Bio	
	Discharge of pump.	450 LPM	900lpm	MR
	Head of pump.	40m	Provided	MR
	Power supply.Auto starting of pump.	Required	Provided	MR
4	Captive water storage for Fire Fighting.	Required	Provided	MR
		NIA	'AT A	A TA
	 Underground tank capacity. Draw-off connection. 	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	 Overhead tank capacity. 	-NA- 20,000 Ltrs	-NA-	-NA-
15	Exit Signage.	Required	20,000ltrs Provided	MR MR
6	Provision of Lifts.	required	TIOVIDED	NIV
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	 Pressurization of lift lobby. 	-NA-	-NA-	-NA-
	 Communication in lift car. 	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
			Provided	MR
7	Standby Power Supply	Required	11001111111	TATE
	Standby Power Supply Refuge Area	Required		
7	Refuge Area	refriens	no studenti il e e e e e e e e e e e e e e e e e e	
				-NA-

	Detector System Panel.Flow Switch Panel.	-NA-	-NA-	-NA-
	PA system Panel.	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Building floor plan	-NA-	-NA-	-NA-
20	Building floor plan Special Fire Protection System for the Protection of special Risk, if any:	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-

The Fire protection systems provided in the building were test checked at random and found functional at the time of inspection

Keeping in view of the substantially satisfactory compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, it is recommended to grant Fire Safety Certificate under rule 35 (3) of the Delhi Fire Service Rules, 2010.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspection Officer

Name: Sh. S. K Dua Designation: DO (SD) Signature of the Inspecting Officer

Name: Rajesh Kumar Designation: ADO/BCP

Directably

Directably

28)6

Directably

Spul be in baldiely

As approved, F.T. better in puttle

for your synature PI

My

306/2074