C-27

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2021/SZ/ 428

Dated: \_\_\_\_/ \_\_\_/ 2021

## FIRE SAFETY CERTIFICATE

(Sunil Chawdhary) Dy. Chief Fire Officer (SZ) Defhí Fíre Servíce

Copy to: -

1

- ore
- 1. The Principal School of Kendriya Vidyalaya, Pushp Vihar, Sec 3, M.B. road, Saket, New Delhi 110017)
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi.

## Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. This certificate cannot be treated as regularization of unauthorized construction, if any.
- 5. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

	INSPECT	ION REPORT				
1	alaya, Pushp Vihar, Sec	-3, M.B.				
		Road, Saket, New Delhi - 110017				
2	Type of Occupancy		coup-B (School)			
3	Building Comprised of	Ground plus Two upper floor				
4	Type of Case	Renewal				
5	Details of Previous NOC	F6/DFS/MS/School/2015/SZ/1417 Dt. 06/08/2015				
6	Fire Safety Directives Letter No	Nil		310.5 - 10.5 - 1		
7	Date of Inspection	22/06/2021				
8	Name of the Inspecting Officers	Sh. Rajesh Kun	nar ADO (BCP)			
9	Name & Designation of Officers	Smt. Dhariti Das( Principal)				
	from the building side					
10	Year of construction	1992	1992			
11	Applicant letter No.	Gmail Dated 17/06/2021				
S.	Minimum standards on Fire	BBL/NBC Provided at Site Remarks				
No	Prevention and Fire Safety U/R 33	Requirements		MR/NMR		
1	Access to Building.			***************************************		
	Road width	Required	Provided	MR		
	Gate width	Required	03 gate 5 mtr, 4 mtr	MR		
	Width of internal road		& 3.75 mtr	IVIK		
		-NA-	-NA-	-NA-		
2	Number, width, type & arrangement					
	of exits.		· ·			
	a) Number of Staircase					
	Upper floors.	03 nos	Provided	MR		
	Basement floor.	-NA-	-NA-	-NA-		
	b) Width of Staircase			L		
	Upper floors	1.50 m	1.35 m, 1.40 & 1.40 m	MR		
	Basement floor	-NA-	-NA-	-NA-		
	c) Protection of exits					
	Fire check door	-NA-	-NA-	-NA-		
	> Pressurization	-NA-	-NA-	-NA-		
The state of the s		-INA-	-1/1/2-	-1NA-		
	d) No. of continuous staircase to terrace	Required	01 nos.	MR		
	e) Width of corridor	Required	1.50 mtr	MR		
		-				
3	f) Door size Compartmentation.	1 mtr	1 mtr	MR		
3		NT A	N.T.A.	D.T.A		
	• Fire check door.	-NA-	-NA-	-NA-		
	Sealing of electrical shafts.  First retire of the Colored.	-NA-	-NA-	-NA-		
	• Fire rating of shaft door.	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
	• Fire dampers.	-NA-	-NA-	-NA-		
4.	Smoke Management system.	20 - /				
	Basement	30 a/c per hour	-NA-	-NA-		
	Upper floors	12 a/c per hour	-NA-	-NA-		
5.	Fire Extinguishers.					
	Total numbers		54 Nos	MR		
	1	ICI1-	ADO 000	MD		
	• Types	ISI mark	ABC,CO2	MR		

6.	First Aid Hose Reels.			
	Total numbers on each floor.	3 nos.	Provided	MR
	<ul> <li>Length of hose-reel hose.</li> </ul>	30 m	Provided	MR
	Nozzle Diameter	5 mm	Provided	MR
7	Automatic fire detection & alarming system.			
	Type of detectors	-NA-	-NA-	-NA-
	Location of Main Panel	-NA-	-NA-	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	-NA-	-NA-
	Hooter's location	-NA-	-NA-	-NA-
8.	MOEFA	-NA-	-NA-	-NA-
9.	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System	11/2	A 1 A A	
10.	Basement	-NA-	-NA-	-NA-
	Upper floors	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.	1112		
Lie	Size of Riser/Down-comer	-NA-	-NA-	-NA-
	Number of Hydrant per floor	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
12.	Yard Hydrants.	4.47.8	A 1 A A	- 14.6
1.4.	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.	1421	1112	2122
10.	Ground Level			
	<ul><li>Discharge of main pump.</li></ul>	-NA-	-NA-	-NA-
	<ul><li>Head of main pump.</li></ul>	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual	-NA-	-NA-	-NA-
	Stopping.  > Pump house access.	-NA-	-NA-	-NA-
	Terrace Level			
	Discharge of pump.	Required	450 Lpm /	MR
	➤ Head of pump.	Required	38 m	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.		87	
	Underground tank capacity.	-NA-	-NA-	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	<ul> <li>Overhead tank capacity.</li> </ul>	10,000 ltrs	Provided	MR
			Provided	MR
15.	Exit Signage.	Required	riovided	TATT
15. 16.	Exit Signage. Provision of Lifts.	Required	-NA-	-NA-

M/12

	Draggyrigation of lift labby	-NA-	-NA-	-NA-
	<ul> <li>Pressurization of lift lobby.</li> <li>Communication in lift car.</li> </ul>	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.			-NA-
17.	Standby Power Supply	-NA-	-NA-	-IVA-
18.	Refuge Area			
	Total area	-NA-	-NA-	-NA-
	Location	-NA-	-NA-	-NA-
19.	Fire Control Room.			
	<ul><li>Detector system panel.</li><li>Flow switch panel.</li></ul>	-NA-	-NA-	-NA-
	PA system panel.	-NA-	-NA-	-NA-
	Battery backup.	-NA-	-NA-	-NA-
	Building floor plan.	-NA-	-NA-	-NA-
	Dunung noor plan.	-NA-	-NA-	-NA-
20.	<b>Special Fire Protection System for the</b>	-NA-	-NA-	-NA-
	Protection of special Risk, if any.			to a principal de la constantina della constanti

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/School/2015/SZ/1417 Dt. 06/08/2015, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

Dolon Live

Defolar

F.t. pless.

ADOBO F.J.

you synature Bl.

tetter is fourth for

30/6

Dechys2

M

वतरित हो तो कृपया लौटाएँ