GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110001**

F.6/DFS/MS/GH/2021/SZ/ 197 No.

Dated: 0.6../.0.7./2021

FIRE SAFETY CERTIFICATE

Certified that the Guest House in the Name & Style of M/s Sareen Villa Guest House, K - 51, Kalkaji, New Delhi - 110019 comprised of Basement & Ground plus three upper floors (15 Guest Rooms) was already been issued Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/GH/2018/SZ/248 dated 15/02/2018. The premise was re-inspected by the officer concerned of this department on 01/07/2021 in the presence of Sh. P. C Sareen (owner) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential & Lodging", Group-A" (Guest House) with effect from the date of issue 66 / 67/2021 for a period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010

Issued on <u>06 07 2021</u> at New Delhi by

(Sunil Chawdhary) Dy. Chief Fire Officer (SZ)

Delhi Fire Service

Copy to: -

opy to:
1. The Manager M/s Sareen Villa Guest House, K – 51, Kalkaji, New Delhi – 110019.

2. The Addl. Commissioner of Police (Lic.), 1st Floor, P.S. Defence Colony, New Delhi–110049.

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

All the staff members must know the correct method of operation of fire fighting system.

The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any

"The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

	INSPECT	TION REPOI	DE			
1	Name & Address of the Building	M/a SADEFNAVIA				
		VALUAT	EEN VILLA GUEST HO	GUEST HOUSE, K – 5		
2	Type of Occupancy	KALKAJI, New Delhi – 110019				
3	Building Comprised of	Residential (Guest House), "Group – A"				
4	Type of Case	Basement + Ground + 03 upper floors				
5	Details of Previous NOC	Renewal				
6	Fire Safety Directives Letter No	F.6/DFS/M	IS/GH/2018/SZ/248 dated 1	15/02/2018		
7	Date of Inspection	INII				
8	Name of the Inspecting Officers	01/07/2021				
9	Name & Designation of Officers	Sh. Rajesh Kumar ADO (BCP)				
	from the building side	Mr. P. C S	Mr. P. C Sareen (owner)			
10	Year of construction	10004				
			Basement (vacant), Ground Floor (R			
		1	Unice & 03 (i/Room) let Floor (040/p)			
1.1			2 F100F (04 G/Room) 3" F	Floor 4 G/room		
11	Applicant letter No.	Gmail Date	Total 15 Guest Rooms.			
S. No.	Standards of Fire Prevention	Old NO	Gmail Dated- 30-06-2021			
	and Fire Safety U/R 33	Requireme		Remarks		
1	Access to Building.	requireme	III	MR/NMR		
	Road width	Required	1 00			
	Gate width	-NA-	V AIILI	MR		
	 Width of internal road 	-NA-	-NA-	-NA-		
2	Number, width, type & arrangement of exits.	-IVA-	-NA-	-NA-		
	a) Number of Staircase					
	Upper floors.	D 1				
	Basement floor.	Required	One	MR		
	b) Width of Staircase	Required	Two	MR		
	Upper floors	1.05.16				
	Basement floor	1.25 Mtr	1.25 Mtr	MR		
		1.25 Mtr	1.25 Mtr & 1.0m	MR		
	c) Protection of exits		1.011	(old case)		
	Fire check door	-NA-				
	Pressurization	-NA-	-NA-	-NA-		
	d) No. of continuous staircase to terrace		-NA-	-NA-		
	e) Width of corridor	Required -NA-	One	MR		
	f) Door size		-NA-	-NA-		
3	Compartmentation.	1 mtr	1.08 mtr (Final exit)	MR		
	Fire check door.	-NA-				
	Sealing of electrical shafts.	-NA-	-NA-	-NA-		
	Fire rating of shaft door.	AND REAL PROPERTY AND ADDRESS OF THE PARTY AND	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
	Fire dampers.	-NA-	-NA-	-NA-		
4	Smoke Management system.	-NA-	-NA-	-NA-		
	Basement	26 15				
	Upper floors	30 ACPH	Exhaust Fan provided	MR		
5	Fire Extinguishers.	12 ACPH	-NA-	-NA-		
	Total numbers					
	Types		10 Nos	MR		
		ISI marked	CO2- 04 & ABC-06	MR		
6	101 Warking		Provided	MR		
3	First Aid Hose Reels.			TATIC		
	Total numbers on each floor.	Hose Reel	Provided	MD		
	 Length of hose-reel hose. 	30m	Provided	MR		
	Nozzle Diameter	05 mm		MR		
		OJ IIIIII	Provided	MR		

1

7	Automatic fire detection & alarming system.		1	
	Type of detectors	NA	-NA-	NA
	 Location of Main Panel 	-NA-	-NA-	
	 Location of Repeater Panel 	-NA-		-NA-
	 Alternate source of power 	-NA-	-NA-	-NA-
	 Hooter's location 	-NA-	-NA-	-NA-
8	MOEFA	Required	Provided	-NA-
9	Public Address System	-NA-		MR
10	Automatic Sprinkler System	-INT	Provided	-NA-
	Basement	Required	Provided	MD
	 Upper floors 	-NA-		MR
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11	Internal Hydrants.	-11/4-	-NA-	-NA-
	Size of Riser/Down-comer	-NA-	-NĂ-	NT 4
	Number of Hydrant per floor	-NA-		-NA-
	Hose box		-NA-	-NA-
12		-NA-	-NA-	-NA-
14	Yard Hydrants.			
	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13	Pumping arrangements.			
	Ground Level			
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Terrace Level	<u></u>		
	Discharge of pump.	900 LPM	Provided	MR
	Head of pump.	40m	Provided	MR
	Power supply.Auto starting of pump.	Required	Provided	MR
	ratio starting of pump.	Required	Provided	MR
14	Captive water storage for fire fighting.	7-1-1		TATIX
	Underground tank capacity.	-NA-	-NA-	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	6,000 Ltrs	Provided	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			TATIX
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
17	Standby Power Supply	Required	Provided	
18	Refuge Area	required	TIOVIUCU	MR

		-NA-	-NA-	-NA-
	Total areaLocation	-NA-	-NA-	-NA-
19	Fire Control Room.	-NA-	-NA-	-NA-
	 Detector system panel. Flow switch panel. PA system panel. Battery backup. Building floor plan. 	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-		-NA-
20	Special Fire Protection System for the	Protection of special i	NISK, II dily.	

The fire protection system provided in the building / premises were checked, tested at random and found functional at the time of inspection.

Further, fire safety measures prescribed under the notification dated 27.05.2019, wherein amendment made in the UBBL 2016 under clause 7.31 is not applicable as there are total 15 guest rooms i.e. 03 guest rooms at ground floor and 4 guest rooms at FF, 04 G/rooms at SF and 04 G/rooms at 3rd floor.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F.6/DFS/MS/GH/2018/SZ/248 dated 15/02/2018, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Rajesh Kumar Design: ADO (BCP)

As approved, F.T. Letter in forth your signature P1

Dy Golsz

livered please return to