GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/NDZ/2021/ 3/1

Dated: 09 07 /2021

FIRE SAFETY CERTIFICATE

Certified that the building at Plot No.-5, Block-II, B block, Middle Circle, Connaught place, New Delhi comprised of Ground + 02 Upper floors was granted FSC by this department vide letter No.F6/DFS/MS/Hotel/2016/WZ/1385 dated 07/09/16. The premises was re-inspected by the officers concerned of this department on 05/07/21 in the presence of Sh. Kailash Joshi and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly/ Business Building with renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued - 09/07/201 at New Delhi by.

(Dr. S.K.Tomar) Dy. Chief Fire officer Delhi Fire Service 011-23412025

OK TOTAL

Copy to:-

1. The Chief Architect, NDMC Palika Kendra, New Delhi.

2. The Medical Health officer, NDMC Palika kendra, New Delhi

3. The Manager, The colonnade, Plot No.-5, Block-II, B block, Middle Circle, Connaught place, New Delhi

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of

an emergency.

The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

H3

1. Name & address of the building : Plot No.-5, Block-II, B block, Middle Circle, Connaught place, New Delhi.

2. Type of occupancy : Assembly Building Ground + 02 Upper floor

3. Type of case:- : Renewal
4. Details of previous NOC : F6/DFS/MS/Hotel/2016/WZ/1385 dated

07/09/2016

5. Fire safety directives No.

6. Date of inspection: 05/07/21

7. Name of the inspecting officer : Sh. Rajinder Atwal (DO/CD) & Sh. Ravinder Singh ADO/CC

8. Name & designation of officer From the building side

: Sh.Kailash Joshi

9. Year of construction : 2016

10. Applicant's letter No : e-mail < thecolonnadecp@gmail.com > dated 16 06 2021

| | dated 16.06.2021 | | | | |
|-------|---|--|------------------|-------------------|--|
| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement as per BBL/NBC part IV | Provided at site | Remarks MR/NMR | |
| 1. | Access to Building | | | | |
| - | 1) Road width | 06 mtr. | 12 mtr. | MR | |
| | 2) Gate width | 4.5 mtr. | Provided | MR | |
| | 3)Width of internal road | NA | NA | NA | |
| 2. | Number, Width Type & Arrangement of Exits | | | | |
| | A. Number of staircases | | | | |
| | 1. Upper floors | 04 Nos. | 04 Nos. | MR | |
| | 2. Basements | NA | NA | NA | |
| | B. Width of staircase | | | | |
| | 1. Upper floors | 1.5 -two 2.0-one 1.0-one | Provided | MR | |
| | 2. Basements | NA | NA | NA | |
| | C. Protection of exits | | | 12 | |
| | 1. Fire check door | NA | NA | NA | |
| | 2. Pressurization | NA | NA | NA | |
| | D. No. of continuous staircase to terrace | One of 1.0 mtr. | Provided | MR | |
| | E. Width of corridor | NA | NA | NA | |
| | F. Door size | Two doors of 2.0 mtr. | Provided | MR | |
| 3. | Compartmentation | | | | |
| | 1) Fire check door | Required | Provided | MR | |
| | 2) Sealing of electrical shafts | Required | Provided | MR | |
| | 3) Fire rating of shaft door | 2 hrs. | Provided | MR | |
| | 4) Water curtain | NA | NA | NA | |
| | 5) Fire Dampers | NA | NA | NA | |
| 4. | Smoke Management System | | | | |
| | 1) Basements | NA | NA | NA | |
| | 2) Upper floors | 12 ACPH | Provided | MR | |
| 5. | Fire Extinguishers | | | | |

| | 1) Total numbers | 12 | 14 | MR | | |
|----|--|-----------------|-----------|-------|--|--|
| | 2) Types | ABC & CO2 | ABC & CO2 | MR | | |
| | 3) ISI marking | Required | Provided | MR | | |
| 6. | First-Aid Hose Reel | | | | | |
| | 1)Total number of each floor | 02 | Provided | MR | | |
| | 2) Length of hose reel hose | 30 mm | Provided | MR | | |
| | 3) Nozzle diameter | 5 mm | Provided | MR | | |
| 7. | Automatic Fire Detection & Alarming System | | | | | |
| | 1) Type of detectors | Heat & Smoke | Provided | MR | | |
| | 2) Location of main panel | On ground floor | Provided | MR | | |
| | 3) Location of repeater panel | NA | NA | NA | | |
| | 4) Alternate source of power | Required | Provided | MR | | |
| | 5) Hooter's Location | On each floor | Provided | | | |
| 3. | MOEFA | | | MR | | |
|). | | Required | Provided | MR | | |
| 0. | Public Address System | Required | Provided | MR | | |
| U. | Automatic Sprinkler System | 214 | 271 | | | |
| | 1) Basement | NA | NA | NA | | |
| | 2) Upper floors | NA | NA | NA | | |
| | 3) Sprinkler above false ceiling | NA | NA | NA | | |
| 1. | Internal Hydrants | φ. | | | | |
| | 1) Size of riser/down-comer | 100 mm | Provided | MR | | |
| | 2) Number of hydrants per floor | 02 | Provided | MR | | |
| | 3) Hose box each floor | 02 | Provided | MR | | |
| 2. | Yard Hydrants | | 11011404 | IVIIC | | |
| | 1) Total number of hydrants | NA | NA | NA | | |
| | 2) Hose box | NA | NA | NA | | |
| 3. | Pumping Arrangement | 1411 | 1471 | IVA | | |
| | 1) Ground level | | | | | |
| | a) Discharge of main pump | 2280 LPM | Provided | MR | | |
| | b) Head of main pump | 40 M | Provided | MR | | |
| | c) Number of main pump | 01 | Provided | MR | | |
| | d) Jockey pump out put | 180 LPM | Provided | MR | | |
| | e) Jockey pump head | 40 M | Provided | | | |
| | f) Stand by pump output | 2280 LPM | Provided | MR | | |
| | g) Stand by pump head | 40 M | | MR | | |
| | h) Auto starting/Manual | 40 1/1 | Provided | MR | | |
| | stopping | Required | Provided | MR | | |
| | 2) Terrace level | | Provided | MR | | |
| | a) Discharge of pump | 450 LPM | Provided | MR | | |
| | b) Head of pump | 40 M | Provided | MR | | |
| | c) Power supply | Required | Provided | MR | | |
| | d) Auto starting of pump | Required | Provided | MR | | |
| 4. | Captive Water Storage for Fire | 1 | | | | |

| | Under ground tank capacity | 50,000 ltr. | Provided | MR |
|-----|-------------------------------------|------------------|---------------------|----|
| | a) Draw-off connection | Required | Provided | MR |
| | b) Fire service inlet | Required | Provided | MR |
| | c) Access to tank | Required | Provided | MR |
| | d) Over head tank capacity | 10,000 ltr. | Provided | MR |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | - | |
| | a) Pressurization of lift shaft | NA | NA | NA |
| | b) Pressurization of lift lobby | NA | NA | NA |
| | c) Communication in lift car | NA | NA | NA |
| | d) Fireman's switch | NA | NA | NA |
| | e) Lift signage | NA | NA | NA |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | NA | NA | NA |
| | Total area location | NA | NA | NA |
| 19. | Fire Control Room | | | |
| | a) Detector system panel | NA | NA | NA |
| | b) Flow switch panel | NA | NA | NA |
| | c) PA system panel | NA | NA | NA |
| | d) Battery backup | NA | NA | NA |
| | e) Building floor plan | NA | NA | NA |
| 20. | Special Fire Protection System any: | n for Protection | of special Risk, if | MR |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC of issued vide letter no. F6/DFS/MS/2016/WZ/1385 dated 07/09/2016 under rule 35 of the Delhi Fire Service rules 2010.

Signature of the Inspecting Officer

Name:- Rajinder Atwal

Designation :- DO (CD)

Signature of the Inspecting Officer

Name: Ravinder Singh

Designation :- ADO (CC)

Dych Con

F.A. PI

D. No. 338

वितरित हो तो कृपया