GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/Bnqt/2021/NDZ/ 322

Dated: 14/07/21

FIRE SAFETY CERTIFICATE

Certified that the Multipurpose community hall with facilities of Homeopathic dispensary near MIG complex at East of Loni Road, Delhi-110093 comprised of ground plus three upper floors (ground floor parking, 1st floor dispensary and 2nd & 3rd floors community hall) owned/occupied by Delhi Development Authority was inspected by the officer concern of this department in the presence of Mr. Manish Gaur, JE (Elect.) and found that the community hall have complied with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and observed that the building is fit for ground plus three upper floor occupancy class "D" 'Assembly Building' (community Hall) with effect from Aurice 10 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on at New Delhi by

Director
Delhi Fire Service

To,

The Executive Engineer (Elect.)
Delhi Development Authority
Office of the Executive Engineer Electrical Division No.1
Seed Bed Park School Block Shakarpur,
Delhi-110092

Conditions for the validity of Fire Safety Certificate

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

- 3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form `J` [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

social of

Name & address of the building

: Multipurpose community hall with facilities of

Homeopathic dispensary near MIG complex at

East of Loni Road, Delhi-110093

2. Building is comprised of

: Ground plus three upper Floors

3. Type of Occupancy

: Assembly Building

4. Type of Case

:New

5. Details of Previous NOC letter

: Nil

6. Fire Safety directive letter No.

: F6/DFS/MS/BP/2014/138 dated 16/05/14

7. Date of Inspection

: 24/06/2021

8. Name of the Inspecting officers

: ADO Mehmood

9. Name and designation of Officer

from the building side

: Mr. Manish Gaur, JE (Elect.)

10. Year of Construction

: 2015-2016

11. Applicant's letter No

:F.23(01)EE/ELD-1/DDA/2020-21/5155 dt 18/03/21

Sr.	Minimum Standards on Fire	As Per	Provided at Site	Remarks			
No.	Prevention and Fire Safety U/R33	Directive		MR/NMR			
		Requirement					
01	Access to Building.						
	Road width	09 mtr.	24 mtr.	MR			
	 Gate width 	06 mtr	06 mtr	N/A			
	 Width of internal road 	N/A	N/A	N/A			
02	Number, Width, Type and Arrangement of Exits.						
	a. Number of Staircases						
	 Upper Floor 	02 nos.	02 nos.	MR			
	 Basement 	N/A	N/A	N/A			
	B. Width of Staircases		v = 18				
	 Upper Floor 	02 mtr	02 mtr each	MR			
	 Basement 	N/A	N/A	N/A			
	c. Protection of exits						
	Fire check door	Required	Provided	MR			
	 Pressurization 	N/A	N/A	N/A			
	d. No. of continuous staircases to terrace	02 no.	02 no.	MR			
	e. Width of Corridor	N/A	N/A	N/A			
	f. Door Size	02 mtr.	02 mtr.each	MR			
03	Compartmentation.						
	Fire check door	Required	Provided	MR			
	 Sealing of electrical shafts 	Required	Concealed type	MR			
	 Fire rating of shaft door 	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
04	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	Upper floor	Required	Ventilated	MR			
05.	Fire Extinguishers.						
	Total numbers	16 nos.	16 nos.	MR			
	• types	ABC /CO ₂	ABC /CO ₂	MR			
	IS marking	ISI marked	ISI marked	MR			

06	First-Aid-Hose Reels.						
	Total numbers on each floor	02 No.	02 No.	MR			
	 Length of hose reel hose 	30 mtr.	30 mtr.	MR			
	 Nozzle diameter 	05 mm	05 mm	MR			
07	Automatic Fire Detection and Alarming System.						
	Type of detectors	Heat/Smoke	Provided	MR			
	 Location of main panel 	Near staircase	Provided	MR			
	Location of repeater panel	Required	Provided	MR			
	Alternate source of power	Required	Provided	MR			
	Hooter's location	Staircase	Provided	MR			
80	MOEFA	Required	Provided	MR			
)9	Public Address System.	N/A	Provided	MR			
10	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	upper floor	N/A	N/A	N/A			
	sprinkler above false ceiling	N/A	N/A	N/A			
1	Internal Hydrants	14//-1	IN/A	11//-1			
	size of riser/down-comer	100 mm	100 mm	MR			
	 Number of hydrants per floor 	02 No.	02 No.	MR			
	Hose Box per floor	02 No.	02 No.	MR			
2	Yard Hydrants.	02.13	02 110.	IVIIX			
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
3	Pumping Arrangements.			14//			
	Ground Level						
	Discharge of main Pump	2280 Lpm.	2280 Lpm.	MR			
	> Head of Main Pump	60 M	60 M	MR			
	> Number of main pumps	01 No.	01 No.	MR			
	> Jockey pump out put	180 Lpm.	180 Lpm.	MR			
	Jockey pump head	60 M	60 M	MR			
	Standby pump out put	2280 Lpm.	2280 Lpm.	MR			
7.5	> Standby pump Head	60 M	60 M	N/A			
	> Auto Starting /Manual stopping	Required	Provided	MR			
	> Pump House Access	Required	Provided	MR			
	Terrace Level	required	riovided	IVIE			
	Discharge of pump	450 Lpm.	450 Lpm.	MR			
	Head of the Pump	60 M	60 M	MR			
	Power supply	Required	Provided	MR			
	Auto Starting of pump	Required	Provided	MR			
4	Captive Water Storage for Fire Fighting.	. toganou	TTOVIGOG	IVII C			
	Underground tank capacity	50,000 Ltr.	75,000 Ltr.	MR			
	Draw-off connection	Required	Provided	MR			
	Fire service inlet	Required	Provided	MR			
	Access to tank	Required	Provided	MR			
	 Overhead Tank capacity 	5,000 Ltr.	10,000 Ltr.	MR			
5	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	 Pressurization of Lift lobby 	N/A	N/A	N/A			
	Communication in lift car	Required	Provided	MR			
	 Firemen's grounding switch 	Required	Provided	MR			
	Lift Signage	Required	Provided	MR			

ALL S

17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	Total area	N/A	N/A	N/A		
	Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector system panel	N/A	N/A	N/A		
	Flow switch panel	N/A	N/A	N/A		
	PA system panel	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, it is recommended to issue Fire Safety Certificate.

Signature of the Inspecting Officer

Name

- Mehmood

Designation

- A.D.O (TP)

Dy.CFO(NDZ)