c15

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2021/SZ/ 47 5

Dated: 2 / 7 / 2021

FIRE SAFETY CERTIFICATE

Certified that the S.D.M.C Primary Boys School, located at Katwaria Sarai, New Delhi-110016 comprised of ground plus One upper floor was already issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/2018/SZ/1529 Dt. 02/07/2018. The said premises was re-inspected by officer concerned of this department on 03/07/2021 in presence of Mrs. Anita Kumari (Principal) of the school and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with DOE Circular dated 01/03/2011 and that the building is fit for occupancy class "Educational Building Group – B" with effect from 13/7 / 2021 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules 2010.

Issued on 3 / 2021 at New Delhi by

(Sunil Chawdhary) Dy. Chief Fire Officer (SZ) Delhi Fire Service

Copy to: -

- 1. The Principal, S.D.M.C Primary Boys School, located at Katwaria Sarai, New Delhi- 110016
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi- 110054.

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

1	INSPEC	INSPECTION REPORT						
1	Name & Address of the Building	S.D.M.C Prima	ary Boys School Katara	io Core: 37				
2	T CO	S.D.M.C Primary Boys School, Katwaria Sarai, New Delhi- 110016, (HD 1959066)						
3	- JP or Occupancy	Educational, G	roup-B (School)					
4	Building Comprised of	Ground plus or	Educational, Group-B (School) Ground plus one upper floor					
5	Type of Case	Renewal	to apper moor					
6	Details of Previous NOC		hool/2018/SZ/1529 Dt. 0	2/07/2010				
7	Fire Safety Directives Letter No	F.16//Estate/CC/Fi	re Safety/2011/3298 to 3398 da	2/07/2018				
8	Date of Inspection	03-07-2021	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	ned 01.03.2011				
9	Name of the Inspecting Officers	Sh. Rajesh Kun	Sh. Rajesh Kumar ADO (BCP)					
	Name & Designation of Officers	Mrs. Anita Kumari (Principal)						
10	from the building side Year of construction		(morpar)					
11		2007						
S. No	Applicant letter No.	Gmail Dated 30	/06/2021					
D. 146	Standards of Fire Prevention	Old NOC	Provided at Site	I D				
1	and Fire Safety U/R 33	Requirement	Trovided at Site	Remarks				
	Access to Building.		- Jacobson	MR/NMR				
	Road width	Required	06 m	MR				
	Gate width	NA	4.5 mtr					
2	Width of internal road	-NA-	-NA-	NA				
4	Number, width, type & arrangement of exits.		11/14	-NA-				
	a) Number of Staircase							
	> Upper floors.	02 Nos	02 Nos	T				
	Basement floor.	-NA-	-NA-	MR				
	b) Width of Staircase		14/4-	-NA-				
	> Upper floors	1.5 m / 0.75 m	1.70 m & 1.63 m	T				
	Basement floor	-NA-	-NA-	MR				
	c) Protection of exits		-IVA-	-NA-				
	Fire check door	-NA-	-NA-					
	Pressurization	-NA-	1	-NA-				
	d) No. of continuous staircase to terrace	-	-NA-	-NA-				
	e) Width of corridor	Required -NA-	Two	MR				
	f) Door size		-NA-	-NA-				
3	Compartmentation.	1 mtr	1 mtr	MR				
	Fire check door.	2						
	Sealing of electrical shafts.	-NA-	-NA-	-NA-				
	• Fire rating of shaft door.	-NA-	-NA-	-NA-				
	Water curtain	-NA-	-NA-	-NA-				
	Fire dampers.	-NA-	-NA-	-NA-				
4.	Smoke Management system.	-NA-	-NA-	-NA-				
	Basement							
	Upper floors	-NA-	-NA-	-NA-				
5.	Fire Extinguishers.	-NA-	-NA-	-NA-				
	Total numbers			1111				
	I Utal Hillingers	Required	06 Nos	MR				
			7 2 1 0 0					
	• Types	ABC						
		ABC	ABC & Co2 Type	MR				
6.	TypesISI Marking							
6.	 Types ISI Marking First Aid Hose Reels.	ABC	ABC & Co2 Type	MR				
6.	 Types ISI Marking First Aid Hose Reels. Total numbers on each floor. 	ABC	ABC & Co2 Type Provided	MR MR				
6.	 Types ISI Marking First Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. 	ABC ISI mark	ABC & Co2 Type Provided -NA-	MR MR -NA-				
	 Types ISI Marking First Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter 	ABC ISI mark -NANA-	ABC & Co2 Type Provided -NANA-	MR MR -NANA-				
	 Types ISI Marking First Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. 	ABC ISI mark -NA-	ABC & Co2 Type Provided -NA-	MR MR -NA-				

	 Location of Main Panel 	-NA-	-NA-	-NA-
	 Location of Repeater Panel 	-NA-	-NA-	-NA-
	 Alternate source of power 	-NA-	-NA-	-NA-
	Hooter's location	-NA-	-NA-	-NA-
8.	MOEFA	-NA-	-NA-	-NA-
9.	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System			
	Basement	-NA-	-NA-	-NA-
	 Upper floors 	-NA-	-NA-	-NA-
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA-
11.	Internal Hydrants.			
	 Size of Riser/Down-comer 	-NA-	-NA-	-NA-
	 Number of Hydrant per floor 	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
12.	Yard Hydrants.			
	 Total number of hydrants. 	-NA-	-NA-	-NA-
****	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.			1471
	Ground Level			
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level		T	1 12 1
	Discharge of pump.	-NA-	-NA-	-NA-
	Head of pump.	-NA-	-NA-	-NA-
	Power supply.	-NA-	-NA-	-NA-
	Auto starting of pump.	-NA-	-NA-	-NA-
14.	Captive water storage for fire fighting.	. 12.2	1.47.8	TNA
	Underground tank capacity.	-NA-	-NA-	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	 Overhead tank capacity. 	-NA-	-NA-	-NA-
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			17117
	 Pressurization of lift shaft. 	-NA-	-NA-	-NA-
	 Pressurization of lift lobby. 	-NA-	-NA-	-NA-
	 Communication in lift car. 	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
17.	Standby Power Supply	-NA-	-NA-	-NA-
18.	Refuge Area		7.17.7	-14\Z-
	Total area	-NA-	-NA-	-NA-
	Location	-NA-		
19.	Fire Control Room.	-11/1-	-NA-	-NA-
		NT A	***	
	 Detector system panel. 	-NA-	-NA-	-NA-
	 Flow switch panel. 	-NA-	The state of the s	

PA system panel.	-NA-	-NA-	-NA-
Battery backup.	-NA-	-NA-	-NA-
Building floor plan.	-NA-	-NA-	-NA-
20. Special Fire Protection System for the Protection of special Risk, if any.	-NA-	-NA-	-NA-

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the DOE Circular, FSC issued vide letter no F6/DFS/MS/School/2018/SZ/1529 Dt. 02/07/2018, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer
Name: Sh. Rajesh Kumar

Design: ADO (BCP)

7. plense oved, F.T. tettel in putip metare II M.S.