5-26

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2021/ 135

Dated: 1.5...../2021

FIRE SAFETY CERTIFICATE

Certified that the M/s Lord of the Drinks (A Unit of RSVK Restaurant Pvt. Ltd.) located at G-72, 1st floor, Connaught Place, New Delhi comprises of Ground + Mezzanine + 01 Upper floor, Restaurant is running at 1st floor owned/ occupied by M/s Lord of the Drinks **FSC** earlier granted by this department No.F6/DFS/MS/EH/2018/NDZ/1681 dated 18/07/18. The premises was re-inspected by the officer concerned of this department on 09/07/21 in the presence of Mr. Yogesh Mehata and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D, Restaurant running at 1st unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 177721--at New Delhi by.

(**Dr. S.K Tomar**)

Dy. Chief Fire officer

Pelhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
 Online Id no. 2021062414184 dated 24/06/2021
- 2. The Executive Engineer, NDMC, Palika Kendra, New Delhi.
- 3. The Manager,
 M/s Lord of the Drinks (A Unit of RSVK Restaurant Pvt. Ltd.) at G-72, 1st floor,
 Connaught Place, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INICPE	CTION	REPORT
TIANT	CITOIN	KLIUKI

1. Name & address of the building M/s Lord of the Drinks (A Unit of RSVK

Restaurant Pvt. Ltd.) at G-72, 1st floor,

Connaught Place, New Delhi

2. Type of occupancy:-Assembly Building Group-D

Gr. + Mezz. + 01 upper floors, Restaurant is running at

1st floor

3. Type of case:-Renewal

4. Details of previous FSC:-F6/DFS/MS/EH/2018/NDZ/1681 dated

18/07/18.

5. Fire safety directives No.-

N/A

6. Date of inspection:-09/07/21

7. Name of the inspecting officer:-Sh. Ravinder Singh (ADO/CC) Sh. Rajinder Atwal DO (CD)

8. Name & designation of officer from the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Mr. Yogesh Mehata Old Heritage Bldg.

2021062414184 dated 24/06/2021

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			
	1) Road width	09 mtr.	20 mtr.	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arr			
	A. Number of staircases			
	1. Upper floors	02 No.	02 No.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	0.80 & 1.25 mtr.	1.27 & 1 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits	N/A	N/A	N/A
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	N/A	N/A	N/A
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	2 mtr.	2.30 mtr.	N/A
•	Compartmentation			
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
•	Smoke Management System			
	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 ACPH	Natural	MR
	Fire Extinguishers		,	
	1) Total numbers	08 Nos.	12 Nos.	MR



.1	
N/21	

	2) Types	ABC	& CO2	AE	3C & CO2	M	R	
	3) ISI marking	Requ	iired	Pro	ovided	M	R	
				1				
i.	First-Aid Hose Reel							
	1) Total number of eachfloor	01		01		M		
	2) Length of hose reel hose	30 m	ntr.	-	mtr.	M		
	3) Nozzle diameter	05 m	nm	05	mm	M	R	
7.	Automatic Fire Detection &	Alarn	ning Syste					
	1) Type of detectors	N/A		N/A		-	N/A	
	2) Location of main panel	N/A		N/			/A	
	3) Location of repeater panel	N/A		N/A			N/A	
	4) Alternate source of power	N/A		N/			/A	
	5) Hooter's Location	N/A		N/	'A	N	/A	
3.	MOEFA	Requ	uired	Pr	ovided	M	IR	
).	Public Address System	N/A		N/	/A	N	/A	
10.	Automatic Sprinkler System	1	2					
. 00	1) Basement	N/A		N	/A	N	/A	
	2) Upper floors	N/A		N		N	/A	
	3) Sprinkler above false	N/A		N		N	/A	
	ceiling		The Control of the Co					
11.	Internal Hydrants							
11.	1) Size of riser/down-comer	100	mm	10	00 mm	N	1R	
	2) Number of hydrants per	01		01	l	N	1R	
	floor							
	3) Hose box	01		01	1	N	1R	
12.	Yard Hydrants				9/1			
124.	1) Total number of hydrants	N/A		N/A		N	I/A	
	2) Hose box	N/A		N	/A	N	I/A	
13	Pumning Arrangement			_	Tax Magazine			
13.	Pumping Arrangement 1) Ground level				275.54			
13.	1) Ground level		N/A		N/A	+	N/A	
13.	Ground level Discharge of main		N/A		N/A	•	N/A	
13.	Ground level Discharge of main pump				N/A N/A		N/A N/A	
13.	Ground level Discharge of main pump Head of main pump	p	N/A					
13.	Ground level a) Discharge of main pump b) Head of main pump c) Number of main pu	p ump	N/A N/A		N/A	1	N/A	
13.	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out p	p ump out	N/A N/A N/A		N/A N/A	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	N/A N/A	
13.	Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head	p ump out	N/A N/A N/A N/A		N/A N/A N/A		N/A N/A N/A	
13.	The standard of the stand	p ump out	N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A	1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	N/A N/A N/A N/A	
13.	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head f) Stand by pump out g) Stand by pump head	p ump out put	N/A N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A	
13.	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head f) Stand by pump out g) Stand by pump head h) Auto starting/Manu	p ump out put	N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A N/A	
13.	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head f) Stand by pump out g) Stand by pump head h) Auto starting/Manustopping	p ump out put	N/A N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A N/A	1 1 2	N/A N/A N/A N/A N/A N/A	
13.	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head f) Stand by pump out g) Stand by pump head h) Auto starting/Manustopping 2) Terrace level	pumput ad ual	N/A N/A N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A N/A	
13.	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head f) Stand by pump out g) Stand by pump head h) Auto starting/Manustopping 2) Terrace level a) Discharge of pump	pumput ad ual	N/A N/A N/A N/A N/A N/A N/A 450 LPM		N/A N/A N/A N/A N/A N/A N/A 450 LPM	1 1 2 2	N/A N/A N/A N/A N/A N/A N/A	
13.	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head f) Stand by pump out g) Stand by pump head h) Auto starting/Manustopping 2) Terrace level a) Discharge of pump b) Head of pump	pumput ad ual	N/A N/A N/A N/A N/A N/A N/A 450 LPM 40 mtr.		N/A N/A N/A N/A N/A N/A N/A N/A N/A A N/A N/		N/A N/A N/A N/A N/A N/A N/A N/A M/A M/A MR	
13.	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head f) Stand by pump out g) Stand by pump head h) Auto starting/Manustopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	pumput ad ual	N/A		N/A		N/A N/A N/A N/A N/A N/A N/A N/A M/A M/A MR MR	
	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head f) Stand by pump out g) Stand by pump head h) Auto starting/Manustopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pu	pumput ad ual	N/A N/A N/A N/A N/A N/A N/A N/A N/A A A A		N/A N/A N/A N/A N/A N/A N/A N/A N/A A N/A N/		N/A N/A N/A N/A N/A N/A N/A N/A M/A M/A MR	
13.	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head f) Stand by pump out g) Stand by pump head h) Auto starting/Manustopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for	put ad ual or Fir	N/A N/A N/A N/A N/A N/A N/A N/A A N/A A N/A A Required Required Required		N/A N/A N/A N/A N/A N/A N/A N/A N/A Provided Provided		N/A N/A N/A N/A N/A N/A N/A N/A MR MR MR MR	
	1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out pump e) Jockey pump head f) Stand by pump out g) Stand by pump head h) Auto starting/Manustopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pu	put ad ual or Fir	N/A N/A N/A N/A N/A N/A N/A N/A N/A A A A		N/A		N/A N/A N/A N/A N/A N/A N/A N/A M/A M/A MR MR	



	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	10,000 ltr.	10,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syster Risk, if any: ABC & Co2	em for Protect	tion of special	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2018/NDZ/1681 dated 18/07/21 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the inspecting officer

Name: - Rajinder Atwal

Designation: - DO (CD)

(1. 1. 101.

Docco) (1377

1317121

Signature of the Inspecting Officer

Name: Ravinder Singh

Designation: ADO (CC)

तरित हो तो कृपया लौटाएँ :