GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/School/2021/NDZ/ 487

Dated: 1577/21

FIRE SAFETY CERTIFICATE

Issued on at New Delhi by

(Dr. S. K. Tomar) Dy. Chief Fire Officer

He De

To.

The Principal, Lovely Public English School, A-Block, Yojna Vihar, Delhi-110092

Copy:-

The Dy. Director of Education, D-Block, Anand Vihar, Delhi

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry

	INS	PECTION REP	ORT				
1.	Name & address of the building		olic English School, A-B	lock.			
	Yojna Vihar, Delhi-110092						
2.	Building is comprised of		is two upper floors				
	3. Type of Occupancy : Educational						
4. Type of Case : Renewal							
5.			[S/School/2018/NDZ/15	dt_ 01/01/18			
6.	Fire Safety direction letter No		c/CC/Fire Safety/2011/32	290 10 3390			
		dated- 01/03/2011 : 06/07/2021 : ADO Nagender Singh					
7.							
8.		: ADO Nage	ender Singn				
9.	0						
	from the building side		Arora, Receptionist				
	O. Year of Construction	: 1996	0 11 1.100	106/2021			
	1. Applicant's Email ID		nar@gmail.com dated 22				
Sr.	Minimum Standards on fire	Circular	Provided at Site	Remarks			
No	prevention and fire safety U/R33	Requirement		MR/NMR			
01	Access to building.						
	Road width	06 m	06 m	MR			
	Gate width	N/A	N/A	N/A			
	Width of internal road	N/A	N/A	N/A			
02	Number, Width, Type and Arrangem	nent of Exits.					
	a. Number of Staircases	I	T				
	Upper Floor	01 no.	02 nos.	MR			
37	Basement	N/A	N/A.	N/A			
	B. Width of Staircases	-					
	Upper Floor	1.5 m	1.5 m & 1.3 m	MR			
	Basement	N/A	N/A	N/A			
	c. Protection of exits						
	Fire check door	N/A	N/A	N/A			
	 Pressurization 	N/A	N/A	N/A			
		02 nos.	02 nos.	MR			
	d. No. of continuous staircases						
	to terrace e. Width of Corridor	1.5 m	1.5 m	MR			
	f. Door Size	01 m	01 m	MR			
03	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	N/A	N/A			
	• Fire rating of shaft door	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	• Fire Dampers	N/A	N/A	N/A			
04	Smoke Management System.						
v 3			27/4	N/A			
	Basement	N/A	N/A	IN/A			
	Basement Upper floor	N/A N/A	N/A N/A	N/A			
05.	BasementUpper floorFire Extinguishers.	N/A N/A					
05.	Upper floor Fire Extinguishers.	N/A	N/A	N/A			
05.	• Upper floor Fire Extinguishers.						

06	First-aid-Hose Reels.							
	Total numbers on each floor	01 no.	01 no.	MR				
	Length of hose reel hose	30 m	30 m	MR				
	Nozzle diameter	05 mm	05 mm	MR				
07	Automatic fire detection and alarming system.							
	• Type of detectors	N/A	N/A	N/A				
	Type of detectorsLocation of main panel	N/A	N/A	N/A				
		N/A	N/A	N/A				
	Location of repeater panel	N/A	N/A	N/A				
	Alternate source of powerHooter's location	Value of the second sec	A STATE OF THE PARTY OF THE PAR	F				
		N/A	N/A	N/A				
08	MOEFA	N/A	N/A	N/A N/A				
09	Public address System.	N/A	N/A	IN/A				
10	Automatic Sprinkler System.							
	• Basement	N/A	N/A	N/A				
	upper floor	N/A	N/A	N/A				
	sprinkler above false ceiling	N/A	N/A	N/A				
11	Internal Hydrants							
	size of riser/down-comer	N/A	100 m	MR				
1 2 3 3 3	Number of hydrants per floor	. N/A	01 no.	MR				
	Hose Box	N/A	01 no.	MR				
12	Yard Hydrants.							
	Total number of hydrants	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
13	Pumping Arrangements.	11/12	N. A.					
	C 11 -1	N/A	N/A	N/A				
	Ground Level Discharge freein Property	N/A	N/A	N/A				
	Discharge of main Pump Head of Main Pump	N/A N/A	N/A N/A	N/A				
		N/A N/A	N/A N/A	N/A				
	Number of main pumpsJockey pump out put	N/A	N/A	N/A				
	> Jockey pump head	N/A	N/A	N/A				
	> Standby pump out put	N/A	N/A	N/A				
	> Standby pump Head	N/A	N/A	N/A				
	> Auto Starting /Manual stopping	N/A	N/A	N/A				
	> Pump House Access	. N/A	N/A	N/A				
	Terrace Level							
	Discharge of pump	450 LPM	450 LPM	MR				
	> Head of the Pump	40 m	40 m	MR				
	> Power supply	Required	Provided	MR				
	> Auto Starting of pump	Required	Provided	MR				
14	Captive Water Storage for Fire Fighting.							
	Underground tank capacity	N/A	N/A	N/A				
	> Draw-off connection	N/A	N/A	N/A				
	> Fire service inlet	N/A	N/A	N/A				
	> Access to tank	N/A	N/A	N/A				
	Overhead Tank capacity	10,000 Ltrs.	10,000 Ltrs.	MR				
15	Exit Signage.	Required	Provided	MR				
16	Provision of Lifts.							
	Pressurization of Lift Shaft	N/A	N/A	N/A				
	Pressurization of Lift lobby	· N/A	N/A	N/A				
	Communication in lift car	N/A	N/A	N/A				
	Firemen's grounding switch	N/A	N/A	N/A				
	Lift Signage	N/A	N/A	N/A				

17	Standby power supply	N/A	Provided	MR
18	Refuge Area.		2207400	IVIIC
	Total area	N/A	N/A	N/A
19	• Location Fire Control Room	N/A	N/A	N/A
	Detector system panel	N/A	N/A	N/A
	Detector system panel	N/A	N/A	NI/A
1	• Flow switch panel	N/A	N/A	N/A
	111 System paner	N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
20	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were Tested/Checked and found functional, at the time of inspection.

Keeping in view of the compliance of the minimum standards of fire prevention and fire safety measures required as per circular F. 16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011, it is recommended to renew Fire Safety Certificate under rule 37 of Delhi Fire Service Rules, 2010.

Dy. CFO (NDZ)

FT letter is placed for signatures please

ND2)

Xour

1313

MSCell