cur

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2021/ 137

Dated:1.5.7....../2021

FIRE SAFETY CERTIFICATE

Certified that the M/s Pindi Restaurant located at Shop No. 16, Pandara Road Market, New Delhi comprises of Ground + 01 Upper floor, Restaurant is running at this department vide granted FSC by floor only was No.F6/DFS/MS/EH/NDZ/2018/1141 dated 18/05/18. The premises was re-inspected by the officer concerned of this department on 08/07/21 in the presence of Mr. Yeshpal Wadhwa and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D, Restaurant at Ground floor only with effect from 15/7/21 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 1577/21 at New Delhi by.

(**Dr.S.K.Tomar**)
Dy. Chief Fire officer
Delhi Fire Service

0210mm

Copy to:-

- 1. The Jt Commissioner of police, Is Floor, Defence colony, New Delhi online id. 2021060713674 dated. 07.06.2021
- 2. The Medical Officer of Health, Health Department, Palika Kendra, New Delhi.
- 3. The Manager,

M/s Pindi Restaurant at Shop No. 16, Pandara Road Market, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT M/S Pindi Restaurant at Shop No. 16, 1. Name & address of the building Pandara Road Market, New Delhi. Assembly Building Group-D 2. Type of occupancy:-Gr. + 01 upper floors, Restaurant is running at Ground floor only Renewal 3. Type of case:-F6/DFS/MS/EH/NDZ/2018/1141 dated 4. Details of previous FSC:-18/05/18 N/A 5. Fire safety directives No.-07/07/21 6. Date of inspection:-Sh. Ravinder Singh (ADO/CC) 7. Name of the inspecting officer:-8. Name & designation of officer from the building side:-Mr. Yeshpal Wadhwa Old Heritage Bldg. 9. Year of construction:-10. Applicant's letter No:online id no.2021060713674 dated. 07.06.2021 Requirement/ Provided at site Remarks Minimum Standards on fire S.No. Existing fire safety MR/NMR Prevention and fire safety arrangements U/R 33 **Access to Building** 1. MR 06 mtr. 1) Road width 06 mtr N/A N/A N/A 2) Gate width N/A N/A N/A 3) Width of internal road Number, Width Type & Arrangement of Exits 2. A. Number of staircases N/A N/A N/A 1. Upper floors N/A N/A N/A 2. Basements B. Width of staircase N/A N/A N/A 1. Upper floors N/A N/A 2. Basements N/A N/A N/A N/A C. Protection of exits N/A N/A N/A 1. Fire check door N/A N/A N/A 2. Pressurization N/A N/A N/A D. No. of continuous staircase to terrace N/A N/A N/A E. Width of corridor 1.30 & 1.10 MR 1.30 & 1.10 F. Door size mtr. mtr. Compartmentation 3. N/A N/A 1) Fire check door N/A N/A N/A N/A 2) Sealing of electrical shafts N/A N/A N/A 3) Fire rating of shaft door N/A N/A N/A 4) Water curtain N/A N/A N/A 5) Fire Dampers Smoke Management System 4. N/A N/A 30 ACPH 1) Basements MR Exhaust fan 12 ACPH 2) Ground floors Fire Extinguishers 5. MR 06 Nos. 05 Nos. 1) Total numbers

ABC & CO2

Provided

ABC & CO2

Required

MR

MR



2) Types

3) ISI marking

6.	First-Aid Hose Reel	01	01	MR		
	1) Total number of eachfloor		30 mtr.	MR		
	2) Length of hose reel hose	30 mtr.	05 mm	MR		
	3) Nozzle diameter	05 mm		1711		
7.	Automatic Fire Detection &	Alarming Sys	N/A	N/A		
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A		N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A			
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	N/A	N/A	N/A		
10.	Automatic Sprinkler System			77/4		
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling					
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor					
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants					
12.	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
	1) Ground level		*			
	a) Discharge of main	N/A	N/A	N/A		
	pump		q ε" μ = 1	× 4		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main	N/A	N/A	N/A		
	pump		. 1	. a		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump	N/A	N/A	N/A		
	output					
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual		N/A	N/A		
	stopping					
	2) Terrace level					
	a) Discharge of pump	450 LPM	450 LPM	MR		
	b) Head of pump	30 mtr.	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
14	d) Auto starting of	Required	Provided	MR		
		Teoquitou				
	Captive Water Storage for Fire Fighting					
4.4	Camting Water Stanger for					
14.			N/A	N/A		
14.	1) Under ground tank capacity	N/A	N/A	N/A		

M13

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			-
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/NDZ/2018/1141 dated 18/05/18, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

Durces

13/7 Dycho Carozi F. (1. p).

ABOCCE)