GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No.F6/DFS/MS/School/NDZ/2021/ 502

Dated:- / 6 /07/2021

FIRE SAFETY CERTIFICATE

(Dr. S.K. Tomar) Dy. Chief Fire Officer Delhi Fire Service

0x 10 mm

Ole

Copy to:-

1. The Dy. Director of Education, D-Block, Anand Vihar, Delhi-91.

2. The Principal, Yog Bharti Public School, C-block, New Ashok Nagar, Delhi-96.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSP	ECTION REPO	RT						
1.	Name & address of the building		Public School, C-l	olock, New					
			ar, Delhi-96.						
2.	Type of occupancy:- Educational Group								
	Gr.+03 Upper Floor								
3.	Type of case:- Renewal								
4.	Details of previous NOC:- F6/DFS/MS/School/2018/NDZ/368 dated								
		06/03/2018							
	Fire safety directives No								
	Date of inspection:-	10/07/2021							
	Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/LN)								
8.	Name & designation of officer								
	From the building side:-	Mr. Umesh	(Owner)						
	Year of construction:-	1997							
	Applicant's letter No:-	email dated							
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks					
	Prevention and fire safety	Circular		MR/NMR					
1	U/R 33								
1.	Access to Building								
	1) Road width	06 mtr.	06 mtr.	MR					
	2) Gate width	NA	NA	NA					
	3)Width of internal road	NA	NA	NA					
2.	Number, Width Type & Arrangement of Exits								
	A. Number of staircases		2						
	1. Upper floors	02 nos.	02 nos.	MR					
	2. Basements	N/A	N/A	N/A					
	B. Width of staircase			1 1/1 1					
	1. Upper floors	1.5 mtr	1.10M & .90 M	MR					
	2. Basements	N/A	N/A	N/A					
	C. Protection of exits	1372		1071					
	1. Fire check door	N/A	N/A	N/A					
	2. Pressurization	N/A	N/A	N/A					
	D. No. of continuous	01 nos.	02 nos.	MR					
	staircase to terrace		oz nos.	TVIIC					
	E. Width of corridor	1.5 mtr	1.45 M & 1.5 M	MR					
	F. Door size	1.0 mtr.	1.0 mtr.	MR					
3.	Compartmentation		1						
ACCESSES NO.	1) Fire check door	N/A	N/A	N/A					
	2) Sealing of electrical shafts	Required	Sealed	MR					
	3) Fire rating of shaft door	N/A	N/A	N/A					
	4) Water curtain	N/A	N/A	N/A					
	5) Fire Dampers	N/A	N/A	N/A					
4.	Smoke Management System								
	1) Basements	N/A	N/A	N/A					
	2) Upper floors	N/A	N/A	N/A					
5.	Fire Extinguishers	1 1/1 1	IVA	14/7					
٥.	1) Total numbers	08 Nos.	10 Nos.	MR					
	2) Types	ABC & CO2	ABC, CO2	MR					
	3) ISI marking	Required	Provided	MR					
	TO THE THIRD AND THE PARTY OF T	I INCUMINEU		IVIN					

6.	First-Aid Hose Reel			tt.			0.	
	1)Total number of each 1 no.				1 no.		MR	
	floor		T IIO.		1 110.		IVIIV	
	2) Length of hose reel hose	30	30 M		30 M		MR	
	3) Nozzle diameter	3) Nozzle diameter 5 m		nm 5mm		MR		
7.	Automatic Fire Detection & Alarming System							
	1) Type of detectors		N/A		N/A		N/A	
			N/A		N/A		N/A	
	3) Location of repeater panel	N/	A		N/A		N/A	
	4) Alternate source of power	N/	A		N/A		N/A	
	5) Hooter's Location	N/	A	N/A		N/A		
8.	MOEFA		Required Provided		Provided	MR		
9.	Public Address System	N/	A	N/A		N/A		
10.	Automatic Sprinkler System							
	1) Basement N/A			N/A		N/A		
	2) Upper floors	N/		N/A		N/A		
	3) Sprinkler above false	N/A		N/A		7	N/A	
1.1	ceiling							
11.	Internal Hydrants		10010					
	1) Size of riser/down-comer	-	0 MM	_	100 MM		MR	
	2) Number of hydrants per floor	1 No.			1 No.		MR	
		127					2	
12.	3) Hose box 1 No.		NO.	1 No.		MR		
12.	Yard Hydrants		1 -	7/1				
	1) Total number of hydrants 2) Hose box	N/A N/A		N/A		N/A		
13.		N/2	4		V/A]	N/A	
13.	Pumping Arrangement	_	> T/A					
	1) Ground level		N/A		N/A		N/A	
	a) Discharge of main pump	p	N/A		N/A		N/A	
	b) Head of main pump		N/A		N/A	1	N/A	
	c) Number of main pump	1	N/A	A ===	N/A		N/A	
	d) Jockey pump out put e) Jockey pump head		N/A		N/A		N/A	
	f) Stand by pump output	-	N/A		N/A		N/A	
	g) Stand by pump output		N/A		N/A	,	N/A	
		2	N/A		N/A		N/A	
	II) Auto starting/Manual etoppin	no l	NI/A		TAT/A		N/A	
	h) Auto starting/Manual stoppin 2) Terrace level	ng	N/A		N/A			
	2) Terrace level	ng					M	
	Terrace level Discharge of pump		450 LPM		450 LPM		MR	
	2) Terrace level a) Discharge of pump b) Head of pump		450 LPM 40 M		450 LPM 40 M		MR	
	2) Terrace levela) Discharge of pumpb) Head of pumpc) Power supply		450 LPM 40 M Required		450 LPM 40 M Provided		MR MR	
14.	2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump		450 LPM 40 M Required Required		450 LPM 40 M		MR	
14.	2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire	Figh	450 LPM 40 M Required Required ting		450 LPM 40 M Provided Provided		MR MR MR	
14.	2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire 1) Under ground tank capacity	Figh	450 LPM 40 M Required Required ting		450 LPM 40 M Provided Provided		MR MR MR	
14.	2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire 1) Under ground tank capacity a) Draw-off connection	Figh	450 LPM 40 M Required Required ting J/A		450 LPM 40 M Provided Provided N/A N/A		MR MR MR N/A	
14.	2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire 1) Under ground tank capacity a) Draw-off connection b) Fire service inlet	Figh	450 LPM 40 M Required Required ting J/A J/A		450 LPM 40 M Provided Provided N/A N/A N/A		MR MR MR N/A N/A N/A	
14.	2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire 1) Under ground tank capacity a) Draw-off connection	Figh	450 LPM 40 M Required Required ting J/A		450 LPM 40 M Provided Provided N/A N/A		MR MR MR N/A	

mul

36, 37, 38, 39,

सैक्टर-1, नीएडा 101 3

16.	Provision of Lifts.			1
10.	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System f	For Protection of spec	cial Risk, if any:	N/A

The fire protection system provided in the school building were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/School/2018/NDZ/368 dated 06/03/2018, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- M.K. Sharma Designation: - ADO (LN)

Dy.CFO/NDZ

1. Pl. Check noting > DFA before rijnature

P.T. little is put upf ist. M