GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/School/2021/ 529

Dated: 26/7/2/

FIRE SAFETY CERTIFICATE

Certified that the Adarsh Lakhpat Model Sec School located at E-25, Khajoori Khas, Dayal Pur Road. Delhi 110094, comprised of ground plus three upper floors (two separate blocks), owned/occupied by Adarsh Lakhpat Model Sec School was issued FSC vide letter No. F6/DFD/MS/School/2018/NDZ/1165 dated 22/05/18. The school building was re-inspected by the officer concerned of this department in the presence of Mr. Bhagwan Singh, Admin of the school and found that the school building have complied with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and observed that the school building is fit for ground plus three upper floors occupancy class "B" 'Educational Building' with effect from 2.6.17.12..... for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Issued on at New Delhi by

(Dr. S. K. Tomar) Dy. Chief Fire Officer

To,

The Principal Adarsh Lakhpat Model Sec School E-25, Khajoori Khas, Dayal Pur Road Delhi 110094

Copy:-

The Dy. Director of Education, B-Block, Yamuna Vihar, Delhi-110053

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form `J` [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

: Adarsh Lakhpat Model Sec School 1. Name & address of the building

E-25, Khajoori Khas, Dyal Pur Rd. Delhi 95

2. Building is comprised of

: G+3 (Two Separate blocks) : Educational 3. Type of Occupancy

: Renewal 4. Type of Case

: F6/DFD/MS/School/2018/NDZ/1165 dt 22/05/18 5. Details of Previous FSC letter : NBC Part IV

6. Fire Safety directive letter No

: 05/07/2021 7. Date of Inspection

: ADO Mehmood 8. Name of the Inspecting officers

9. Name and designation of Officer

: Mr. Bhagwan Singh, Admin from the building side : 1999, 2006 & 2017

10. Year of Construction

: Nil, dated 25/06/2021 11. Applicant's letter No

	Minimum Standards on fire	NBC Part-IV	Provided at Site	Remarks MR/NMR		
Sr. No.	prevention and fire safety U/R33	Requirement				
01	Access to building.		MR			
01		06 mtr.	24 mtr.	N/A		
1	Road width	N/A	N/A	N/A		
	Gate width	N/A	N/A	14//		
	Width of internal road Number, Width, Type and Arrange	ement of Exits.				
02	Number, Width, Type and Arrange					
	a. Number of Staircases		02 no. (each block)	MR		
	Upper Floor	02 no.	N/A	N/A		
	Basement	N/A				
-	B. Width of Staircases • Upper Floor	1.50 mtr	Block A=1.25 mtr & 0.80 mtr Block B-1.50 mtr & 0.80	MR		
		N1/A	N/A	N/A		
	 Basement 	N/A				
	c Protection of exits	D1/A	N/A	N/A		
	 Fire check door 	N/A	N/A	N/A		
	Pressurization	N/A	01 no. each block	MR		
	d. No. of continuous staircases	01 no.	No. of the second secon	MR		
	to terrace	1.50 mtr.	1.50 mtr	MR		
	e. Width of Corridor f. Door Size class room	01 mtr.	01 mtr.	MR		
	g. Number of Door class room	01 no.	01 no.	IVIIX		
03		N/A	N/A	N/A		
	Fire check door	1977	N/A	N/A		
	 Sealing of electrical 	N/A		N/A		
	shafts	NI/A	N/A	N/A		
	Fire rating of shaft door	N/A	N/A	N/A		
	 Water curtain 	N/A	N/A	19/7		
Electronic Control	Fire Dampers					
(O4 Smoke Management System.	N/A N/A		N/A		
-	Basement	N/A	N/A	N/A		
	Upper floor	N/A	14//			
-	= (i viahoro			MD		
		16 nos.	18 nos.	MR		
	Total numbers	ABC /CC	ABC /CO ₂	MR		
	types	ISI mark		MR		
	IS marking	101111311				

06	First-aid-Hose Reels.						
8	Total numbers on each floor	01 No.	01 No. each block	MR			
	 Length of hose reel hose 	30 mtr.	30 mtr	MR			
	Nozzle diameter	05 mm	05 mm	MR			
07	Automatic fire detection and alarming syst	tem.	l b				
7	Type of detectors	N/A	N/A	N/A			
	 Location of main panel 	N/A	N/A	N/A			
	 Location of repeater panel 	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	 Hooter's location 	N/A	N/A	N/A			
80	MOEFA	N/A	N/A	N/A			
09	Public address System.	N/A	N/A	N/A			
10	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	upper floor	N/A	N/A	N/A			
	 sprinkler above false ceiling 	N/A	N/A	N/A			
11	Internal Hydrants						
	 size of riser/down-comer 	N/A	N/A	N/A			
	 Number of hydrants per floor 	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level	N/A	N/A	N/A			
	Discharge of main Pump	N/A	N/A	N/A			
7	➤ Head of Main Pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby pump out put	N/A	N/A	N/A			
	> Standby pump Head	N/A	N/A	N/A			
	> Auto Starting /Manual stopping	N/A N/A	N/A N/A	N/A N/A			
	Pump House AccessTerrace Level	IN/A	IN/A	IN/A			
	Terrace Level Discharge of pump	450 Lpm.	450 Lpm	MR			
	➢ Head of the Pump	40 mtr	each block 40 mtr	MR			
	> Power supply	Required	Provided	MR			
	> Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for Fire Fighting.	, roquirou					
	Underground tank capacity	N/A	N/A	N/A			
	Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	N/A	N/A			
	Access to tank	Required	Provided	MR			
×	Overhead Tank capacity	10,000 Ltr. each block)	10000 Ltr. each block	MR			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
1	Communication in lift car	N/A	N/A	N/A			
		1, 25.5	1 177.71 17				
	Firemen's grounding switch	N/A	N/A	N/A			

17	Standby power supply	N/A	N/A	N/A
18	Refuge Area.			
	Total area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector system panel	N/A	N/A	N/A
	Flow switch panel	N/A	N/A	N/A
	PA system panel	N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection systems		N/A	N/A
	for protection of special Risks, if			
	any:			

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety required under the NBC Part IV, it is recommended to renew Fire Safety Certificate.

Signature of the Inspecting Officer

Name Designation : ADO (TP)

: Mehmood

DY. CFO(NDZ)

