GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

No. F.6/DFS/MS/Motel/SZ/2021/ 3 4 8

Dated: 23/07/2021

FIRE SAFETY CERTIFICATE

Certified that M/s Avalon Resorts Pvt. Ltd., at Khasra No – 365 & 383, Sultanpur, Mehrauli, - Gurgaon Road, New Delhi- 110030 comprised of Small Basement Ground Plus Four Upper Floors (4th Floor is Sealed with Brick Wall) was issued FSC by this department vide letter F6/DFS/MS/Motel/2018/SZ/1054 dated 14/05/18 for Basement, ground plus four upper floors. The premise was re-inspected by the officer concerned of this department on 14/07/2021in the presence of Sh. G. S Joshi and found to have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010and that the building is fit for occupancy Group A "Residential Building" (Motel Building is running at Small Basement, ground plus three upper floor only) with effect 37/07 2021 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

Issued on 23/07/2021 New Delhi by

(SUNIL CHAWDHARY) DY, CHIEF FIRE OFFICER (SZ)

Copy to:-

- 1. The Joint Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi-110049. (Ref. MHA Portal ID 2021041112723 dated 11/04/2021)
- 2. M/s Avalon Resorts Pvt. Ltd., Khasra No 365 & 383, Sultanpur, Mehrauli, Gurgaon Road, New Delhi 110030.

Conditions for the validity of fire safety certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 5. This fire safety certificate may not in any way be treated as regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

| | INSPECTI | ON REPORT | The state of the s | | | |
|--|---|--|--|--|--|--|
| 1 | Name & Address of the Building | M/s Avalon Resorts Pvt. Ltd., Khasra No – 365 & 383, Sultanpur, Mehrauli, - Gurgaon Road, New Delhi - 110030 | | | | |
| 2 | Type of Occupancy | Residential, Group 'A' (Motel) | | | | |
| 3 | Building Comprised of | Small Basement, G + 04 (Basement for pump house) & (04 Floor is sealed with Brick wall) | | | | |
| 4 | Type of Case | Renewal | | | | |
| 5 | Details of Previous NOC | F6/DFS/MS/M | otel/2018/SZ/1054 date | ed 14/05/18 | | |
| 6 | Fire Safety Directives Letter No | Nil | | | | |
| 7 | Date of Inspection | 14/07/2021 | | The Part of the Commission of | | |
| 8 | Name of the Inspecting Officers | Sh. Rajesh Kumar ADO (BCP) | | | | |
| 9 | Name & Designation of Officers from the building side | Sh. C.S Joshi | | | | |
| 10 | Year of construction | 2000 | | | | |
| 11 | Applicant letter No. | | 2021041112723 dated 11 | /04/2021 | | |
| S. No. | Minimum standards on Fire Prevention | Old NOC | Provided at Site | | | |
| | and Fire Safety U/R 33 | Requirements | 1 tovided at Site | Remarks MR/NMR | | |
| 1 | Access to Building. | | _ | ATAMAT TITAL | | |
| | Road width | 9m | Provided | MR | | |
| | Gate width | 5m | Accessible from road | MR | | |
| | Width of internal road | -NA- | -NA- | -NA- | | |
| 2 | Number, width, type & arrangement of e | xits. | | and the confirmation of the control date of the control of the con | | |
| | a) Number of Staircase | | | | | |
| | Upper floors. | 03 Nos | 03 Nos | MR | | |
| | Basement floor. | 01 Nos | 01 Nos | MR | | |
| | b) Width of Staircase | | | | | |
| | > Upper floor | 1.25 mtr | 1.35 , 0.95 & 0.90 mtr | MR (old case) | | |
| | Basement floor | 0.90 mtr | 1.30 m | MR | | |
| | c) Protection of exits | | | | | |
| | Fire check door Pressurization | Required Provided MR | | | | |
| | d) No. of continuous staircase to terrace | -NA- | -NA- | -NA- | | |
| | e) Width of corridor | Required | 03 no's | MR | | |
| | f) Door size | Required | 1.25 mtr | MR | | |
| | 1) Door size | 1m | Provided | MR | | |
| 3 | Compartmentation. | | | | | |
| The state of the s | Fire check door. | -NA- | -NA- | -NA- | | |
| | Sealing of electrical shafts. | Required | Provided | MR | | |
| | Fire rating of shaft door. | -NA- | -NA- | -NA- | | |
| | Water curtain | -NA- | -NA- | -NA- | | |
| 4 | Fire dampers. Smale Management | -NA- | -NA- | -NA- | | |
| 46 | Smoke Management system. | | | | | |
| | Basement Unpart floorer | 30 ACPH | Exhaust fan provided | MR | | |
| 5 | • Upper floors Fire Extinguishers. | 12 ACPH | Exhaust fan provided | MR | | |
| | | | | | | |
| | Total numbers | • | 46 Nos | MR | | |
| And a second contract of the second contract | • Types | ISI marked | ABC & CO2 | MR | | |
| 6 | ISI Marking First Aid Hose Reels. | | Provided | MR | | |
| V | | | | Manual management and an arrangement and an arrangement and arrangement arrangement and arrangement arrangemen | | |
| | Total numbers on each floor. I enoth of hose real have | Hose-reel | 02 Nos | MR | | |
| | Length of hose-reel hose.Nozzle Diameter | (02 Nos) | 30m | MR | | |
| 7 | Automatic fire detection & alarming system. | | 5mm | MR | | |
| *** | Town of 1 to the | P 1 | | | | |

| TT 97 | Location of Main Panel | Required | Ground floor | MR |
|---|--|------------------|------------------|------------|
| | Location of Repeater Panel | -NA- | -NA- | -NA- |
| | Alternate source of power | Required | Provided | MR |
| | Hooter's location | Required | On Each Floor | MR |
| 8 | MOEFA | Required | Provided | MR |
| 9 | Public Address System | Required | Provided | MR |
| 10 | Automatic Sprinkler System | | | |
| | Basement | Required | Provided | MR |
| | Ground & Upper floors | Required | Provided | MR |
| | Sprinkler above false ceiling | -NA- | -NA- | -NA- |
| 11 | Internal Hydrants. | | | |
| | Size of Riser/Down-comer | 100 mm | Provided | MR |
| | Number of Hydrant per floor | 02 Nos | Provided | MR |
| | Hose box. | 02 Nos | Provided | MR |
| 12 | Yard Hydrants. | | | |
| | Total number of hydrants. | Required | 01 Nos | MR |
| | Hose box. | Required | 01 Nos | MR |
| 13 | Pumping arrangements. | | | |
| | Ground Level | 2200 1 51 5 | D 11.1 | 1 3 5 |
| | Discharge of main pump. | 2280 LPM | Provided | MR |
| | Head of main pump. | 40m | Provided | MR |
| | Number of main pumps. Jockey Pump output | 02 Nos | Provided | MR |
| | Jockey Pump output.Jockey Pump head. | 180 LPM | Provided | MR |
| | Standby Pump output. | 40m | Provided | MR |
| | Standby Pump head. | 2280 LPM | Provided | MR |
| | Auto Starting/Manual Stopping. | 40m | Provided | MR |
| | Pump house access. | Required | Provided | MR |
| | Terrace Level | Required | Provided | MR |
| | | 3.T.A. | N.T.A. | 774 |
| | Discharge of pump. | -NA- | -NA- | -NA- |
| | Head of pump. Power supply | -NA- | -NA- | -NA- |
| | Power supply.Auto starting of pump. | -NA- | -NA- | -NA- |
| 14 | Captive water storage for fire fighting. | -NA- | -NA- | -NA- |
| *************************************** | | 50,000 Ltrs | Provided | MR |
| | Underground tank capacity. | Required | Provided | |
| | Draw-off connection. | Required | Provided | MR MR |
| | Fire Service Inlet. | Required | Provided | MR |
| | Access to tank. | | Provided | 1 |
| | Overhead tank capacity. | 20,000 Ltrs | | MR |
| 15 | Exit Signage. | Required | Provided | MR |
| 16 | Provision of Lifts. | | | |
| | Pressurization of lift shaft. | -NA- | -NA- | -NA- |
| | Pressurization of lift lobby.Communication in lift car. | -NA- | -NA- | -NA- |
| | Fireman's switch. | -NA- | -NA- | -NA- |
| | - I II VIII G GWILVII. | Required | Provided | MR |
| | Lift signage. | | 274 | -NA- |
| 1= | Zant digitage. | -NA- | -NA- | |
| 17 | Standby Power Supply | -NA- Required | -NA- Provided | MR |
| 17 18 | Standby Power Supply Refuge Area | Required . | Provided | MR |
| | Standby Power Supply Refuge Area Total area | Required -NA- | Provided -NA- | MR -NA- |
| | Standby Power Supply Refuge Area | Required . | Provided | MR |

| 17 | THE COULT OF ROOM. | | | | |
|----|------------------------|------|------|------|--|
| | Detector system panel. | -NA- | -NA- | -NA- | |
| | Flow switch panel. | -NA- | -NA- | -NA- | |
| | PA system panel. | -NA- | -NA- | -NA- | |

Battery backup.
Building floor plan.
-NA-NA-NA-NA-NA-NA
20 Special Fire Protection System for the Protection of special Risk, if any. No
-NA-

The fire protection system provided in the premises were checked, tested at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/Motel/2018/SZ/1054 dated 14/05/18, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar Designation: ADO (BCP)

DO (8D)

XIV 9

Folse) K.J. D. Ce

ADDAS (P)

you synature

lettel is pulp to

1/19

Dy cfo/52

M. S. UC