GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/EH/SZ/2021/ | 56

Dated: 28 / 7 / 2021

FIRE SAFETY CERTIFICATE

Certified that M/s TKS THE TRI KITCHEN (A Unit of Oxford Finvest Limited) at 3rd Floor, E-31–32, South Extension Market–II, New Delhi–110049, comprised of Basement, Ground plus three upper floors (Restaurants at 3rd Floor only) was issued fire safety certificate by this department vide letter No. F.6/DFS/MS/EH/2018/SZ/775 dated 20/04/2018. The premise was reinspected by the officer concerned of this department on 14/07/2021 in the presence of Avhay Taneja (Manager) and found that the said restaurant have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the said premise is fit for occupancy class D "Assembly Building" (Restaurant) with effect from 28/7/2021 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on $\sqrt{2021}$ at New Delhi by

(Sunil Chawdhary) Dy. Chief Fire Officer (SZ) Delhi Fire Service

Copy to: -

- 1. The Dy. Health Officer, South Delhi Municipal Corporation, South Zone, Public Health Department, Green Park, New Delhi–110016
- 2. The Manager, M/s TKS THE TRI KITCHEN (A Unit of Oxford Finvest Limited), 3rd Floor, E-31–32, South Extension Market–II, New Delhi–110049

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

	INSPE	CTION REPORT				
1	Name & Address of the Building M//s TKS THE TRI KITCHEN (A Unit of Oxford					
		Finvest Limited) at 3 rd Floor, E-31–32, South Extension Market–II, New Delhi–110049				
2.	Type of Occupancy	Group-D "Assembly Building" (Restaurant)				
3	Building Comprised of	Basement, Ground plus three upper floors (Restaurant running at 3 rd Floor only)				
4	Type of Case	Renewal				
5	Details of Previous NOC		18/SZ/775 dated 20/04/	2018		
6	Fire Safety Directives Letter No		F.6/DFS/MS/EH/2018/SZ/775 dated 20/04/2018 Cir. No. F6/DFS/MS/EH/2005/718 dated 04/04/2014			
7	Date of Inspection	14/07/2021				
8	Name of the Inspecting Officers	DO (SD) S.K. Dua				
9	Name & Designation of Officers	Mr. Avhay Taneja (Manager)				
	from the building side					
10	Year of construction	1947				
11	Applicant letter No.	Online ID: 2020051604923 dated 29/06/2021				
S. No	Minimum standards on Fire Prevention	Old NOC	Provided at	Remarks		
1	and Fire Safety U/R 33	Requirements	Site	NR/NMR		
1	Access to Building.	Did	24m	MR		
	Road width	Required	140140011000000000000000000000000000000			
	Gate width	-N/A-	-N/A-	-N/A-		
	Width of internal road	-N/A-	-N/A-	-N/A-		
2	Number, width, type & arrangement of	exits.				
	a) Number of Staircase					
	> Upper floors.	Two	Two	MR		
	> Basement floor.	-N/A-	-N/A-	-N/A-		
	b) Width of Staircase		φ.			
	> Upper floors	Required	1.14m & 0.90m	MR (Old case		
	Basement floor	-N/A-	-N/A-	-N/A-		
	c) Protection of exits					
	Fire check door	-N/A-	-N/A-	-N/A-		
	Pressurization	-N/A-	-N/A-	-N/A-		
	d) No. of continuous staircase to terrace		-N/A-	-N/A-		
		-N/A-	-N/A-	-N/A-		
	e) Width of corridorf) Door size	2 exits	1.22m & 1.10m	MR (Old case		
3	Compartmentation.	2 CAILS	1.2211 & 1.1011	Titte (Ord case		
3	Fire check door.	-N/A-	-N/A-	-N/A-		
	• Sealing of electrical shafts.	-N/A-	-N/A-	-N/A-		
		-N/A-	-N/A-	-N/A-		
	• Fire rating of shaft door.		-N/A-	-N/A-		
	Water curtain	-N/A-				
	• Fire dampers.	-N/A-	-N/A-	-N/A-		
4.	Smoke Management system.					
	 Basement 	-N/A-	-N/A-	-N/A-		
	 Upper floors 	Required	Exhaust fan provided	MR		
5.	Fire Extinguishers.		8			
	Total numbers	04 Nos	10 Nos.	MR		
	• Types	ABC / CO ₂ / W.CO ₂	ABC & CO ₂	MR		
	ISI Marking	ISI marked	Provided	MR		
	First Aid Hose Reels.	151 marked	TTOVICCE	14117		
6.		0	Duaridad	MR		
	Total numbers on each floor	One	Provided			
	Length of hose-reel hose.	30m	Provided	MR		
	Nozzle Diameter	5mm	Provided	MR		

7 A	Automatic Fire Detection & Alarming Syste	em.		
1 1	Type of Detectors	-N/A-	-N/A-	-N/A-
	Y CMain Donal	-N/A-	-N/A-	-N/A-
	T	-N/A-	-N/A-	-N/A-
*		-N/A-	-N/A-	-N/A-
	Alternate source of power		-N/A-	-N/A-
	Hooter's location	Required	Provided	MR
	MOEFA	-N/A-	-N/A-	-N/A-
	Public Address System	14/14	-	
10. A	Automatic Sprinkler System	-N/A-	-N/A-	-N/A-
	Basement.Upper floors/Restt. Premise	Required	Provided	MR
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA-
11.	Internal Hydrants.	and a contract of the contract		3.73
11.	Size of Riser / Down-comer	Required	100 mm	MR
	Number of Hydrant per floor	Required	One	MR
	Hose box.	Required	One	MR
2.	Yard Hydrants.			DI/A
	Total number of hydrants.	-N/A-	-N/A-	-N/A- -N/A-
	Hose box.	-N/A-	-N/A-	-1////-
13	Pumping arrangements			
	Ground Level		NT/A	-N/A-
	Discharge of main pump.	-N/A-	-N/A-	-N/A-
	➤ Head of main pump.	-N/A-	-N/A-	
	Number of main pumps.	-N/A-	-N/A-	-N/A-
	Jockey Pump output.	-N/A-	-N/A-	-N/A-
	> Jockey Pump head.	-N/A-	-N/A-	-N/A-
	Standby Pump output.	-N/A-	-N/A-	-N/A-
	Standby Pump head.	-N/A-	-N/A-	-N/A-
	> Auto Starting/Manual stopping.	-N/A-	-N/A-	-N/A-
	> Pump house access.	-N/A-	-N/A-	-N/A-
	i de la companya de l			
	Terrace LevelDischarge of pump.	450 LPM	450 LPM	MR
	Head of pump.	40ms	40m	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for firefighting.			
17.	Underground tank capacity.	-N/A-	-N/A-	-N/A-
	Draw-off connection.	-N/A-	-N/A-	-N/A-
	Fire Service Inlet.	-N/A-	-N/A-	-N/A-
	Access to tank.	-N/A-	-N/A-	-N/A-
	And the second of the second o	10,000 Ltrs	10,000 Ltrs	MR
	Overhead tank capacity. This is a second control of the capacity of the	Required	Provided	MR
15.	Exit Signage.	required		
16.	Provision of Lifts.	-N/A-	-N/A-	-N/A-
	Pressurization of lift shaft.	-N/A-	-N/A-	-N/A-
	 Pressurization of lift lobby. 		-N/A-	-N/A-
	 Communication in lift car. 	-N/A-		-N/A-
	• Fireman's switch.	-N/A-	-N/A-	×
	• Lift signage.	-N/A-	-N/A-	-N/A
17	Standby Power Supply	Required	Provided	MR
18.				N.T./ A
	Total area	-N/A-	-N/A-	-N/A
	 Location 	-N/A-	-N/A-	-N/A-

Ż.

19.	Fire C	ontrol Room.			
	Detector Sy	Detector System Panel.	-N/A-	-N/A-	-N/A-
		Flow Switch Panel.	-N/A-	-N/A-	-N/A-
	BU VA .	PA system Panel. Battery backup	-N/A-	-N/A-	-N/A-
			-N/A-	-N/A-	-N/A-
		Building floor plan	-N/A-	-N/A-	-N/A-
20.	Specia	l Fire Protection System for the tion of special Risk, if any:	-N/A-	-N/A-	-N/A-

The Fire protection systems provided in the premises were checked & tested at random and found functional at the time of inspection.

In view of deemed compliance of the minimum standards on fire prevention and fire safety required under the rules, renewal of the FSC issued vide letter no. F.6/DFS/MS/EH/2018/SZ/775 dated 20/04/2018 under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

DCFO (SZ)

F. J. pleef (

Signature of the Inspecting

Name: S.K. Dua Designation: DO (SD)

F.T. letter is put up for est. pl.