GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/WZ/2021/ 354

Dated: 26 /07/2021

FIRE SAFETY CERTIFICATE

Centre, Block-B, Shalimar Bagh, Delhi, comprised of 03 Basement & Ground + 08 Upper Floors, owed/occupied by Ambience Tower Pvt. Ltd. was issued FSC by this department Vide Letter No. F6/DFS/MS/2017/WZ/434 dated 23.03.2017. The said premise was re-inspected by the officers concerned of this department on 06.07.2021 in the presence of Sh. Daksh (GM Architect) & Sh. Manoj Shaha (Representative) and found that the premises / building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010, and that the premises/building is fit for occupancy class "Commercial/Office" with effect from 26 07 2021 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Issued on 26 07 2021 at New Delhi by.

(Atul Garg)
Director

Copy to:-

- 1. The Authorized Signatory, Commercial Complex, Located at Plot no. Plot No. 10, Community Centre, Block-B, Shalimar Bagh, Delhi.
- 2. The Vice Chairman, DDA, INA, Vikas Sadan, New Delhi-110023.

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time. It should not bolted /locked.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any loss of life any property due to the non-functional of any fire safety measures, management shall be held responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this **Fire Safety** Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.
- 9. Atrium & Lift lobby shall be open to sky.
- 10. The Basement shall be used as per BBL.

THE CALL

1. Name & address of the building: Commercial Complex (Ambience Tower Pvt. Ltd.), Located at Plot No.10, Community Centre, B-Block, Shalimar Bagh, Delhi.

2. Type of Occupancy : Mercantile (03 Basement + Ground + 08 Upper Floors)

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/2017/WZ/434 dated 23.03.2017

5. Fire Safety directives Letter No.: F6/DFS/MS/BP/2016/278 dated 07.11.2016

6. Date of inspection : 06.07.2021

7. Name of the Inspecting Officer: M. K. Chattopadhyay DO (West) & S.P. Bhardwaj ADO (WP)

8. Name and designation of Officer

from the building side :Sh. Daksh (GM Architect) & Manoj Shaha (Representative)

9. Year of Construction : 2016

10. Applicant's letter No. : email dated 22.06.2021

S No	Minimum standards on fire prevention and fire safety U/.	R Re	NBC Requirements/ letter dated 23.03.2017		Provided at site		Remarks MR/NMR		
1.	Access of building								
	 Road width 	10 m	10 m Pro		vided	MR			
	Gate width		6 m			vided	MR		
	 Width of internal road 		6 m		Provided		MR		
2.	Number, width, Type & Arrangements of exits								
	a. Number of staircases			e *	C 20				
	 Upper floors 		02			MR			
	 Basements 	02+02	02 Provide 02+02 ramps Provide			MR			
	b. Width of staircases	il.							
	 Upper floors 	1.5m	I	Provided		MR			
	 Basements 	1.5m	P	rovided		MR			
	c. Protection of exits				10.00				
		 Fire check door 			Required		MR		
	 Pressurization 	Required			Provided	MR			
	d. No of continuous staircase to terrace		(02 Pro		Provided	MR		
	e. Width Of Corridor	NA	NA NA		(Hall Only)	NA			
	f. Door Size		1	1 m		Provided			
	T. Door Size 1 m Provided MR Compartmentation								
	 Fire check door 		Requ	Required		Provided	MR		
	 Sealing of electrical sha 	 Sealing of electrical shafts 		Required		Provided	MR		
	 Fire Rating of shaft doo 	Required			Provided	MR			
	 Water Curtain 	Required			Provided	MR			
	 Fire Dampers 		Required		Provided	MR			
	Smoke managements System								
	 Basements 	12 a/c pe		The second secon			MR		
	 Upper floors 	12 a/c pe	a/c per hour		Provided		MR		
	Fire Extinguishers								
	 Total numbers 	72	2 nos.	CO ₂ , WCO ₂ Prov		ed	MR		
	 Types 	ABC &	CO ₂ , WCO ₂			Provided			
	IS marking	ISI	marked				MR MR		
	First – Aid Hose Reels	- V							
	Total numbers on each floor		Two at each floor		Provided		MR		

	ype of detectors	Time-	S	moke &	Pr	ovided		MR
				Heat				
	Location of Main Panel			Required		Provided		MR
	Location of Repeater Panel			Each floor		Provided		MR
	Alternate source of power			Requir		Provided		MR
8.	Hooters' Location			Requir		Provided	-	MR
9.	MOEFA Public Address Service			Required		Provided		MR
$\frac{1}{10}$.	Public Address System Automatic Sprinkler System	ess System			ed F	Provided		MR
10.	Basements		D :	1				
				Requir		Provided		MR
	Upper FloorSprinkler above false ceiling			Required NA		Provided		MR
11.	Internal Hydrants:		NA		NA		NA	
	Size of riser/down- comer			150 mm		Drovidad) (D
	 Number of hydrants per floor Hose Box 			02		Provided Provided		MR
				02		Provided		MR
12.	Yard Hydrants			02	I	Tovided		MR
	Total number of hydrants	R	equired		Provided		MD	-
	Hose Box		equired		Provided		MR MR	
13.	Pumping Arrangements:	10	- quired		TTOVIDEU		WIK	
	Ground Level			-				
	Discharge of main pump	28	50 lpm	Provi			MR	
	Head of main pump	70 m			Provided		MR	
	Number of main pumps	2			Provided		MR	
	> Jockey pump out put	180 lpm			Provided		MR	
	Jockey pump head		70 m		Provided		MR	
	Standby Pump out put	2850 lpm			Provided		MR	
	Standby Pump Head	70 m			Provided		MR	
	Auto Staring/Manual	Required			Provided		MR	
	stopping					2		
	Pump House AccessTerrace level	Re	equired		Provided		MR	
	Discharge of pump	×	NT 4			7	-	
	Head of the pump	NA NA			NA NA		NA	
	> Power supply						NA	,
	Auto starting of pump		NA NA	70 0	NA		NA	
14.	Captive water Storage for firefighting		INA		NA		NA	
	Underground tank capacity	,.	2,00,0001	tro	Provid	lad	M	D
	> Draw off connection				Provid		M	0.1
	Fire service inlet		Required Required		Provid		M	
	Access to tank	,	Require		Provid	110 May 100 Ma	M	
	 Overhead Tank capacity 		20,000 liters		Provid			
	Exit Signage Re	equired			Provided		MR MR	
16.	Provision of Lifts							
	Pressurization of Lift Shaft		Requ	iired	Prov	vided	N	R
	Pressurization of lift lobby	R R		Required Required Required		vided	MR	
	Communication in lift Car					vided		R
	Fireman's Grounding Switch					Provided		R
	Lift Signage			Required		Provided		R
7.	Standby power supply			Required		ided	M	P
	Refuge Area			required		Provided N		
	> Total area		Regu	Required		As per plan		R
	> Location			7 th Floor		Provided Provided		
9.	Fire control room 7" Floor Provided MR							
	Detector system panel	Required			Provided		MR	-
	Flow Switch Panel	Required		Provid				
	PA System Panel	Required			Provided		MR	
	Battery backup	Required			Provided		MR	
	D Ruilding Floor Dl							

/					
1	20.	Special Fire Protection Systems for Protection of special Risks, if any;	CO2 Flooding System for HT & LT Panel	Provided	MR
		The fire protection sys at the time of inspection. The 25.03.2021 found rectified. In view of the deemed safety requirements under	tems provided in the building the Shortcomings vide letter no compliance of the minimum state rules, renewal of ted 23.03.2017 is recommended the DFS Act 2007.	. F6/DFS/MS/WZ tandards on fire pr FSC issued v	Z/2021/696 dated revention and fire vide letter no.
		M. K. Chattopadhyay DO (West)		S.P. B	hardwaj 7121 (WP)
D.O. (WEST) DATED\\	07/2	Des (WZ)	1917 DOLY		
		Kenny			
Idh!	(2)	19/3 by sul			
That F	Omica		10 FTP/		
		Dofwest			
		ABO/(WP)	23/2		
	-		A 1304	o for Sig	Sm 33/3124
		26/0	1/201/		