GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/NDZ/2021/ 273

FIRE SAFETY CERTIFICATE

Certified that the Hindustan International Guest House located at 8220, Multani Dhanda, Pahar Ganj, New Delhi comprised of Ground + 05 Upper floors, Ground floor (Reception + 01 office), 1st floor to 4th floor (05 guest rooms at each floor) and 5th floor found sealed, total 20 guest rooms owned/occupied by Hindustan International Guest House was earlier granted FSC by this department vide letter No.F6/DFS/MS/GH/2018/NDZ/1784 dated 01/08/18. Now, The premise was re-inspected by the officer concerned of this department on 20/07/21 in the presence of Sh. Anil Kumar and found that the said guest house building having affidavit dated 05.12.2019 regarding not to use above third, has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 Ground floor (Reception + 01 office), 1st floor to 3rd floor (05 guest rooms at each floor) as above 15 guest rooms up to third floor only with effect from 30(-7/7)--- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued - 3-6/7/2-1----at New Delhi by.

(Dr. S.K. Tomar) Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Commissioner, North MCD, Civic Centre, New Delhi.

- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. 2021070314607 dated 06.07.21
- 3. The Manager, Hindustan International Guest House 8220, Multani Dhanda, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

This clearance/ FSC shall stand canceled if guest house owner/occupier fails to comply all other conditions mentioned in the gazette notification dated 27.05.2019 & clarification issued on dated 29.06.2021 latest by 30.09.2021

2. All the fire safety arrangements provided therein shall be maintained in good working conditions at

all times.

3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

4. The trained fire fighting staff should be available round the clock.

5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building

Hindustan International Guest House at 8220, Multani Dhanda, Pahar Ganj, New Delhi

2. Type of occupancy:-

Residential, Sub Division-A-1

Gr. + 05 Upper floors & store room at terrace Ground floor (Reception + 01 office), 1st floor to 3rd floor (05 guest rooms at each floor) total -15 room

and 4th & 5th floor(sealed)

not in use as per affidavit dated 05.12.2019

3. Type of case:-

4. Details of previous FSC:-

Renewal

No. F6/DFS/MS/GH/2018/NDZ/1784 dated 01/08/18.

5. Fire safety directives No.-

N/A

6. Date of inspection:-

20/07/21

7. Name of the inspecting officer:-

Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer From the building side:-

Sh. Anil Before 2001

9. Year of construction:-

2021070314607 dated 06.07.21

| 10. | Applicant's letter No:- | 2021070314607 | dated 06.07.21 | Old Case | |
|-------|--|--|------------------|--|--|
| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement/ Existing fire safety arrangements | Provided at site | Remarks MR/NMR | |
| 1. | Access to Building | | | | |
| | 1) Road width | N/A | 06 mtr. | N/A | |
| | 2) Gate width | N/A | N/A | N/A | |
| | 3)Width of internal road | N/A | N/A | N/A | |
| 2. | Number, Width Type & Arra | angement of Ex | rits | | |
| 40 | A. Number of staircases | | | | |
| | 1. Upper floors | 01 Nos. | 01 Nos. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | B. Width of staircase | | | | |
| | 1. Upper floors | 1.0 mtr. | 1.24 mtr. | MR | |
| | 2. Basements | N/A | N/A | N/A | |
| | C. Protection of exits | | | 27/4 | |
| | 1. Fire check door | N/A | N/A | N/A | |
| | 2. Pressurization | N/A | N/A | N/A | |
| | D. No. of continuous staircase to terrace | 01 | 01 | MR | |
| į. | E. Width of corridor | N/A | N/A | N/A | |
| | F. Door size | 01 mtr. | 01 mtr. | MR | |
| 3. | Compartmentation | | 100 | | |
| J. | 1) Fire check door | N/A | N/A | N/A | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | |
| | 4) Water curtain | N/A | N/A | N/A | |
| | 5) Fire Dampers | N/A | N/A | N/A | |
| 4. | Smoke Management System | | | | |
| | 1) Basements | 30 ACPH | N/A | N/A | |
| | 2) Upper floors | Required as per G.N dated 27.05.19 | Not provided | Last dt. 30.09.21 of compliance extended vide order dt. 29.06.2021 | |
| 5. | Fire Extinguishers | - 1.5 | | MD | |
| - | 1) Total numbers | 20 Nos. | 20 Nos. | MR | |

N/24

| | 2) Types | ABC & CO2 | ABC & CO2 | MR | |
|-------------|----------------------------------|--|--------------|---|--|
| | 3) ISI marking | Required | Provided | MR | |
| 6. | First-Aid Hose Reel | 1 | | | |
| 0. | 1) Total number of each | 01 | 01 | MR | |
| | floor | - | | | |
| | 2) Length of hose reel hose | 30 mtr. | 30 mtr. | MR | |
| | 3) Nozzle diameter | 05 mm | 05 mm | MR | |
| 7. | Automatic Fire Detection & | | | [4] | |
| | 1) Type of detectors CO type | Required as per G.N dated 27.05.19 | Not provided | Last dt. 30.09.21 of compliance extended vide order dt. 29.06.2021 | |
| | 2) Location of main panel | N/A | N/A | N/A | |
| | 3) Location of repeater panel | N/A | N/A | N/A | |
| | 4) Alternate source of power | N/A | N/A | N/A | |
| | 5) Hooter's Location | N/A | N/A | N/A | |
| 8. | MOEFA | Required | Provided | MR | |
| 9. | Public Address System | Required | Provided | MR | |
| 10. | Automatic Sprinkler System | harry 1000 per 1000 p | | | |
| 10. | 1) Basement | N/A | N/A | N/A | |
| | 2) Upper floors | N/A | N/A | N/A | |
| | 3) Sprinkler above false | N/A | N/A | N/A | |
| | ceiling | | | | |
| 11. | Internal Hydrants | | | | |
| | 1) Size of riser/down-comer | N/A | N/A | N/A | |
| | 2) Number of hydrants per | N/A | N/A | N/A | |
| | floor | | | | |
| | 3) Hose box | N/A | N/A | N/A | |
| 12. | Yard Hydrants | | | | |
| , | 1) Total number of hydrants | N/A | N/A | N/A | |
| | 2) Hose box | N/A | N/A | N/A | |
| 13. | Pumping Arrangement | | | | |
| | 1) Ground level | N/A | N/A | N/A | |
| | a) Discharge of main pump | N/A | N/A | N/A | |
| | b) Head of main pump | N/A | N/A | N/A | |
| | c) Number of main pump | | N/A | N/A | |
| | d) Jockey pump out put | N/A | N/A | N/A | |
| | e) Jockey pump head | N/A | N/A | N/A | |
| | f) Stand by pump output | | N/A | N/A | |
| | g) Stand by pump head | N/A | N/A | N/A | |
| | h) Auto starting/Manual stopping | N/A | N/A | N/A | |
| | 2) Terrace level | | | | |
| | a) Discharge of pump | 225 LPM | 225 LPM | MR | |
| | b) Head of pump | 30 mtr. | 30 mtr. | MR | |
| | c) Power supply | Required | Provided | MR | |
| | d) Auto starting of pump | Required | Provided | MR | |
| 14. | Captive Water Storage for l | Fire Fighting | | | |
| | 1) Under ground tank | N/A | N/A | N/A | |

| | capacity | T | | T |
|-----|--|--|-----------|-----|
| * | a) Draw-off connection | N/A | N/A | N/A |
| | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank capacity | 2500 ltr. | 2500 ltr. | MR |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | 1 | | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| 7 | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection Syst Risk, if any: One ABC type fire | tem for Protection of special ire extinguisher found provided. | | MR |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

The height of building is shown on the section /elevation plan is16.15 meter up to terrace level and 13.00 meter up to third floor as submitted by owner, if approved, we may renew the FSC up to third floor

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2018/NDZ/1784 dated 01/08/18 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended up to third floor only.

Signature of the Inspecting Officer

Name: - Ravinder Singh Designation: - ADO (CC)

apporance of a parting for law foruse