## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2021/ 67

Dated: 2./.8../2021

## FIRE SAFETY CERTIFICATE

Certified that the P.K. SHEFI FOOD PLAZA located at, Platform No 16, New Delhi Railway Station comprises of Ground + 01 upper floor. The premises was inspected by officer concerned of this department on 16/07/2021 in the presence of Mr. Miraj and found that the said premises has complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D for Restaurant at ground & Ist floor, with effect from 2/8/2+-----for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -24-8-(-2-)-----at New Delhi by.

DIRECTOR

Delhi Fire Service

Copy to:-

- 1. The Dy. Commissioner of Police (Lic), 1<sup>st</sup> floor, PS Defence Colony, New Delhi Online ID no. 2021031311258 dated 19.04.21
- 2. The Manager,

M/S P.K.SHEFI FOOD PLAZA,

Plat form No 16, New Delhi Railway Station, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is strictly prohibited.

## **INSPECTION REPORT**

1. Name & address of the building

P.K. SHEFI FOOD PLAZA

At Platform No. 16, New Delhi Railway Station, New Delhi, Ground + Ist Floor Assembly Building Group-D, Restaurant is

running on Ground & first floor.

2. Type of occupancy:-

New case N/A

3. Type of case:-4. Details of previous FSC:-

N/A

5. Fire safety directives No.-

6. Date of inspection: -

16/07/2021

7. Name of the inspecting officer:-

Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer From the building side:-

Mr. Miraj

9. Year of construction:-

2021

10. Applicant's letter No:-

Online ID no. 2021031311258 dated 19.04.21

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing	Provided at site	Remarks MR/NMR				
1.	Access to Building			7.40				
	1) Road width	06mtr	10 mtr.	MR				
	2) Gate width	N/A	N/A	N/A				
	3)Width of internal road	N/A	N/A	N/A				
2.	Number, Width Type & Arrangement of Exits							
	A. Number of staircases			) (D)				
	1. Upper floors	02nos	02 nos	MR				
	2. Basements	N/A	N/A	N/A				
	B. Width of staircase			) (D				
	1. Upper floors	1.5meter	2.0 & 1.5 meter	MR				
	2. Basements	N/A	N/A	N/A				
	C. Protection of exits			DT/A				
	1. Fire check door	N/A	N/A	N/A				
	2. Pressurization	N/A	N/A	N/A				
	D. No. of continuous	Required	Provided	MR				
	staircase to terrace	<u> </u>		DI/A				
	E. Width of corridor	N/A	N/A	N/A				
	F. Door size	1.5 mtr	1.5 m & 2.0 m	MR				
3.	Compartmentation		21/4					
	1) Fire check door	N/A	N/A	N/A				
	2) Sealing of electrical shafts	N/A	N/A	N/A				
	3) Fire rating of shaft door	N/A	N/A	N/A				
	4) Water curtain	N/A	N/A	N/A N/A				
	5) Fire Dampers	N/A	N/A	IN/A				
4.	Smoke Management System	DT/A	N/A					
	1) Basements	30 ACPH	N/A	MR				
	2) Upper floors	12 a/c per	Natural	IVIK				
		hour		-				
5.	Fire Extinguishers	10637	OC Nos	MR				
	1) Total numbers	06 Nos.	06 Nos.	MR				
	2) Types	ABC & CO2	ABC & CO2	MR				
	3) ISI marking	Required	Provided	IVIK				
6.	First-Aid Hose Reel		0.1	MR				
	1) Total number of each	01	01	IVIK				



	floor			30	) mtr.		MR		
1	2) Length of hose reel hose	30 n			5 mm		MR		
}	3) Nozzle diameter	05 r	nm		) 111111				
	3) Nozzle diameter  Automatic Fire Detection &	Alar	ming S	ystem	ovided	1	N/A		
	1) Type of detectors	7 41 2		Dr	ovided	1	N/A		
	2) I contion of main panel	N/A			rovide		N/A	1	
	Tax I reaction of reneater pariet	N/1		D <sub>1</sub>	rovide	d	N/A	4	
	4) Alternate source of power	N/			rovide		N/A	A	
	5) Hooter's Location	N/		1	rovide		MI	3	
	MOEFA	Re	equired			u	N/		
	Public Address System	N/	/A		N/A		1 11		
•	Automatic Sprinkler System	m			1	ad	N	Ά	
0.	Automatic Springer	N	/A		Provid		N.	-	
	1) Basement	N	/A		Provid	ea		/A	
	2) Upper floors 3) Sprinkler above false	N	I/A		N/A		1,4	1 1	
	3) Sprinkler above laise						-		
	ceiling				100		- I	1R	- 15 m
11.	Internal Hydrants  1) Size of riser/down-comer	1	00mm		100m	m		ЛR	
	2) Number of hydrants per	(	)1		01		1	,110	
							- I	ИR	_
	floor		01		01			VIIC	
	3) Hose box				1 1 4			N/A	
12.	Yard Hydrants  1) Total number of hydran	ts	N/A		N/A			N/A	
	1) Total number of my draw		N/A		N/A			14/14	
	2) Hose box						-	N/A	
13.	Pumping Arrangement	_	N/A		N/A		-	N/A	
	1) Ground level	1	N/A		N/A			INIT	
	a) Discharge of mair	•						N/A	
	pump	nn	N/A		N/A			N/A	
	b) Head of main pur	тР	N/A		N/A			INIA	
	c) Number of main					!	-	N/A	
	pump	nut	N/A		N/A	The second secon		N/A	
	d) Jockey pump out	ad	N/A		N/A			N/A	
	e) Jockey pump hea	10	N/A		N/A	A	4.16	INA	
	f) Stand by pump							N/A	
	output  g) Stand by pump l	nead	N/A		N/			N/A	
	L time / NA	anual			N/	A		111/1	r
	h) Auto starting/ivi	arrow.					1		
	stopping 2) Terrace level					D) (		MI	2
	- 1 1 of ni	ımp	450	LPM		00LPM		MI	
-	a) Discharge of pu	- Timp	30 r	ntr.		rovided		M	
	b) Head of pump			uired		rovided		M	
	c) Power supply	f		uired	P	rovided		IVI	
	d) Auto starting o			- -					
	pump	go fo	r Fire	Fightin	g			N.I.	/ ^
t	pump  14. Captive Water Stora	tank	A LIEU	N/A	1	V/A		N.	/A
	1) Under ground	ialik						7.7	14
	capacity	cs reaction			]	N/A			/A
	a) Draw-off cont	nlet		N/A N/A		N/A			IA
	b) Fire service in			N/A		N/A			I/A
	c) Access to tan	K	- oaitu	20,00	0	25,000 1	it.	N	ΛR
	d) Over head tar	ik caj	pacity	20,00					



		lit.		
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
<u>.</u>	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System Risk, if any:	N/A		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, if agreed, the fire Safety Certificate under rule 35 of Delhi Fire Service Rules-2010 is recommended to for approval.

Signature of the Inspecting Officer

Name: - Rayinder Singh Designation: - ADO (CC)

Doku)
19/7

Sych Cross

X 50mm/

CFO(nd) - DIM

Director Auf Jon

of coll of and for the town the