cyp

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6 DFS/MS/School/2021/SZ/ 570

Dated: 30 / 7 / 2021

FIRE SAFETY CERTIFICATE

Certified that Sarvodaya Kanya Vidyalaya No- 2, Mehrauli, Main Bazar, New Delhi110030 (1923079) comprised of Ground plus Three Upper floor have complied with the fire
prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules,
2010 and verified by officer concern of this department on 19/07/2021 in the presence of Smt. Seema
Khetar Pal (Vice Principal) of the school and that the building/premises is fit for occupancy class
"Educational, Group—B" (School) as above with effect from the date of issue of this certificate for
period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled
under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service
Rules, 2010. Issued on 30/7 2021 at New Delhi by

Copy to: -

- 1. The Principal, Sarvodaya Kanya Vidyalaya No- 2, Mehrauli, Main Bazar, New Delhi- 110030 (1923079)
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. This certificate cannot be treated as regularization of unauthorized construction, if any.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

		ION REPORT			
1	Name & Address of the Building	Sarvodaya Kany	a Vidyalaya No 2, Me	hrauli, Maii	
		Bazar New Delhi -110030 (ID- 1923079)			
2	Type of Occupancy	Educational			
3	Building Comprised of	Ground plus three upper			
4	Type of Case	New			
5	Details of Previous NOC	Nil			
6	Fire Safety Directives Letter No	Nil			
7	Date of Inspection	19/03/2021			
8	Name of the Inspecting Officers	Sh. Rajesh Kumar ADO (BCP)			
9	Name & Designation of Officers	Smt. Seema Khetar pal (Vice Principal)			
	from the building side				
10	Year of construction	1964		1	
11	Applicant letter No.	Gmail Dated 12/07/2021			
S. No	Minimum standards on Fire Prevention	requirements	Provided at Site	Remarks	
	and Fire Safety U/R 33			MR/NMF	
1	Access to Building.				
	Road width	Accessible	6 mtr	MR	
	Gate width	-NA-	-NA-	-NA-	
	Width of internal road	-NA-	-NA-	-NA-	
2	Number, width, type & arrangement of exits.				
	a) Number of Staircase				
	Upper floors.	Required	2 Nos	MR	
	Basement floor.	-NA-	-NA-	-NA-	
	b) Width of Staircase				
	Upper floors	1.5 m/ 0.75 m	1.50 mtr each	MR	
	Basement floor	-NA-	-NA-	-NA-	
	c) Protection of exits				
	Fire check door	-NA-	-NA-	-NA-	
	Pressurization	-NA-	-NA-	-NA-	
	d) No. of continuous staircase to terrace	Required	Provided	MR	
	e) Width of corridor	-NA-	NA	-NA-	
	f) Door size	1 mtr	1 mtr.		
3	Compartmentation.	1 1110	1	MR	
	- Sample the Miles of the Sample Samp				
	Fire check door.	-NA-	-NA-	-NA-	
	 Sealing of electrical shafts. 	-NA-	-NA-	-NA-	
	 Fire rating of shaft door. 	-NA-	-NA-	-NA-	
	Water curtain	-NA-	-NA-	-NA-	
	Fire dampers.	-NA-	-NA-	-NA-	
4.	Smoke Management system.				
Control of the State of the Sta	Basement	30a/c per hour	-NA-	-NA-	
	Upper floors	12a/c per hour	-NA-	-NA-	
5.	Fire Extinguishers.			4.14.4	
	Total numbers	Required	30 Nos	MR	
	 Types 	CO ² &ABC	CO ² & ABC	MR	
	 ISI Marking 	ISI mark	Provided	MR	
6.	First Aid Hose Reels.				
	Total numbers on each floor.	02	Provided	MR	
	Length of hose-reel hose.	30m	Provided	MR	
	Nozzle Diameter		Provided	MR	
7		5m	1 10 10 00	IVIK	
1	Automatic fire detection & alarming system.			-	
	Type of detectors	-NA-	-NA-	-NA-	

	Location of Main Panel	-NA-	-NA-	-NA-
	 Location of Repeater Panel 	-NA-	-NA-	-NA-
	 Alternate source of power 	-NA-	-NA-	-NA-
	Hooter's location	-NA-	-NA-	-NA-
8.	MOEFA	-NA-	-NA-	-NA-
9.	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System		,	
	Basement	-NA-	100 mm	-NA-
	Upper floors	-NA-	02	-NA-
	Sprinkler above false ceiling	-NA-	02	-NA-
11.	Internal Hydrants.		The state of the s	
	Size of Riser/Down-comer	-NA-	-NA-	-NA-
	 Number of Hydrant per floor 	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
12.	Yard Hydrants.			
	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.			
	Ground Level			
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level			
	Discharge of pump.	450 LPM	Provided	MR
	Head of pump.	40 m	Provided	MR
	Power supply.	Required	Provided	• MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.	Required	Tioyided	IVIN.
17.	Underground tank capacity.	-NA-	-NA-	-NA-
	> Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	NA-
				-
	Access to tank.	-NA-	-NA-	- N.A-
		-NA-	-NA- Provided	
15.	Overhead tank capacity.	10,000 ltrs	Provided	MR
	Overhead tank capacity. Exit Signage.		The same of the sa	
	Overhead tank capacity. Exit Signage. Provision of Lifts.	10,000 ltrs Required	Provided Provided	MR MR
	 Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. 	10,000 ltrs Required -NA-	Provided Provided -NA-	MR MR -NA-
	 Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. 	10,000 ltrs Required -NANA-	Provided Provided -NANA-	MR MR -NA-
	Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car.	10,000 ltrs Required -NANANA-	Provided Provided -NANANA-	MR MR -NA- -NA-
	Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch.	10,000 ltrs Required -NANANANA-	Provided Provided -NANANANA-	MR MR -NA- -NA- -NA-
16.	 Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. 	-NANANANANANA-	Provided Provided -NANANANANA-	MR MR -NANANANANANANANA
16. 17.	 Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply 	10,000 ltrs Required -NANANANA-	Provided Provided -NANANANA-	MR MR -NA- -NA- -NA-
15. 16. 17. 18.	Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area	10,000 ltrs Required -NANANANANANANA-	Provided Provided -NANANANANANA-	MR MR -NANANANANA-
16. 17.	Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area Total area	10,000 ltrs Required -NANANANANANANA-	Provided Provided -NANANANANANANAN	MR MR -NANANANANANA-
16. 17. 18.	Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area Total area Location	10,000 ltrs Required -NANANANANANANA-	Provided Provided -NANANANANANA-	-NA- -NA- -NA- -NA- -NA- -NA-
16. 17.	Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage. Standby Power Supply Refuge Area Total area	10,000 ltrs Required -NANANANANANANA-	Provided Provided -NANANANANANANAN	MR MR -NA- -NA- -NA- -NA- -NA-

	 Flow switch panel. 	-NA-	-NA-	-NA-
and the same	 PA system panel. 	-NA-	-NA-	-NA-
	 Battery backup. 	-NA-	-NA-	-NA-
	Building floor plan.	-NA-	-NA-	-NA-
20.	Special Fire Protection System for the Protection of special Risk, if any.	-NA-	-NA-	-NA-

The Fire protection systems provided in the building were test checked at random and found functional at the time of inspection.

Further, the party has complied all the observation / Shortcoming already issued & communicated by this department vide letter of even no 156 dated 26/03/2021

Keeping in view of the substantially satisfactory compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, it is recommended to issue Fire Safety Certificate under rule 35 (3) of the Delhi Fire Service Rules, 2010.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

Recombed for F.S.1.

approved F.T. Lettel el