GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No. F.6/DFS/MS/Indl./SZ/2021/ 356

Dated : 26 / 07/2021

FIRE SAFETY CERTIFICATE

Certified that M/s Supreme Impex Industrial building at S-59, Okhla, Industrial Area, Phase-II, New Delhi-110020 comprised of Basement, Ground floor + three upper floors was issued FSC by this department vide letter no F6/DFS/MS/Indl./2014/SZ/1467 Dated 26/11/2014. The Premise was re- inspected by the officer concerned of this department on 20/07/2021 in the presence of Sh. Ashok Kumar and found that said Industrial building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and found that the said building / premises is fit for occupancy class G "Industrial Building" with effect from 26/07 /2021 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .. 2.6) 0.7/202.\.. at New Delhi by

(SUNIL CHAWDHARY) DY. CHIEF FIRE OFFICER (SZ)

Copy to:

- 1. The Auth. Signatory, Supreme Impex Industrial building at S-59, Okhla, Industrial Area, Phase-II, New Delhi-110020
- 2. The Executive Engineer (Building), HQ, 9th floor, Building department, Civic Center Delhi 110002

Conditions for the validity of the safety certificate:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used strictly as per Building Bye Laws.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1	INSPECTI	ON REPORT				
1	Name & Address of the Building	Supreme Impex, S- 59, Okhla Industrial Area, Ph- I				
	47	New Delhi -110020				
2	Type of Occupancy	Industrial Building				
3	Building Comprised of	Basement, Ground + Three Upper Floors				
4	Type of Case	Renewal				
5	Details of Previous NOC	F6/DFS/MS/Indl./2014/SZ/1467 Dated 26/11/2014				
6	Fire Safety Directives Letter No	Nil				
7	Date of Inspection	20/07/2021				
8	Name of the Inspecting Officers	Sh. Rajesh Kumar, ADO (BCP)				
9	Name & Designation of Officers from the building side	Sh. Ashok Kumar (Manager)				
10	Year of construction	1986				
11	Applicant letter No.	Gmail Dated 13/07/2021				
S. No	Minimum standards on Fire Prevention	BBL/ NBC	Provided at Site	Remarks		
	and Fire Safety U/R 33	requirement		MR/NMR		
1	Access to Building.					
	Road width	14 mtr	Provided	MR		
	Gate width	Required	5 mtr	MR		
	Width of internal road	N/A	N/A	N/A		
2	Number, width, type & arrangement of exits					
	a. Number of Staircase					
	1. Upper floors	2 No's	Provided	MR		
	2. Basement floor	2 No's	Provided	MR		
	b. Width of Staircase					
	1. Upper floors	1.50 m	1.50m & 0.90m	MR (old case		
	2. Basement floor	1.50 m	1.50m & 0.90m	MR (old case		
	c. Protection of exits	1.50 III				
		Did	Provided	MR		
	Fire check door Pressurization	Required N/A	N/A	N/A		
			Provided	MR		
	d. No, of continuous staircase to terrace	01				
	e. Width of corridor	N/A	N/A	N/A		
	f. Door size	Required	Provided	MR		
3	Compartmentation.					
	Fire check door.	Required	Provided	MR		
	Sealing of electrical shafts.	Required	Provided	MR		
	Fire rating of shaft door.	N/A	N/A	N/A		
	Water curtain	N/A	N/A	N/A		
	Fire dampers.	N/A	N/A	N/A		
4.	Smoke Management system.			Park		
	Basement	30 ACPH	Exhaust Fan provided	M/R		
	Upper floors	12 ACPH	Natural ventilation	M/R		
5.	Fire Extinguishers	17	Provided	MR		
	• Total numbers	17	Provided	MR		
	TypesISI Marking	ABC / Co2	Provided	MR		
		ISI Marked	riovided	IVIK		
6.	First Aid Hose Reels.	01 at each floor	Provided	MR		
	Total numbers on each floor. Levels of been real base.	30 m	Provided	MR		
	 Length of hose-reel hose. Nozzle Diameter 	5 mm	Provided	MR		
	Nozzle Diameter	J HIIII	LIOVIGEO	TATE		

	Type of detectors	NA	N/A	NA
	Location of Main Panel	Required	Provided at GF	MR
	Location of Repeater Panel	NA	N/A	NA
*	Alternate source of power	Required	Battery backup	MR
	Hooter's location	All area	Provided	MR
0	MOEFA	Required	Provided	MR
8.		Required	Provided	MR
9.	Public Address System	Required	1101100	
10.	Automatic Sprinkler System	Required	Provided	MR
	Basement	Required	Provided	MR
	• Upper floors (on 2 nd floor)	N/A	N/A	N/A
	Sprinkler above false ceiling	INA	2.112.4	
11.	Internal Hydrants.	100 mm	Provided	MR
	Size of Riser / Down-comer	01	Provided	MR
	Number of Hydrant per floor		Provided	MR
	Hose box.	01	TIOVIGO	11116
12.	Yard Hydrants.	. DT/A	N/A	N/A
	Total number of hydrants.	N/A	N/A N/A	N/A
	Hose box.	N/A	IN/A	INIT
13.	Pumping arrangements.			
	Ground Level	N/A	N/A	N/A
	Discharge of main pump.	N/A	N/A	N/A
	Head of main pump.	N/A	N/A	N/A
	Number of main pumps.	N/A	N/A	N/A
	> Jockey Pump output.	N/A	N/A	N/A
	Jockey Pump head.	N/A	N/A	N/A
	Standby Pump output.Standby Pump head.	N/A	N/A	N/A
	Standby Pump head.Auto Starting / Manual Stopping.	N/A	N/A	N/A
	> Pump House Access	N/A	N/A	N/A
	Discharge of pump.	900 LPM	900 LPM	MR
	Head of pump.	40 mtr	Provided	MR
	Power supply.	Required	Provided (DG Set)	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.			
1.4.	Underground tank capacity.	N/A	N/A	N/A
	> Draw-off connection.	N/A	N/A	N/A
	Fire Service Inlet.	Required	Provided	MR
	Access to tank.	Required	Provided	MR
	Overhead tank capacity.	10,000 Ltrs	Provided	MR
15.	Exit Signage.	Required	Provided	NMR
16.	Provision of Lifts.	Good lift provided		
201	Pressurization of lift shaft.	NA	NA	NA
	 Pressurization of lift lobby. 	NA	NA	NA
	Communication in lift car.	NA	NA	NA
	• Fireman's switch.	NA	NA	NA
	• Lift signage.	NA	NA	NA
17		Required	Provided	MR
18				
10	Total area	NA	NA	NA
	• Location	NA	NA	NA
19			Augustia III an manua	
-	G (P1	Paguired	Provided	MR

	Flow Switch Panel.	N/A	N/A	N/A
1	PA system Panel.	N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
	Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for the Protection of special Risk, if any.	N/A	N/A	N/A

The fire protection system provided in the building were randomly checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/Indl./2014/SZ/1467 Dated 26/11/2014, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar Designation: ADO (BCP)

DO (SP)

F. T. please.

As approved, F.T. retter is putup your synature Pl