

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No. F6/DFS/MS/GH/NDZ/2021/ 286

Dated: 0.4 0 8./2021

FIRE SAFETY CERTIFICATE

Issued on 04 08 2021 at New Delhi by

(Dr. S.K. Tomar) Dy. Chief Fire Officer Tel: 011-23412025

0×10mm

Copy to:-

- 1. The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defense Colony, New Delhi 2021061413827 dated 14.06.2021.
- 2. The Licensee, M/s Hazi Hotel, 914-18, Kabari Bazar, Jama Masjid, Delhi-06

Condition for the validity of fire safety certificate

- 1. This clearance/FSC shall stand cancelled if guest house owner/occupier fails to comply all other conditions mentioned in the gazette notification dated 27.05.2019 and any violation of clarification issued on 25.09.2019 & 17.12.2020 latest by 30.09.2021
- 2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub Rule (I) of Rule 37] along with a copy of this Certificate, six month prior to its expiry". Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained there to before occupancy of the same.

INSPECTION REPORT

1.	Name and address of the building:	M/s Hazi Hotel, 914-18, Kabari Bazar, Jama Masjid, Delhi-06
2.	Type of occupancy with details of floors:	Residential Group A-1 (Ground + 02 upper floors) Ground floor- commercial use, 1 st floor - reception + 07 guest rooms, 2 nd floor- 02 guest rooms,
3.	Type of case:	Renewal case
4.	Details of previous FSC: F6/DFS/MS/GH/2017/NDZ/1533 dated 24.10.2017 Fire safety directives no.: NA	
5.		
6.	Date of inspection:	23.07.2021
7.	Name of the inspecting officer:	DO Rajinder Atwal, ADO Ravinder Singh (CC)
8.	Name and designation of the officer from the building side:	Manager
9.	Year of construction:	1938
10.	Reference letter no.:	Online application I.D. 2021061413827 dated 14.06.202

S,No	1	inimum standard of Fire evention and Fire Safety U/R 33	Requirements (Existing Fire & Safety Measures)	Provide at site (PSS)	Remarks MR/NMR		
1	Ac	cess to Building					
	A	Road width	NA	14 m	MR		
	B	Gate width	NA	NA	NA		
	C	Width of internal roads	NA	NA	NA		
2	Number, Width, Type & Arrangement of Exits						
	A No. of Staircase:						
		a) Upper Floor	01 No	02 No	MR		
		b) Basements	NA	NA :	NA		
	В	Width of the Staircase:			1		
		a) Upper floors	80 cms	90 cms, 95 cms	MR		
		b) Basements	NA	NA	NA		
	C Protection of Exits						
		a) Fire Check Door	NA	NA	NA		
		b) Pressurization	NA	NA	NA		
	D	No. Of continuous staircase to terrace:	01 No	01 No	MR		
	F	Width of the corridor	NA	NA ,	NA		
	E	Door size	1 m	1m	MR		
3	Compartmentation:						
	A	Fire Check doors	NA	NA	NA		
	B	Sealing of Electrical Shafts	NA	NA	NA		
	C	Fire rating of shaft Doors	NA	NA	NA		
	D	Water curtain	NA	NA	NA		
	E	Fire dampers	NA	NA	NA		
4	8						
	A	Upper floors	Natural/Mechanical	Natural	MR		
	В	Basements	NA	NA	NA		
5	Fire extinguishers						
The same of the sa	A	Total numbers	05 no.	08 no.	MR		
	В	Types	CO2, ABC	CO2, ABC	MR		
	C	ISI marking	Required	Provided	MR		



		who	0		
6	Fire	st Aid Hose reel			
	A	Total no. at each floor	01 No	0 1No at 1 st floor only	MR
	В	Length of Hose Reel	30 mtrs	30 mtrs	MR
	C	Nozzle diameter	5 mm	5 mm	MR
7	Aut	omatic Fire Detection and Alarm S	System (ADAS)	· · · · · · · · · · · · · · · · · · ·	
	A	Type of Detectors -(CO) detector	CO detectors (required as per point no. viii of GN dated 27.05.2019)	Not Provided	Last date of compliance extended till 30.09.2021 vide order dated 29.06.2021
	В	Location of main Panel	NA	NA	NA
	C	Location of Repeater Panel	NA	NA	NA
	D	Alternate power Source	NA	NA	NA
	E	Hooter's location	NA	NA	NA
8	MO	EFA	NA	NA	NA
9	Pub	lic Address System	Required	Provided	MR
10		omatic Sprinkler System	2		
	A	Basement	NA	NA	NA
	В	Upper Floor	NA	NA	NA
	C	Sprinklers above false ceiling	NA	NA	NA
11	Inte	rnal hydrants			
	A	Size of the riser/down comer	NA	NA	NA
	В	No. Of hydrants per floor	NA	NA	NA
	C	Hose box	NA	NA	NA
12	Yar	d Hydrants			
	A	Total no. of hydrants	NA	NA	NA
	В	Hose box	NA	NA	NA
13	Pun	ping arrangements			
	A	Ground Level			
		a) Discharge of main pump	NA	NA	NA
		b) Head of main pump	NA	NA	NA
		c) Number of main pump	NA	NA	NA
		d) Discharge of jockey pump	NA	NA	NA
		d) Discharge of Joekey pump	1471	14/1	
		e) Head of jockey pump	NA	NA	NA
v		f) Discharge of Standby pump	NA	NA	NA
		g) Head of Standby pump	NA	NA	NA
		h) Auto starting/ manual stopping	NA	NA	NA
	В	Terrace Level			
		a) Discharge of terrace pump	225 LPM	225 LPM	MR
		b) Head of terrace pump	40 mtrs	40 mtrs	MR
		c) Alternate power supply	Required	Required	MR
		d) Auto starting of pump	Required	Required	MR
14	Can	tive Water Storage for Fire Fighti		14.14	
-	A	Underground tank capacity	NA	NA	NA
ŀ	B	Draw off connection	NA	NA	NA
		Fire Service Inlet	NA	NA	NA
	C	I II O OOI VIOO IIIIOt		NA	NA
	C	Access to tank	INA	1 4 74 4	14 14 14
	E	Access to tank Overhead tank canacity	NA 2 500 ltrs		MR
15	E D	Overhead tank capacity	2,500 ltrs	2,500 ltrs	MR MR
_	E D Exit	Overhead tank capacity Signage			MR MR
_	E D Exit	Overhead tank capacity Signage vision of lift	2,500 ltrs Required	2,500 ltrs Provided	MR
_	E D Exit Prov	Overhead tank capacity Signage vision of lift Pressurization of lift shaft	2,500 ltrs Required NA	2,500 ltrs Provided NA	MR
_	E D Exit Prov	Overhead tank capacity Signage vision of lift Pressurization of lift shaft Pressurization of lift lobby	2,500 ltrs Required NA NA	2,500 ltrs Provided NA NA	MR NA NA
_	E D Exit Prov A B C	Overhead tank capacity Signage vision of lift Pressurization of lift shaft Pressurization of lift lobby Communication in lift car	2,500 ltrs Required NA NA NA	2,500 ltrs Provided NA NA NA	MR NA NA NA
15 16	E D Exit	Overhead tank capacity Signage vision of lift Pressurization of lift shaft Pressurization of lift lobby	2,500 ltrs Required NA NA	2,500 ltrs Provided NA NA	MR NA NA

18	Refuge Area				
	A	location	NA	NA	NA
	B	Total area	NA	NA	NA
19	Fire Control Room				INA
	A	Fire Detection System panel	NA	NA	NA
	B	Flow switch panel	NA	NA	NA
	C	P A system panel	NA	NA	NA
	D	Battery backup	NA	NA	NA NA
	E	Building floor plan	NA	NA	
20	Special Fire Protection for special risk if any			NA	
		T	T ttilly		NA

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspections.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No. F6/DFS/MS/GH/2017/NDZ/1533 dated 24.10.2017 is recommended to be renewed under Rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name: Rajinder Atwal Designation DO (CD)

Name: Ravinder Singh Designation ADO (CC)

Dy.CFO (NDZ)

F. G. P1.

Q4 2/9/21

rvice *

3/8/21

and Engrishme Please

DY CEO (MOZ)

MSICH